

# AVEZ336M25D16T-F

#### **AVEZ336M25D16T-F Information**





Request a Quote

For Reference Only

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## AVEZ336M25D16T-F Specifications

CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - SMDSeriesAVEZCapacitance33µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency136mA @ 120HzImpedance850 mOhmsLead Spacing-Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.260" L x 0.260" W (6.60mm x 6.60mm)Package / CaseRadial, Can - SMD		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - SMDSeriesAVEZCapacitance33µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency136mA @ 120HzImpedance850 mOhmsLead Spacing-Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.260" L x 0.260" W (6.60mm x 6.60mm)Package / CaseRadial, Can - SMD	Manufacturer Part Number	AVEZ336M25D16T-F
Adminum Electrolytic CapacitorsPackageRadial, Can - SMDSeriesAVEZCapacitance33µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationGeneral PurposeApplicationsSton OhmsRipple Current - Low Frequency136mA @ 120HzImpedance850 mOhmsLead Spacing-Size / Dimension0.248° Dia (6.30mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.260° L x 0.260° W (6.60mm x 6.60mm)Package / CaseRadial, Can - SMD	Manufacturer	Cornell Dubilier Electronics (CDE)
PackageRadial, Can - SMDSeriesAVEZCapacitance33µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationGeneral PurposeApplications360m A@ 120HzRipple Current - Low Frequency136mA @ 120HzImpedance850 mOhmsLead Spacing-Size / Dimension0.248° Dia (6.30mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.260° L x 0.260° W (6.60mm x 6.60mm)Package / CaseRadial, Can - SMD	Category	Capacitors
SeriesAVEZCapacitance33µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency136mA @ 120HzImpedance850 mOhmsLead Spacing-Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.260" L x 0.260" W (6.60mm x 6.60mm)Polaring TypeSurface MountPolaring TypeSurface Mount		Aluminum Electrolytic Capacitors
Capacitance33µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency136mA @ 120HzImpedance850 mOhmsLead Spacing-Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.260" L x 0.260" W (6.60mm x 6.60mm)Mounting TypeRatial, Can - SMD	Package	Radial, Can - SMD
Tolerance±20%Tolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency136mA @ 120HzImpedance850 mOhmsLead Spacing-Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.260" L x 0.260" W (6.60mm x 6.60mm)Pokage / CaseRadial, Can - SMD	Series	AVEZ
Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency136mA @ 120HzImpedance850 mOhmsLead Spacing-Size / Dimension0.217" (5.50mm)Height - Seated (Max)0.210" (5.50mm)Surface Mount Land Size0.260" L x 0.260" W (6.60mm x 6.60mm)Pokage / CaseRadial, Can - SMD	Capacitance	33µF
For the series Resistance)-ESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency136mA @ 120HzImpedance850 mOhmsLead Spacing-Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.260" L x 0.260" W (6.60mm x 6.60mm)Mounting TypeRadial, Can - SMD	Tolerance	±20%
Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency136mA @ 120HzRipple Current - High Frequency170mA @ 100kHzImpedance850 mOhmsLead Spacing-Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.2017" (5.50mm)Surface Mount Land Size0.260" L x 0.260" W (6.60mm x 6.60mm)Mounting TypeRadial, Can - SMD	Voltage - Rated	25V
Operating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency136mA @ 120HzRipple Current - High Frequency170mA @ 100kHzImpedance850 mOhmsLead Spacing-Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.201" (5.50mm)Surface Mount Land Size0.260" L x 0.260" W (6.60mm x 6.60mm)Mounting TypeRadial, Can - SMD	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency136mA @ 120HzRipple Current - High Frequency170mA @ 100kHzImpedance850 mOhmsLead Spacing-Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.260" L x 0.260" W (6.60mm x 6.60mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Lifetime @ Temp.	1000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency136mA @ 120HzRipple Current - High Frequency170mA @ 100kHzImpedance850 mOhmsLead Spacing-Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.260" L x 0.260" W (6.60mm x 6.60mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency136mA @ 120HzRipple Current - High Frequency170mA @ 100kHzImpedance850 mOhmsLead Spacing-Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.260" L x 0.260" W (6.60mm x 6.60mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Polarization	Polar
Ripple Current - High Frequency170mA @ 100kHzImpedance850 mOhmsLead Spacing-Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.260" L x 0.260" W (6.60mm x 6.60mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Applications	General Purpose
Impedance850 mOhmsLead Spacing-Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.260" L x 0.260" W (6.60mm x 6.60mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Ripple Current - Low Frequency	136mA @ 120Hz
Lead Spacing-Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.260" L x 0.260" W (6.60mm x 6.60mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Ripple Current - High Frequency	170mA @ 100kHz
Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.260" L x 0.260" W (6.60mm x 6.60mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Impedance	850 mOhms
Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.260" L x 0.260" W (6.60mm x 6.60mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Lead Spacing	-
Surface Mount Land Size0.260" L x 0.260" W (6.60mm x 6.60mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Size / Dimension	0.248" Dia (6.30mm)
Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Height - Seated (Max)	0.217" (5.50mm)
Package / Case Radial, Can - SMD	Surface Mount Land Size	0.260" L x 0.260" W (6.60mm x 6.60mm)
-	Mounting Type	Surface Mount
Report errors?	Package / Case	Radial, Can - SMD
		Report errors?

E-mail: salesdept@heisener.com

### AVEZ336M25D16T-F Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### AVEZ336M25D16T-F Payment Methods



If you have any question about AVEZ336M25D16T-F, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com