



AYM18DTBD Information

Heisener.com

Part Number AYM18DTBD

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 36POS 0.156

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AYM18DTBD Specifications

Manufacturer Part Number AYM18DTBD Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 18 Number of Positions 36 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Loop Bellows Color Green Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	71 W110D 1 DD Specifications		
Category Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 18 Number of Positions 36 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Loop Bellows Color Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Manufacturer Part Number	AYM18DTBD	
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 18 Number of Positions 36 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Loop Bellows Color Green Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Manufacturer	Sullins Connector Solutions	
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 18 Number of Positions 36 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Loop Bellows Color Green Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Category	Connectors, Interconnects	
Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 18 Number of Positions 36 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Loop Bellows Color Green Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeLoop BellowsColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeLoop BellowsColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Series	-	
Number of Positions/Bay/Row Number of Positions 36 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Loop Bellows Color Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Card Type	Non Specified - Dual Edge	
Number of Positions 36 Card Thickness $0.062"$ (1.57mm)Number of Rows 2 Pitch $0.156"$ (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness $30μin (0.76μm)$ Contact TypeLoop BellowsColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, $0.125"$ (3.18mm) DiaOperating Temperature $-65°C \sim 150°C$	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeLoop BellowsColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Number of Positions/Bay/Row	18	
Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Loop Bellows Color Green Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Number of Positions	36	
Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Loop Bellows Color Green Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Card Thickness	0.062" (1.57mm)	
Features Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Contact Finish Thickness 30μin (0.76μm) Contact Type Loop Bellows Color Green Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Number of Rows	2	
Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeLoop BellowsColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Pitch	0.156" (3.96mm)	
Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μ in $(0.76\mu m)$ Contact Type Loop Bellows Color Green Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125 " $(3.18mm)$ Dia Operating Temperature -65 °C ~ 150 °C	Features	-	
Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μ in $(0.76\mu$ m) Contact Type Loop Bellows Color Green Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125 " $(3.18$ mm) Dia Operating Temperature -65 °C ~ 150 °C	Mounting Type	Through Hole, Right Angle	
Contact Finish Gold Contact Finish Thickness 30μ in $(0.76\mu m)$ Contact Type Loop Bellows Color Green Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125 " $(3.18mm)$ Dia Operating Temperature -65 °C ~ 150 °C	Termination	Solder	
Contact Finish Thickness $30\mu in (0.76\mu m)$ Contact Type Loop Bellows Color Green Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Contact Material	Beryllium Copper	
Contact Type Loop Bellows Color Green Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Contact Finish	Gold	
Color Green Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125 " (3.18mm) Dia Operating Temperature -65 °C ~ 150 °C	Contact Finish Thickness	30μin (0.76μm)	
Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125 " (3.18mm) Dia Operating Temperature -65 °C ~ 150 °C	Contact Type	Loop Bellows	
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Color	Green	
	Flange Feature	Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	
	Operating Temperature	-65°C ~ 150°C	
Report errors a		Report errors	?

AYM18DTBD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AYM18DTBD Payment Methods





















AYM18DTBD Shipping Methods













If you have any question about AYM18DTBD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com