

AZ574Z-E1 Information

Heisener.com

Part Number AZ574Z-E1

Manufacturer Diodes Incorporated

Category Integrated Circuits (ICs)
PMIC - Voltage Reference

Description IC REGULATOR LDO

Package TO-226-2, TO-92-2 (TO-226AC)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AZ574Z-E1 Specifications

Manufacturer Part Number AZ574Z-E1 Manufacturer Diodes Incorporated Category Integrated Circuits (ICs) PMIC - Voltage Reference Package TO-226-2, TO-92-2 (TO-226AC) Series - Reference Type Shunt Output Type Adjustable Voltage - Output (Min/Fixed) 31V Voltage - Output (Max) 35V Current - Output 30mA Tolerance - Temperature Coefficient - Noise - 0.1Hz to 10Hz - Noise - 0.1Hz to 10kHz - Voltage - Input - Current - Supply - Current - Cathode 1.5mA Operating Temperature -20°C ~ 75°C (TA) Mounting Type Through Hole Package / Case TO-226-2, TO-92-2 (TO-226AC) Supplier Device Package TO-92-2		
Category Integrated Circuits (ICs) PMIC - Voltage Reference Package TO-226-2, TO-92-2 (TO-226AC) Series - Reference Type Shunt Output Type Adjustable Voltage - Output (Min/Fixed) 31V Voltage - Output (Max) 35V Current - Output 30mA Tolerance - Temperature Coefficient - Noise - 0.1Hz to 10Hz - Noise - 10Hz to 10kHz - Voltage - Input - Current - Supply - Current - Cathode 1.5mA Operating Temperature -20°C ~ 75°C (TA) Mounting Type Through Hole Package / Case TO-226-2, TO-92-2 (TO-226AC) Supplier Device Package TO-92-2	Manufacturer Part Number	AZ574Z-E1
Package TO-226-2, TO-92-2 (TO-226AC) Series - Reference Type Shunt Output Type Adjustable Voltage - Output (Min/Fixed) 31V Voltage - Output (Max) 35V Current - Output 30mA Tolerance - Temperature Coefficient - Noise - 0.1Hz to 10Hz - Noise - 10Hz to 10kHz - Voltage - Input - Current - Supply - Current - Cathode 1.5mA Operating Temperature -20°C ~ 75°C (TA) Mounting Type Through Hole Package / Case TO-226-2, TO-92-2 (TO-226AC) Supplier Device Package TO-92-2	Manufacturer	Diodes Incorporated
Package TO-226-2, TO-92-2 (TO-226AC) Series - Reference Type Shunt Output Type Adjustable Voltage - Output (Min/Fixed) 31V Voltage - Output (Max) 35V Current - Output 30mA Tolerance - Temperature Coefficient - Noise - 0.1Hz to 10Hz - Noise - 10Hz to 10kHz - Voltage - Input - Current - Supply - Current - Cathode 1.5mA Operating Temperature -20°C ~ 75°C (TA) Mounting Type Through Hole Package / Case TO-226-2, TO-92-2 (TO-226AC) Supplier Device Package TO-92-2	Category	Integrated Circuits (ICs)
Series - Reference Type Shunt Output Type Adjustable Voltage - Output (Min/Fixed) 31V Voltage - Output (Max) 35V Current - Output 30mA Tolerance - Temperature Coefficient - Noise - 0.1Hz to 10Hz - Noise - 10Hz to 10kHz - Voltage - Input - Current - Supply - Current - Cathode 1.5mA Operating Temperature -20°C ~ 75°C (TA) Mounting Type Through Hole Package / Case TO-226-2, TO-92-2 (TO-226AC) Supplier Device Package TO-92-2		PMIC - Voltage Reference
Reference Type Output Type Adjustable Voltage - Output (Min/Fixed) Voltage - Output (Max) 35V Current - Output 30mA Tolerance - Temperature Coefficient Noise - 0.1Hz to 10Hz Noise - 10Hz to 10kHz - Voltage - Input - Current - Supply - Current - Cathode Operating Temperature Mounting Type Through Hole Package / Case TO-92-2 Supplier Device Package	Package	TO-226-2, TO-92-2 (TO-226AC)
Output Type Adjustable Voltage - Output (Min/Fixed) 31V Voltage - Output (Max) 35V Current - Output 30mA Tolerance - Temperature Coefficient - Noise - 0.1Hz to 10Hz Noise - 10Hz to 10kHz - Voltage - Input - Current - Supply - Current - Cathode 1.5mA Operating Temperature - 20°C ~ 75°C (TA) Mounting Type Package / Case TO-226-2, TO-92-2 (TO-226AC) Supplier Device Package	Series	-
Voltage - Output (Min/Fixed) Voltage - Output (Max) 35V Current - Output 30mA Tolerance - Temperature Coefficient Noise - 0.1Hz to 10Hz Noise - 10Hz to 10kHz Voltage - Input - Current - Supply - Current - Cathode 1.5mA Operating Temperature -20°C ~ 75°C (TA) Mounting Type Package / Case TO-226-2, TO-92-2 (TO-226AC) Supplier Device Package	Reference Type	Shunt
Voltage - Output (Max) Current - Output 30mA Tolerance - Temperature Coefficient Noise - 0.1Hz to 10Hz Noise - 10Hz to 10kHz Voltage - Input - Current - Supply Current - Cathode Operating Temperature Mounting Type Package / Case TO-226-2, TO-92-2 (TO-226AC) Supplier Device Package	Output Type	Adjustable
Current - Output Tolerance - Temperature Coefficient - Noise - 0.1Hz to 10Hz - Noise - 10Hz to 10kHz - Voltage - Input - Current - Supply - Current - Cathode 0perating Temperature -20°C ~ 75°C (TA) Mounting Type Through Hole Package / Case TO-226-2, TO-92-2 (TO-226AC) Supplier Device Package 700000000000000000000000000000000000	Voltage - Output (Min/Fixed)	31V
Tolerance - Coefficient - Coefficient - Course - 0.1Hz to 10Hz - Course - 10Hz to 10kHz - Course - Input - Current - Supply - Current - Cathode 1.5mA - 20°C ~ 75°C (TA) - Coefficient - Case - Coefficient - Coeffi	Voltage - Output (Max)	35V
Temperature Coefficient Noise - 0.1Hz to 10Hz Noise - 10Hz to 10kHz - Voltage - Input - Current - Supply - Current - Cathode Operating Temperature Mounting Type Package / Case TO-226-2, TO-92-2 (TO-226AC) Supplier Device Package	Current - Output	30mA
Noise - 0.1Hz to 10Hz Noise - 10Hz to 10kHz - Voltage - Input - Current - Supply - Current - Cathode Operating Temperature Package / Case TO-226-2, TO-92-2 (TO-226AC) Supplier Device Package	Tolerance	-
Noise - 10Hz to 10kHz Voltage - Input Current - Supply Current - Cathode 1.5mA Operating Temperature -20°C ~ 75°C (TA) Mounting Type Through Hole Package / Case TO-226-2, TO-92-2 (TO-226AC) Supplier Device Package	Temperature Coefficient	-
Voltage - Input Current - Supply - Current - Cathode 1.5mA Operating Temperature -20°C ~ 75°C (TA) Mounting Type Through Hole Package / Case TO-226-2, TO-92-2 (TO-226AC) Supplier Device Package	Noise - 0.1Hz to 10Hz	-
Current - Supply - Current - Cathode 1.5mA Operating Temperature -20°C ~ 75°C (TA) Mounting Type Through Hole Package / Case TO-226-2, TO-92-2 (TO-226AC) Supplier Device Package TO-92-2	Noise - 10Hz to 10kHz	-
Current - Cathode 1.5mA Operating Temperature -20°C ~ 75°C (TA) Mounting Type Through Hole Package / Case TO-226-2, TO-92-2 (TO-226AC) Supplier Device Package TO-92-2	Voltage - Input	-
Operating Temperature -20°C ~ 75°C (TA) Mounting Type Through Hole Package / Case TO-226-2, TO-92-2 (TO-226AC) Supplier Device Package TO-92-2	Current - Supply	-
Mounting Type Through Hole Package / Case TO-226-2, TO-92-2 (TO-226AC) Supplier Device Package TO-92-2	Current - Cathode	1.5mA
Package / Case TO-226-2, TO-92-2 (TO-226AC) Supplier Device Package TO-92-2	Operating Temperature	-20°C ~ 75°C (TA)
Supplier Device Package TO-92-2	Mounting Type	Through Hole
	Package / Case	TO-226-2, TO-92-2 (TO-226AC)
Report errors?	Supplier Device Package	TO-92-2
		Report errors?

AZ574Z-E1 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AZ574Z-E1 Payment Methods





















AZ574Z-E1 Shipping Methods













If you have any question about AZ574Z-E1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com