



B07D034BC2-0053 Information



For Reference Only

Part Number B07D034BC2-0053

Manufacturer TE Connectivity Aerospace, Defense and Marine

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 10A 26.5V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B07D034BC2-0053 Specifications

Manufacturer Part NumberB07D034BC2-0053ManufacturerTE Connectivity Aerospace, Defense and MarineCategoryRelaysPackage-SeriesMilitary, MIL-R-5757/23, 07, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current88.3mACoil Voltage26.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)13 VDCTurn Off Voltage (Min)2.3 VDCOperate Time15msRelease Time15msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesMilitary, MIL-R-5757/23, 07, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current88.3mACoil Voltage26.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)13 VDCTurn Off Voltage (Min)2.3 VDCOperate Time15msRelease Time15msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	B07D034BC2-0053
Package-SeriesMilitary, MIL-R-5757/23, 07, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current88.3mACoil Voltage26.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)13 VDCTurn Off Voltage (Min)2.3 VDCOperate Time15msRelease Time15msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	TE Connectivity Aerospace, Defense and Marine
Package-SeriesMilitary, MIL-R-5757/23, 07, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current88.3mACoil Voltage26.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)13 VDCTurn Off Voltage (Min)2.3 VDCOperate Time15msRelease Time15msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesMilitary, MIL-R-5757/23, 07, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current88.3mACoil Voltage26.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)13 VDCTurn Off Voltage (Min)2.3 VDCOperate Time15msRelease Time15msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current88.3mACoil Voltage26.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)13 VDCTurn Off Voltage (Min)2.3 VDCOperate Time15msRelease Time15msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil Type Non Latching Coil Current 88.3mA Coil Voltage 26.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 13 VDC Turn Off Voltage (Min) 2.3 VDC Operate Time 15ms Release Time 15ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Series	Military, MIL-R-5757/23, 07, CII
Coil Current 88.3mA Coil Voltage 26.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 13 VDC Turn Off Voltage (Min) 2.3 VDC Operate Time 15ms Release Time 15ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 26.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 13 VDC Turn Off Voltage (Min) 2.3 VDC Operate Time 15ms Release Time 15ms Release Time 15ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 13 VDC Turn Off Voltage (Min) 2.3 VDC Operate Time 15ms Release Time 15ms Release Time Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Coil Current	88.3mA
Contact Rating (Current) Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 13 VDC Turn Off Voltage (Min) 2.3 VDC Operate Time 15ms Release Time 15ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Coil Voltage	26.5VDC
Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 13 VDC Turn Off Voltage (Min) 2.3 VDC Operate Time 15ms Release Time 15ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 13 VDC Turn Off Voltage (Min) 2.3 VDC Operate Time 15ms Release Time 15ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Contact Rating (Current)	10A
Turn Off Voltage (Min) Operate Time 15ms Release Time 15ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	115VAC, 28VDC - Max
Operate Time 15ms Release Time 15ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	13 VDC
Release Time 15ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	2.3 VDC
Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Operate Time	15ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	15ms
Termination Style PC Pin	Features	Sealed - Hermetically
·	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

B07D034BC2-0053 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B07D034BC2-0053 Payment Methods



















B07D034BC2-0053 Shipping Methods













If you have any question about B07D034BC2-0053, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com