

### **B23LB Information**



For Reference Only

Part Number B23LB

Manufacturer NKK Switches

Category Switches
Toggle Switches

**Description** SWITCH TOGGLE DPDT 0.4VA 28V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **B23LB Specifications**

Manufacturer Part Number         B23LB           Manufacturer         NKK Switches           Category         Switches           Package         -           Series         B           Circuit         DPDT           Switch Function         On-Off-On           Current Rating         0.4VA (AC/DC)           Voltage Rating - AC         28V           Voltage Rating - DC         28V           Actuator Type         Locking Lever           Actuator Length         12.50mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Mounting Type         Through Hole           Termination Style         PC Pin           Panel Cutout Dimensions         -           Bushing Thread         Unthreaded           Ingress Protection         -           Features         Epoxy Sealed Terminals		
CategorySwitchesPackage-SeriesBCircuitDPDTSwitch FunctionOn-Off-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC28VVoltage Rating - DC28VActuator TypeLocking LeverActuator Length12.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer Part Number	B23LB
Package - Series B B SCITUTE ON THE PROPERTY OF THE PACKAGE OF THE	Manufacturer	NKK Switches
Package-SeriesBCircuitDPDTSwitch FunctionOn-Off-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC28VVoltage Rating - DC28VActuator TypeLocking LeverActuator Length12.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Category	Switches
SeriesBCircuitDPDTSwitch FunctionOn-Off-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC28VVoltage Rating - DC28VActuator TypeLocking LeverActuator Length12.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals		Toggle Switches
CircuitDPDTSwitch FunctionOn-Off-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC28VVoltage Rating - DC28VActuator TypeLocking LeverActuator Length12.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Package	-
Switch Function On-Off-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 28V Voltage Rating - DC 28V Actuator Type Locking Lever Actuator Length 12.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Series	В
Current Rating  Voltage Rating - AC  28V  Voltage Rating - DC  28V  Actuator Type  Actuator Length  Illumination  Illumination  Illumination Type, Color  Illumination Voltage (Nominal)  Mounting Type  Termination Style  Panel Cutout Dimensions  Bushing Thread  Ingress Protection  Features  0.4VA (AC/DC)  28V  Locking Lever  Locking Lever  12.50mm  Non-Illuminated  Illuminated  12.50mm  Non-Illuminated  12	Circuit	DPDT
Voltage Rating - AC28VVoltage Rating - DC28VActuator TypeLocking LeverActuator Length12.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Switch Function	On-Off-On
Voltage Rating - DC Actuator Type Locking Lever Actuator Length 12.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Through Hole Termination Style Panel Cutout Dimensions - Bushing Thread Ingress Protection Features Epoxy Sealed Terminals	Current Rating	0.4VA (AC/DC)
Actuator Type Actuator Length 12.50mm Illumination Non-Illuminated Illumination Type, Color	Voltage Rating - AC	28V
Actuator Length 12.50mm  Illumination Non-Illuminated  Illumination Type, Color -  Illumination Voltage (Nominal) -  Mounting Type Through Hole  Termination Style PC Pin  Panel Cutout Dimensions -  Bushing Thread Unthreaded  Ingress Protection -  Features Epoxy Sealed Terminals	Voltage Rating - DC	28V
Illumination Non-Illuminated  Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole Termination Style PC Pin  Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Actuator Type	Locking Lever
Illumination Type, Color  Illumination Voltage (Nominal)  Mounting Type  Through Hole  PC Pin  Panel Cutout Dimensions  -  Bushing Thread  Ingress Protection  Features  Features  -  Epoxy Sealed Terminals	Actuator Length	12.50mm
Illumination Voltage (Nominal)  Mounting Type Through Hole Termination Style PC Pin  Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting Type Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Illumination Type, Color	-
Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Mounting Type	Through Hole
Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Termination Style	PC Pin
Ingress Protection - Epoxy Sealed Terminals	Panel Cutout Dimensions	-
Features Epoxy Sealed Terminals	Bushing Thread	Unthreaded
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

### **B23LB Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **B23LB Payment Methods**





















## **B23LB Shipping Methods**













If you have any question about B23LB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com