

# B32232A1684K

#### B32232A1684K Information

www.theisener.com	Part Number Manufacturer Category Description Package	B32232A1684K EPCOS (TDK) Capacitors Film Capacitors CAP FILM 0.68UF 10% 100VDC AXIAL Axial For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### **B32232A1684K Specifications**

Manufacturer Part NumberB32232A 1684KManufacturerEPCOS (TDK)CategoryCapacitorsFilm CapacitorsFilm CapacitorsPackageAxialSeriesB32232Capacitance0.68µFTolerance10%Voltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedPorating Temperature-Mounting TypeAxialSize / DimensionAxialHeight - Seated (Max)5.76° (Dia x 0.748° L (7.00mm x 19.00mm)Height - Seated (Max)-		
CategoryCapacitorsFilm CapacitorsPackageAxialSeriesB32232Capacitance0.68µFYoltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedESR (Equivalent Series Resistance)-Operating Type40°C ~ 100°CMounting TypeAxialSize / Dimension0.276" Dia x 0.748" L (7.00mm x 19.00mm)	Manufacturer Part Number	B32232A1684K
Film CapacitorsPackageAxialSeriesB32232Capacitance0.68µFTolerance±10%Voltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedESR (Equivalent Series Resistance)-Operating TypeHrough HolePackage / CaseAxialSize / Dimension0.276" Dia x 0.748" L (7.00mm x 19.00mm)	Manufacturer	EPCOS (TDK)
PackageAxialPackageB32232Capacitance0.68µFTolerance±10%Voltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedESR (Equivalent Series Resistance)-Operating Type-40°C ~100°CMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.276° Diax 0.748° L (7.00mm x 19.00mm)	Category	Capacitors
SeriesB32232Capacitance0.68μFTolerance±10%Voltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 100°CMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.276" Dia x 0.748" L (7.00mm x 19.00mm)		Film Capacitors
Capacitance0.68µFTolerance±10%Voltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedFSR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 100°CMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.276" Diax 0.748" L (7.00mm x 19.00mm)	Package	Axial
Tolerance±10%Voltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 100°CMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.276" Dia x 0.748" L (7.00mm x 19.00mm)	Series	B32232
Voltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 100°CMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.276" Dia x 0.748" L (7.00mm x 19.00mm)	Capacitance	0.68µF
Voltage Rating - DC100VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 100°CMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.276" Diax 0.748" L (7.00mm x 19.00mm)	Tolerance	±10%
Dielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 100°CMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.276" Dia x 0.748" L (7.00mm x 19.00mm)	Voltage Rating - AC	63V
ESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 100°CMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.276" Dia x 0.748" L (7.00mm x 19.00mm)	Voltage Rating - DC	100V
Operating Temperature-40°C ~ 100°CMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.276" Dia x 0.748" L (7.00mm x 19.00mm)	Dielectric Material	Polyester, Polyethylene Terephthalate (PET), Metallized
Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.276" Dia x 0.748" L (7.00mm x 19.00mm)	ESR (Equivalent Series Resistance)	-
Package / CaseAxialSize / Dimension0.276" Dia x 0.748" L (7.00mm x 19.00mm)	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 100^{\circ}\mathrm{C}$
Size / Dimension 0.276" Dia x 0.748" L (7.00mm x 19.00mm)	Mounting Type	Through Hole
	Package / Case	Axial
Height - Seated (Max) -	Size / Dimension	0.276" Dia x 0.748" L (7.00mm x 19.00mm)
	Height - Seated (Max)	-
Termination PC Pins	Termination	PC Pins
Lead Spacing -	Lead Spacing	-
Applications EMI, RFI Suppression	Applications	EMI, RFI Suppression
Features -	Features	-
Report errors'		Report errors

#### B32232A1684K Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## B32232A1684K Payment Methods





If you have any question about B32232A1684K, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com