

B32520C6223K000

B32520C6223K000 Information



Part Number	B32520C6223K000
Manufacturer	EPCOS (TDK)
Category	Capacitors Film Capacitors
Description	CAP FILM 0.022UF 10% 400VDC RAD
Package	Radial
	For the pricing/inventory/lead time, please contact
	us
	Website: https://www.heisener.com
	E-mail: salesdept@heisener.com



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B32520C6223K000 Specifications

Manufacturer Part NumberB32520C6223K000ManufacturerEPCOS (TDK)CategoryCapacitorsFilm CapacitorsFilm CapacitorsPackageRadialSeriesB32520Capacitance0.022µFTolerance±10%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedFSR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HoleSize / Dimension0.394" L x 0.157" W (10.00mm x 4.00mm)Height - Seated (Max)0.35" (8.50mm)Lead Spacing0.295" (7.50mm)ApplicationsAutomotive; EMI, RFI SuppressionAutomotive; EMI, RFI SuppressionEmeretor			
CategoryCapacitorsFalm CapacitorsPackageRadialSeriesB3250Capacitance0.022µFTolerance10%Voltage Rating - AC00VVoltage Rating - BC0.00VVoltage Rating - BC0.00VDielectric Material0.00VForeing Temperature-Operating Type-55°C ~ 125°CMounting Type55°C ~ 125°CNouting TypeGalaiSize / Dimension0.394" L x 0.157" W (1.00mm x 4.00mm)Field - Saacd (Max)0.335" (8.50mm)Height - Seated (Max)0.295" (7.50mm)ApplicationsAutomotive; EMI, RFI SuppressionFeatures-	Manufacturer Part Number	B32520C6223K000	
Film CapacitorsPackageRadialSeriesB32520Capacitance0.022µFTolerance±10%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.394" L x 0.157" W (10.00mm x 4.00mm)Height - Seated (Max)0.335" (8.50mm)Lead Spacing0.295" (7.50mm)ApplicationsAutomotive; EMI, RFI SuppressionFeatures-	Manufacturer	EPCOS (TDK)	
PackageRadialSeriesB32520Capacitance0.022µFTolerance±10%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.335" (8.50mm)Height - Seated (Max)0.335" (8.50mm)Lead Spacing0.295" (7.50mm)ApplicationsAutomotive; EMI, RFI SuppressionFeatures-	Category	Capacitors	
SeriesB32520SeriesB32520Capacitance0.022µFTolerance±10%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.394" L x 0.157" W (10.00mm x 4.00mm)Height - Seated (Max)0.335" (8.50mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsAutomotive; EMI, RFI SuppressionFeatures-		Film Capacitors	
Capacitance0.022μFTolerance±10%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedDielectric Material-Operating Temperature-55°C ~ 125°CMounting TypeRadialPackage / CaseRadialSize / Dimension0.394" L x 0.157" W (10.00mm x 4.00mm)Height - Seated (Max)0.335" (8.50mm)FerminationPC PinsApplicationsAutomotive; EMI, RFI SuppressionFeatures-	Package	Radial	
Tolerance±10%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeHrough HolePackage / CaseRadialSize / Dimension0.394" L x 0.157" W (10.00mm x 4.00mm)Height - Seated (Max)0.335" (8.50mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsAutomotive; EMI, RFI SuppressionFeatures-	Series	B32520	
Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.394" L x 0.157" W (10.00mm x 4.00mm)Height - Seated (Max)0.335" (8.50mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsAutomotive; EMI, RFI SuppressionFeatures-	Capacitance	0.022µF	
Voltage Rating - DC400VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.394" L x 0.157" W (10.00mm x 4.00mm)Height - Seated (Max)0.335" (8.50mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsAutomotive; EMI, RFI SuppressionFeatures-	Tolerance	±10%	
Dielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.394" L x 0.157" W (10.00mm x 4.00mm)Height - Seated (Max)0.335" (8.50mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsAutomotive; EMI, RFI SuppressionFeatures-	Voltage Rating - AC	200V	
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.394" L x 0.157" W (10.00mm x 4.00mm)Height - Seated (Max)0.335" (8.50mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsAutomotive; EMI, RFI SuppressionFeatures-	Voltage Rating - DC	400V	
Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.394" L x 0.157" W (10.00mm x 4.00mm)Height - Seated (Max)0.335" (8.50mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsAutomotive; EMI, RFI SuppressionFeatures-	Dielectric Material	Polyester, Polyethylene Terephthalate (PET), Metallized - Stacked	
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension0.394" L x 0.157" W (10.00mm x 4.00mm)Height - Seated (Max)0.335" (8.50mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsAutomotive; EMI, RFI SuppressionFeatures-	ESR (Equivalent Series Resistance)	-	
Package / CaseRadialSize / Dimension0.394" L x 0.157" W (10.00mm x 4.00mm)Height - Seated (Max)0.335" (8.50mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsAutomotive; EMI, RFI SuppressionFeatures-	Operating Temperature	-55°C ~ 125°C	
Size / Dimension0.394" L x 0.157" W (10.00mm x 4.00mm)Height - Seated (Max)0.335" (8.50mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsAutomotive; EMI, RFI SuppressionFeatures-	Mounting Type	Through Hole	
Height - Seated (Max)0.335" (8.50mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsAutomotive; EMI, RFI SuppressionFeatures-	Package / Case	Radial	
TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsAutomotive; EMI, RFI SuppressionFeatures-	Size / Dimension	0.394" L x 0.157" W (10.00mm x 4.00mm)	
Lead Spacing0.295" (7.50mm)ApplicationsAutomotive; EMI, RFI SuppressionFeatures-	Height - Seated (Max)	0.335" (8.50mm)	
ApplicationsAutomotive; EMI, RFI SuppressionFeatures-	Termination	PC Pins	
Features -	Lead Spacing	0.295" (7.50mm)	
	Applications	Automotive; EMI, RFI Suppression	
Depart emerge	Features	-	
Report errors			Report errors?

B32520C6223K000 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B32520C6223K000 Payment Methods





If you have any question about B32520C6223K000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com