

B32521N8223J189

B32521N8223J189 Information



umber	B32521N8223J189	
acturer	EPCOS (TDK)	
ory	Capacitors Film Capacitors	
ption	CAP FILM 0.022UF 5% 630VDC RAD	
ge	Radial	
	For the pricing/inventory/lead time, please contact	
	us	
	Website: https://www.heisener.com	
	E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B32521N8223J189 Specifications

Manufacturer Part NumberB32521N8223J189ManufacturerEPCOS (TDK)CategoryCapacitorsPackageRadialSeriesB32521Capacitance0.022µFTolerance±5%Voltage Rating - AC200VVoltage Rating - DC630VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedPorting Temperature-55°C ~ 125°CMounting TypeRadialSize / Dimension-File CaseRadialSize / Dimension-Height - Seated (Max)-TerninationPC PinsLead Spacing0.394" (10.00mm)AvanticationsMutorative: EML PEI Sumpression			
CategoryCapacitorsFilm CapacitorsPackageRadialSeriesB32521Capacitance0.022µFTolerance±5%Voltage Rating - AC000Voltage Rating - DC630VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedFSR (Equivalent Series Resistance)-Operating Temperature55°C ~ 125°CNouning TypeRadialSize / Dimension-Keiget / CaseRadialHeight - Seated (Max)-Height - Seated (Max)02 PrinsLead Spacing0.394" (10.00mm)	Manufacturer Part Number	B32521N8223J189	
Hin CapacitorsPackageRadialSeriesB32521Capacitance0.022µFTolerance±5%Voltage Rating - AC200VVoltage Rating - DC630VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedESR (Equivalent Series Resistance)-Operating Tupperaturerhough HolePackage / CaseRadialSize / Dimension-Height - Seated (Max)-Lead Spacing0.394" (10.00mm)	Manufacturer	EPCOS (TDK)	
PackageRadialSeriesB32521Capacitance0.022µFTolerance±5%Voltage Rating - AC200VVoltage Rating - DC630VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedESR (Equivalent Series Resistance)-Operating Type55°C ~ 125°CMounting TypeRadialPackage / CaseRadialSize / Dimension-Height - Seated (Max)-Height - Seated (Max)0.021°CLead Spacing0.394" (10.00mm)	Category	Capacitors	
SeriesB3251Capacitance0.022µFTolerance±5%Voltage Rating - AC200VVoltage Rating - DC630VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeRadialSize / Dimension-Height - Seated (Max)-TerminationPC PinsLead Spacing0.394" (10.00mm)		Film Capacitors	
Capacitance0.022µFTolerance±5%Voltage Rating - AC00VVoltage Rating - DC630VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeRadialSize / Dimension-Keight - Seated (Max)-TerminationPC PinsLead Spacing0.394" (10.00mm)	Package	Radial	
Tolerance±5%Yoltage Rating - AC200VVoltage Rating - DC630VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension-Height - Seated (Max)-TerminationPC PinsLead Spacing0.394" (10.00mm)	Series	B32521	
Voltage Rating - AC200VVoltage Rating - DC630VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension-Height - Seated (Max)-PerminationPC PinsLead Spacing0.394" (10.00mm)	Capacitance	0.022µF	
Voltage Rating - DC630VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension-Height - Seated (Max)-TerminationPC PinsLead Spacing0.394" (10.00mm)	Tolerance	±5%	
Dielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension-Height - Seated (Max)-TerminationPC PinsLead Spacing0.394" (10.00mm)	Voltage Rating - AC	200V	
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension-Height - Seated (Max)-TerminationPC PinsLead Spacing0.394" (10.00mm)	Voltage Rating - DC	630V	
Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension-Height - Seated (Max)-TerminationPC PinsLead Spacing0.394" (10.00mm)	Dielectric Material	Polyester, Polyethylene Terephthalate (PET), Metallized	
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension-Height - Seated (Max)-TerminationPC PinsLead Spacing0.394" (10.00mm)	ESR (Equivalent Series Resistance)	-	
Package / CaseRadialSize / Dimension-Height - Seated (Max)-TerminationPC PinsLead Spacing0.394" (10.00mm)	Operating Temperature	-55°C ~ 125°C	
Size / Dimension-Height - Seated (Max)-TerminationPC PinsLead Spacing0.394" (10.00mm)	Mounting Type	Through Hole	
Height - Seated (Max)-TerminationPC PinsLead Spacing0.394" (10.00mm)	Package / Case	Radial	
TerminationPC PinsLead Spacing0.394" (10.00mm)	Size / Dimension	-	
Lead Spacing 0.394" (10.00mm)	Height - Seated (Max)	-	
	Termination	PC Pins	
Applications Automotive: EMI REI Suppression	Lead Spacing	0.394" (10.00mm)	
Automotive, Ewil, Kri Suppression	Applications	Automotive; EMI, RFI Suppression	
Features -	Features	-	
Report errors?			Report errors?

B32521N8223J189 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B32521N8223J189 Payment Methods



B32521N8223J189 Shipping Methods



If you have any question about B32521N8223J189, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com