

B32529C1683K000

B32529C1683K000 Information

	Part Number Manufacturer Category Description Package	Capacitors Film Capacitors CAP FILM 0.068UF 10% 100VDC RAD Radial For the pricing/inventory/lead time, please contact	
For Reference O	Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B32529C1683K000 Specifications

Manufacturer Part NumberB32529C1683K000ManufacturerEPCOS (TDK)CategoryCapacitorsPackageFilm CapacitorsPackageRadialSeriesB32529Capacitance0.068µFTolerance410%Voltage Rating - AC63VVoltage Rating - DC100VDielectric Material-Portanting Temperature-Operating Temperature-Package / CaseRadialSize / Dimension-Size / Dimension-Height - Seated (Max)0.256" (6.50mm)Fernination-Portantion-Dielectif Material0.256" (6.50mm)Package / Case0.256" (6.50mm)Package / Case0.256" (6.50mm)Package / Max-Package / Max-Package / Max-Package / Max-Package / Case-Package / Case-Pa			
CategoryCapacitorsFilm CapacitorsPackageRadialSeriesB32529Capacitance0.068µFTolerance±10%Voltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedPoprating Temperature-55°C ~ 125°CMounting TypeThrough HoleSize / Dimension0.283° L x 0.098° W (7.20mm x 2.50mm)Height - Seated (Max)0.256° (6.50mm)PerminationPC Pins	Manufacturer Part Number	B32529C1683K000	
Film CapacitorsPackageRadialSeriesB32529Capacitance0.068µFTolerance±10%Voltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.283" L x 0.098" W (7.20mm x 2.50mm)Height - Seated (Max)DC Fins	Manufacturer	EPCOS (TDK)	
PackageRadialPackageB32529Capacitance0.068µFTolerance±10%Voltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating TypeStor 2125°CMounting TypeRadialPackage / CaseRadialSize / Dimension0.283° L x 0.098° W (7.20mm x 2.50mm)Height - Seated (Max)PC Pins	Category	Capacitors	
SeriesB32529Capacitance0.068µFTolerance±10%Voltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeRadialPackage / CaseRadialSize / Dimension0.258" L x 0.098" W (7.20mm x 2.50mm)Height - Seated (Max)PC Pins		Film Capacitors	
Capacitance0.068µFTolerance±10%Voltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedDierating Temperature-Operating Type-55°C ~ 125°CMounting TypeRadialPackage / CaseRadialSize / Dimension0.283" L x 0.098" W (7.20mm x 2.50mm)Height - Seated (Max)OP ins	Package	Radial	
Tolerance±10%Voltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.283" L x 0.098" W (7.20mm x 2.50mm)Height - Seated (Max)0.256" (6.50mm)TerminationPC Pins	Series	B32529	
Voltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.283" L x 0.098" W (7.20mm x 2.50mm)Height - Seated (Max)0.256" (6.50mm)PC PinsPC Pins	Capacitance	0.068µF	
Voltage Rating - DC100VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.283" L x 0.098" W (7.20mm x 2.50mm)Height - Seated (Max)0.256" (6.50mm)TerminationPC Pins	Tolerance	±10%	
Dielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.283" L x 0.098" W (7.20mm x 2.50mm)Height - Seated (Max)0.256" (6.50mm)TerminationPC Pins	Voltage Rating - AC	63V	
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.283" L x 0.098" W (7.20mm x 2.50mm)Height - Seated (Max)0.256" (6.50mm)TerminationPC Pins	Voltage Rating - DC	100V	
Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.283" L x 0.098" W (7.20mm x 2.50mm)Height - Seated (Max)0.256" (6.50mm)TerminationPC Pins	Dielectric Material	Polyester, Polyethylene Terephthalate (PET), Metallized - Stacked	
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.283" L x 0.098" W (7.20mm x 2.50mm)Height - Seated (Max)0.256" (6.50mm)TerminationPC Pins	ESR (Equivalent Series Resistance)	-	
Package / CaseRadialSize / Dimension0.283" L x 0.098" W (7.20mm x 2.50mm)Height - Seated (Max)0.256" (6.50mm)TerminationPC Pins	Operating Temperature	-55°C ~ 125°C	
Size / Dimension 0.283" L x 0.098" W (7.20mm x 2.50mm) Height - Seated (Max) 0.256" (6.50mm) Termination PC Pins	Mounting Type	Through Hole	
Height - Seated (Max)0.256" (6.50mm)TerminationPC Pins	Package / Case	Radial	
Termination PC Pins	Size / Dimension	0.283" L x 0.098" W (7.20mm x 2.50mm)	
	Height - Seated (Max)	0.256" (6.50mm)	
	Termination	PC Pins	
Lead Spacing 0.197" (5.00mm)	Lead Spacing	0.197" (5.00mm)	
Applications Automotive; EMI, RFI Suppression	Applications	Automotive; EMI, RFI Suppression	
Features -	Features	-	
Report errors			Report errors?

B32529C1683K000 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B32529C1683K000 Payment Methods





If you have any question about B32529C1683K000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com