

B32537B8105K

B32537B8105K Information

| Heisener.com | B32537B8105K EPCOS (TDK) Capacitors Film Capacitors CAP FILM 1UF 10% 630VDC AXIAL Axial For the pricing/inventory/lead time, please contact | |
|--------------------|---|-----------------|
| For Reference Only | us Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quote |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B32537B8105K Specifications

| Manufacturer Part Number B32537B8105K Manufacturer EPCOS (TDK) Category Capacitors Film Capacitors Film Capacitors Package Axial Series B32537 Capacitance IµF Tolerance 200V Voltage Rating - AC 200V Voltage Rating - DC 630V Dielectric Material Polyester, Polyethylene Terephthalate (PET), Metallized FSR (Equivalent Series Resistance) - Nouning Type Sto ² ~ 85°C Mouning Type Ofer National Axial Size / Dimension 6.018" Dia x 1.339" L (15.70mm x 34.00mm) Height - Seated (Max) - Lead Spacing - Applications PC Pins Lead Spacing - Applications - Features - | | | |
|---|------------------------------------|---|-------------|
| CategoryCapacitorsFilm CapacitorsPackageAxialSeriesB32537CapacitanceµFTolerance±10%Voltage Rating - AC00VVoltage Rating - BC630VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedPoreating Temperature-5°°C ~ 85°CMounting TypeOtol % Through HolePackage / CaseAxialSize / Dimension0.618° Diax 1.339° L (15.70mm x 34.00mm)Height - Seated (Max)-Lead Spacing-Applications-Features>Features>Applications-Features- </td <td>Manufacturer Part Number</td> <td>B32537B8105K</td> <td></td> | Manufacturer Part Number | B32537B8105K | |
| Init CapacitorsPackageAxialSeriesB32537CapacitanceIµFTolerance10%Voltage Rating - AC300VVoltage Rating - DC630VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedPorating Temperature-Operating TemperatureSto [°] C ~ 85°CMounting TypeHong HoleFackage / CaseAxialHeight - Seated (Max)-Firmination0618" Dia x1.339" L (15.70mm x 34.00mm)Firmination-Applications-Fackage / Gase-Firmination-Firmination-Applications-Firmination-Applications-Fireination-Applications-Fireination-Applications-Fireination-Applications-Fireination-Applications-Fireination-Applications-Fireination-Applications-Fireination-Fireination-Fireination-Applications-Fireination-Fireination-Fireination-Fireination-Fireination-Fireination-Fireination-Fireination-Fireination-Fireina | Manufacturer | EPCOS (TDK) | |
| PackageAxiaSeriesB32537CapacitanceµFTolerance±10%Voltage Rating - AC200VVoltage Rating - DC630VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedESR (Equivalent Series Resistance)-Operating Temperature55°C ~ 85°CMounting TypeMinogh HoleFackage / CaseAxialHeight - Seated (Max)-Fremination0.618" Diax 1.339" L (15.70mm x 34.00mm)Height - Seated (Max)-Applications-Applications-Factures-Applications-Features-Featur | Category | Capacitors | |
| SeriesB32537SeriesJµFCapacitanceJµFTolerance±10%Voltage Rating - AC200VVoltage Rating - DC630VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedDielectric Material-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.618" Dia x 1.339" L (15.70mm x 34.00mm)Height - Seated (Max)-Lead Spacing-Applications-FerminationCP insLead Spacing-Features-Features-Statement- </td <td></td> <td>Film Capacitors</td> <td></td> | | Film Capacitors | |
| CapacitanceIµFTolerance±10%Voltage Rating - AC200VVoltage Rating - DC630VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedESR (Equivalent Series Resistance)-Operating Temperature55°C ~ 85°CMounting TypeNailPackage / CaseAxialSize / Dimension0.618° Diax 1.339° L (15.70mm x 34.00mm)Height - Seated (Max)-Lead Spacing-Applications-Features-Features-Start Space-Applications-Start Space-Start Space-Star | Package | Axial | |
| Tolerance±10%Voltage Rating - AC200VVoltage Rating - DC630VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseAxialSize / Dimension-Height - Seated (Max)-TerminationPC PinsLead Spacing-Applications-Features-Features-States-Applications-States | Series | B32537 | |
| Voltage Rating - AC200VVoltage Rating - DC630VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedESR (Equivalent Series Resistance)-Operating Temperature55°C ~ 85°CMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.618" Dia x 1.339" L (15.70mm x 34.00mm)Height - Seated (Max)-FerminationPC PinsLead Spacing-Applications-Features-Features- | Capacitance | 1μF | |
| Voltage Rating - DC630VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.618" Dia x 1.339" L (15.70mm x 34.00mm)Height - Seated (Max)-TerminationPC PinsLead Spacing-Applications-Features- | Tolerance | $\pm 10\%$ | |
| Dielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.618" Dia x 1.339" L (15.70mm x 34.00mm)Height - Seated (Max)-TerminationPC PinsLead Spacing-Applications-Features- | Voltage Rating - AC | 200V | |
| ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.618" Dia x 1.339" L (15.70mm x 34.00mm)Height - Seated (Max)-TerminationPC PinsLead Spacing-Applications-Features- | Voltage Rating - DC | 630V | |
| Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.618" Dia x 1.339" L (15.70mm x 34.00mm)Height - Seated (Max)-TerminationPC PinsLead Spacing-Applications-Features- | Dielectric Material | Polyester, Polyethylene Terephthalate (PET), Metallized | |
| Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.618" Dia x 1.339" L (15.70mm x 34.00mm)Height - Seated (Max)-TerminationPC PinsLead Spacing-Applications-Features- | ESR (Equivalent Series Resistance) | - | |
| Package / CaseAxialSize / Dimension0.618" Dia x 1.339" L (15.70mm x 34.00mm)Height - Seated (Max)-TerminationPC PinsLead Spacing-Applications-Features- | Operating Temperature | -55°C ~ 85°C | |
| Size / Dimension0.618" Dia x 1.339" L (15.70mm x 34.00mm)Height - Seated (Max)-TerminationPC PinsLead Spacing-Applications-Features- | Mounting Type | Through Hole | |
| Height - Seated (Max)-TerminationPC PinsLead Spacing-Applications-Features- | Package / Case | Axial | |
| TerminationPC PinsLead Spacing-Applications-Features- | Size / Dimension | 0.618" Dia x 1.339" L (15.70mm x 34.00mm) | |
| Lead Spacing-Applications-Features- | Height - Seated (Max) | - | |
| Applications-Features- | Termination | PC Pins | |
| Features - | Lead Spacing | - | |
| | Applications | - | |
| Report errors? | Features | - | |
| | | Repo | ort errors? |

B32537B8105K Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B32537B8105K Payment Methods





If you have any question about B32537B8105K, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com