

B32560J6683J000

B32560J6683J000 Information



B32560J6683J000
EPCOS (TDK)
Capacitors Film Capacitors
CAP FILM 0.068UF 5% 400VDC 2DIP
2-DIP
For the pricing/inventory/lead time, please contact us
Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B32560J6683J000 Specifications

ManufacturerEPCOS (TDK)CapacitorsFilm CapacitorsPackage2-DIPSeriesSilverCap? B32560Capacitance0.068µFColaracitance200VVoltage Rating - DC200VVoltage Rating - DC400VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature55°C ~ 125°CVoltage / Case2-DIPSize / Dimension0.354" L x 0.150" W (9.00mm x 3.80mm)Height - Seated (Max)0.287" (7.30mm)TerminationPC PinsLad Spacing.Applications.Features.			
CategoryCapacitorsFilm CapacitorsPackage2-DIPSeriesSilverCap? B32560Capacitance0.068µFTolerance±5%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / Case0.354" L x 0.150" W (9.00mm x 3.80mm)Siz / Dimension0.287" (7.30mm)Height - Seated (Max)0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Manufacturer Part Number	B32560J6683J000	
Film CapacitorsPackage2-DIPSeriesSilverCap? B32560Capacitance0.068µFTolerance±5%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / Case2-DIPSize / Dimension0.354" L x 0.150" W (9.00mm x 3.80mm)Height - Seated (Max)0.287" (7.30mm)PC Pins0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Manufacturer	EPCOS (TDK)	
Package2-DIPSeriesSilverCap? B32560Capacitance0.068µFTolerance±5%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / Case2-DIPSize / Dimension0.354" L x 0.150" W (9.00mm x 3.80mm)Height - Seated (Max)0.287" (7.30mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Category	Capacitors	
SeriesSilverCap? B32560Capacitance0.068μFTolerance±5%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / Case2-DIPSize / Dimension0.354" L x 0.150" W (9.00mm x 3.80mm)Height - Seated (Max)0.287" (7.30mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-		Film Capacitors	
Capacitance0.068μFTolerance±5%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / Case2-DIPSize / Dimension0.287" (7.30mm)Height - Seated (Max)0.295" (7.50mm)Lead Spacing0.295" (7.50mm)ApplicationsGeneral Purpose	Package	2-DIP	
Tolerance±5%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / Case2-DIPSize / Dimension0.354" L x 0.150" W (9.00mm x 3.80mm)Height - Seated (Max)0.287" (7.30mm)TerminationPC PinsLead Spacing0.295" (7.50mm)Applications-Features-	Series	SilverCap? B32560	
Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / Case2-DIPSize / Dimension0.354" L x 0.150" W (9.00mm x 3.80mm)Height - Seated (Max)0.287" (7.30mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Capacitance	0.068µF	
Voltage Rating - DC400VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / Case2-DIPSize / Dimension0.354" L x 0.150" W (9.00mm x 3.80mm)Height - Seated (Max)0.287" (7.30mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Tolerance	±5%	
Dielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / Case2-DIPSize / Dimension0.354" L x 0.150" W (9.00mm x 3.80mm)Height - Seated (Max)0.287" (7.30mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Voltage Rating - AC	200V	
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / Case2-DIPSize / Dimension0.354" L x 0.150" W (9.00mm x 3.80mm)Height - Seated (Max)0.287" (7.30mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Voltage Rating - DC	400V	
Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / Case2-DIPSize / Dimension0.354" L x 0.150" W (9.00mm x 3.80mm)Height - Seated (Max)0.287" (7.30mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Dielectric Material	Polyester, Polyethylene Terephthalate (PET), Metallized - Stacked	
Nounting TypeThrough HolePackage / Case2-DIPSize / Dimension0.354" L x 0.150" W (9.00mm x 3.80mm)Height - Seated (Max)0.287" (7.30mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	ESR (Equivalent Series Resistance)	-	
Package / Case2-DIPSize / Dimension0.354" L x 0.150" W (9.00mm x 3.80mm)Height - Seated (Max)0.287" (7.30mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Operating Temperature	-55°C ~ 125°C	
Size / Dimension0.354" L x 0.150" W (9.00mm x 3.80mm)Height - Seated (Max)0.287" (7.30mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Mounting Type	Through Hole	
Height - Seated (Max)0.287" (7.30mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Package / Case	2-DIP	
TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Size / Dimension	0.354" L x 0.150" W (9.00mm x 3.80mm)	
Lead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Height - Seated (Max)	0.287" (7.30mm)	
ApplicationsGeneral PurposeFeatures-	Termination	PC Pins	
Features -	Lead Spacing	0.295" (7.50mm)	
	Applications	General Purpose	
Report errors?	Features	-	
			Report errors?

B32560J6683J000 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B32560J6683J000 Payment Methods





If you have any question about B32560J6683J000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com