



B32560J9102J000 Information

Heisener.com

Part NumberB32560J9102J000ManufacturerEPCOS (TDK)CategoryCapacitors
Film Capacitors

Description CAP FILM 1000PF 5% 1KVDC 2DIP

Package 2-DIF

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









D2256010102	TOOO Coo	oifications
B32560J9102	JUUU Spe	cincations

Manufacturer EPCOS (TDK) Category Capacitors Film Capacitors Package 2-DIP Series SilverCap? B32560 Capacitance 1000pF Tolerance ±5% Voltage Rating - AC 500V Voltage Rating - DC 1000V (1kV) Dielectric Material Polyester, Polyethylene Terephthalate (PET), Metallized - Stacked ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case 2-DIP Size / Dimension - Height - Seated (Max) - Termination PC Pins Lead Spacing 0.295" (7.50mm) Applications General Purpose Features -	*		
Category Capacitors Film Capacitors Package 2-DIP Series SilverCap? B32560 Capacitance 1000pF Tolerance ±5% Voltage Rating - AC 500V Voltage Rating - DC 1000V (1kV) Dielectric Material Polyester, Polyethylene Terephthalate (PET), Metallized - Stacked ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case 2-DIP Size / Dimension - Height - Seated (Max) - Termination PC Pins Lead Spacing 0.295" (7.50mm) Applications General Purpose Features -	Manufacturer Part Number	B32560J9102J000	
Film Capacitors Package 2-DIP Series SilverCap? B32560 Capacitance 1000pF Tolerance ±5% Voltage Rating - AC Voltage Rating - DC 1000V (1kV) Dielectric Material Polyester, Polyethylene Terephthalate (PET), Metallized - Stacked ESR (Equivalent Series Resistance) Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case 2-DIP Size / Dimension - Height - Seated (Max) Termination PC Pins Lead Spacing 0.295" (7.50mm) Applications General Purpose Features	Manufacturer	EPCOS (TDK)	
Package 2-DIP Series SilverCap? B32560 Capacitance 1000pF Tolerance ±5% Voltage Rating - AC 500V Voltage Rating - DC 1000V (1kV) Dielectric Material Polyester, Polyethylene Terephthalate (PET), Metallized - Stacked ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case 2-DIP Size / Dimension - Height - Seated (Max) - Termination PC Pins Lead Spacing 0.295" (7.50mm) Applications General Purpose Features -	Category	Capacitors	
Series SilverCap? B32560 Capacitance 1000pF Tolerance ±5% Voltage Rating - AC 500V Voltage Rating - DC 1000V (1kV) Dielectric Material Polyester, Polyethylene Terephthalate (PET), Metallized - Stacked ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case 2-DIP Size / Dimension - Height - Seated (Max) - Termination PC Pins Lead Spacing 0.295" (7.50mm) Applications General Purpose Features -		Film Capacitors	
Capacitance 1000pF Tolerance ±5% Voltage Rating - AC 500V Voltage Rating - DC 1000V (1kV) Dielectric Material Polyester, Polyethylene Terephthalate (PET), Metallized - Stacked ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case 2-DIP Size / Dimension - Height - Seated (Max) - Termination PC Pins Lead Spacing 0.295" (7.50mm) Applications General Purpose Features -	Package	2-DIP	
Tolerance ±5% Voltage Rating - AC 500V Voltage Rating - DC 1000V (1kV) Dielectric Material Polyester, Polyethylene Terephthalate (PET), Metallized - Stacked ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case 2-DIP Size / Dimension - Height - Seated (Max) - Termination PC Pins Lead Spacing 0.295" (7.50mm) Applications General Purpose Features -	Series	SilverCap? B32560	
Voltage Rating - AC Voltage Rating - DC 1000V (1kV) Dielectric Material Polyester, Polyethylene Terephthalate (PET), Metallized - Stacked ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case 2-DIP Size / Dimension - Height - Seated (Max) - Termination PC Pins Lead Spacing 0.295" (7.50mm) Applications General Purpose Features	Capacitance	1000pF	
Voltage Rating - DC Dielectric Material Polyester, Polyethylene Terephthalate (PET), Metallized - Stacked ESR (Equivalent Series Resistance) Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case 2-DIP Size / Dimension - Height - Seated (Max) - Termination PC Pins Lead Spacing 0.295" (7.50mm) Applications General Purpose Features	Tolerance	±5%	
Dielectric Material Polyester, Polyethylene Terephthalate (PET), Metallized - Stacked ESR (Equivalent Series Resistance) Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case 2-DIP Size / Dimension - Height - Seated (Max) - Termination Lead Spacing O.295" (7.50mm) Applications General Purpose Features -	Voltage Rating - AC	500V	
ESR (Equivalent Series Resistance) Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case 2-DIP Size / Dimension - Height - Seated (Max) - Termination PC Pins Lead Spacing O.295" (7.50mm) Applications Features -	Voltage Rating - DC	1000V (1kV)	
Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case 2-DIP Size / Dimension - Height - Seated (Max) - Termination PC Pins Lead Spacing 0.295" (7.50mm) Applications General Purpose Features -	Dielectric Material	Polyester, Polyethylene Terephthalate (PET), Metallized - Stacked	
Mounting Type Through Hole Package / Case 2-DIP Size / Dimension - Height - Seated (Max) - Termination PC Pins Lead Spacing 0.295" (7.50mm) Applications General Purpose Features -	ESR (Equivalent Series Resistance)	-	
Package / Case 2-DIP Size / Dimension - Height - Seated (Max) - Termination PC Pins Lead Spacing 0.295" (7.50mm) Applications General Purpose Features -	Operating Temperature	-55°C ~ 125°C	
Size / Dimension - Height - Seated (Max) - Termination PC Pins Lead Spacing 0.295" (7.50mm) Applications General Purpose Features -	Mounting Type	Through Hole	
Height - Seated (Max) Termination PC Pins Lead Spacing 0.295" (7.50mm) Applications General Purpose Features -	Package / Case	2-DIP	
Termination PC Pins Lead Spacing 0.295" (7.50mm) Applications General Purpose Features -	Size / Dimension	-	
Lead Spacing 0.295" (7.50mm) Applications General Purpose Features -	Height - Seated (Max)	-	
Applications General Purpose Features -	Termination	PC Pins	
Features -	Lead Spacing	0.295" (7.50mm)	
	Applications	General Purpose	
	Features	-	
Report errors?			Report errors?

B32560J9102J000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B32560J9102J000 Payment Methods





















B32560J9102J000 Shipping Methods













If you have any question about B32560J9102J000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com