



B32561J3154J000 Information

Manufac Category Heisener.com

Part Number B32561J3154J000
Manufacturer EPCOS (TDK)
Category Capacitors
Film Capacitors

Description CAP FILM 0.15UF 5% 250VDC 2DIP

Package 2-DIF

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B32561J3154J000 Specifications

Manufacturer Part NumberB32561J3154J000ManufacturerEPCOS (TDK)CategoryCapacitorsPackage2-DIPSeriesSilverCap? B32561Capacitance0.15µFTolerance±5%Voltage Rating - AC160VVoltage Rating - DC250VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / Case2-DIPSize / Dimension0.453" L x 0.130" W (11.50mm x 3.30mm)Height - Seated (Max)0.236" (6.00mm)TerminationPC Pins			
Category Capacitors Film Capacitors Package 2-DIP Series SilverCap? B32561 Capacitance 0.15µF Tolerance ±5% Voltage Rating - AC 160V Voltage Rating - DC 250V Dielectric Material Polyester, Polyethylene Terephthalate (PET), Metallized - Stacked ESR (Equivalent Series Resistance) Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.453" L x 0.130" W (11.50mm x 3.30mm) Height - Seated (Max) 0.236" (6.00mm)	Manufacturer Part Number	B32561J3154J000	
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	Manufacturer	EPCOS (TDK)	
Package2-DIPSeriesSilverCap? B32561Capacitance $0.15\mu F$ Tolerance $\pm 5\%$ Voltage Rating - AC $160V$ Voltage Rating - DC $250V$ Dielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature -55° C ~ 125° CMounting TypeThrough HolePackage / Case 2 -DIPSize / Dimension 0.453° L x 0.130° W (11.50 mm x 3.30 mm)Height - Seated (Max) 0.236° (6.00 mm)	Category	Capacitors	
Series SilverCap? B32561 Capacitance 0.15µF Tolerance ±5% Voltage Rating - AC 160V Voltage Rating - DC 250V Dielectric Material Polyester, Polyethylene Terephthalate (PET), Metallized - Stacked ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.453" L x 0.130" W (11.50mm x 3.30mm) Height - Seated (Max) 0.236" (6.00mm)		Film Capacitors	
Capacitance $0.15\mu F$ Tolerance $\pm 5\%$ Voltage Rating - AC $160V$ Voltage Rating - DC $250V$ Dielectric MaterialPolyester, Polyethylene Terephthalate (PET), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ Mounting TypeThrough HolePackage / Case 2 -DIPSize / Dimension $0.453^{\circ}L \times 0.130^{\circ}W (11.50mm \times 3.30mm)$ Height - Seated (Max) 0.236° ($6.00mm$)	Package	2-DIP	
Tolerance ±5% Voltage Rating - AC 160V Voltage Rating - DC 250V Dielectric Material Polyester, Polyethylene Terephthalate (PET), Metallized - Stacked ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.453" L x 0.130" W (11.50mm x 3.30mm) Height - Seated (Max) 0.236" (6.00mm)	Series	SilverCap? B32561	
Voltage Rating - AC Voltage Rating - DC 250V Dielectric Material Polyester, Polyethylene Terephthalate (PET), Metallized - Stacked ESR (Equivalent Series Resistance) Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.453" L x 0.130" W (11.50mm x 3.30mm) Height - Seated (Max) 0.236" (6.00mm)	Capacitance	0.15μF	
Voltage Rating - DC Dielectric Material Polyester, Polyethylene Terephthalate (PET), Metallized - Stacked ESR (Equivalent Series Resistance) Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.453" L x 0.130" W (11.50mm x 3.30mm) Height - Seated (Max) 0.236" (6.00mm)	Tolerance	±5%	
Dielectric Material Polyester, Polyethylene Terephthalate (PET), Metallized - Stacked ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.453" L x 0.130" W (11.50mm x 3.30mm) Height - Seated (Max) 0.236" (6.00mm)	Voltage Rating - AC	160V	
ESR (Equivalent Series Resistance) Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.453" L x 0.130" W (11.50mm x 3.30mm) Height - Seated (Max) 0.236" (6.00mm)	Voltage Rating - DC	250V	
Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.453" L x 0.130" W (11.50mm x 3.30mm) Height - Seated (Max) 0.236" (6.00mm)	Dielectric Material	Polyester, Polyethylene Terephthalate (PET), Metallized - Stacked	
Mounting TypeThrough HolePackage / Case2-DIPSize / Dimension0.453" L x 0.130" W (11.50mm x 3.30mm)Height - Seated (Max)0.236" (6.00mm)	ESR (Equivalent Series Resistance)	-	
Package / Case 2-DIP Size / Dimension 0.453" L x 0.130" W (11.50mm x 3.30mm) Height - Seated (Max) 0.236" (6.00mm)	Operating Temperature	-55°C ~ 125°C	
Size / Dimension 0.453" L x 0.130" W (11.50mm x 3.30mm) Height - Seated (Max) 0.236" (6.00mm)	Mounting Type	Through Hole	
Height - Seated (Max) 0.236" (6.00mm)	Package / Case	2-DIP	
•	Size / Dimension	0.453" L x 0.130" W (11.50mm x 3.30mm)	
Termination PC Pins	Height - Seated (Max)	0.236" (6.00mm)	
	Termination	PC Pins	
Lead Spacing 0.394" (10.00mm)	Lead Spacing	0.394" (10.00mm)	
Applications General Purpose	Applications	General Purpose	
Features -	Features	-	
Report errors			Report errors?

B32561J3154J000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B32561J3154J000 Payment Methods


































If you have any question about B32561J3154J000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com