

B32652A7103K189

B32652A7103K189 Information

Heisener.com	Part Number Manufacturer Category Description Package	B32652A7103K189 EPCOS (TDK) Capacitors Film Capacitors CAP FILM 10000PF 1.25KVDC RADIAL Radial For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B32652A7103K189 Specifications

Manufacturer Part NumberB32652A7103K189ManufacturerEPCOS (TDK)CategoryCapacitorsFilm CapacitorsFilm CapacitorsPackageRadialSeriesB32652Capacitance1000pFTolerance±10%Voltage Rating - AC500VVoltage Rating - DC1250V (1.25kV)Dielectric Material-Operating Temperature-5°C ~ 100°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.236" W (18.00mm x 6.00mm)Height - Seated (Max)0.6 Xin (10.00mm)		
CategoryCapacitorsFilm CapacitorsPackageRadialSeriesB32652Capacitance10000pFTolerance±10%Voltage Rating - AC500VVoltage Rating - DC1250V (1.25kV)Dielectric Material-Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.236" W (18.00mm x 6.00mm)Height - Seated (Max)0.433" (11.00mm)	Manufacturer Part Number	B32652A7103K189
Fin CapacitorsPackageRadialSeriesB32652Capacitance10000pFTolerance±10%Voltage Rating - AC500VVoltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.236" W (18.00mm x 6.00mm)Height - Seated (Max)0.433" (11.00mm)	Manufacturer	EPCOS (TDK)
PackageRadiaPackageB32652Capacitance10000pFTolerance±10%Voltage Rating - AC500VVoltage Rating - DC1250V (1.25kV)Dielectric MaterialPolyproplene (PP), MetallizedDietertire Material-Operating Temperature-55°C ~ 100°CMounting TypeRadialPackage / CaseRadialSize / Dimension0.709° L x 0.236° W (18.00mm x 6.00mm)Height - Seated (Max)0.433° (11.00mm)	Category	Capacitors
Series B32652 Series B32652 Capacitance 10000pF Tolerance ±10% Voltage Rating - AC 500V Voltage Rating - DC 1250V (1.25kV) Dielectric Material Polypropylene (PP), Metallized Dielectric Material - Operating Temperature -55°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.709" L x 0.236" W (18.00mm x 6.00mm) Height - Seated (Max) 0.433" (11.00mm)		Film Capacitors
Capacitance1000pFTolerance±10%Voltage Rating - AC500VVoltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropelene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 100°CMounting TypeRadialPackage / CaseRadialSize / Dimension0.709" L x 0.236" W (18.00mm x 6.00mm)Height - Seated (Max)0.433" (11.00mm)	Package	Radial
Tolerance±10%Voltage Rating - AC500VVoltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedDielectric Materia-Coperating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.236" W (18.00mm x 6.00mm)Height - Seated (Max)0.433" (11.00mm)	Series	B32652
Voltage Rating - AC500VVoltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.236" W (18.00mm x 6.00mm)Height - Seated (Max)0.433" (11.00mm)	Capacitance	10000pF
Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.236" W (18.00mm x 6.00mm)Height - Seated (Max)0.433" (11.00mm)	Tolerance	±10%
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.236" W (18.00mm x 6.00mm)Height - Seated (Max)0.433" (11.00mm)	Voltage Rating - AC	500V
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.236" W (18.00mm x 6.00mm)Height - Seated (Max)0.433" (11.00mm)	Voltage Rating - DC	1250V (1.25kV)
Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.236" W (18.00mm x 6.00mm)Height - Seated (Max)0.433" (11.00mm)	Dielectric Material	Polypropylene (PP), Metallized
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.236" W (18.00mm x 6.00mm)Height - Seated (Max)0.433" (11.00mm)	ESR (Equivalent Series Resistance)	-
Package / Case Radial Size / Dimension 0.709" L x 0.236" W (18.00mm x 6.00mm) Height - Seated (Max) 0.433" (11.00mm)	Operating Temperature	-55°C ~ 100°C
Size / Dimension 0.709" L x 0.236" W (18.00mm x 6.00mm) Height - Seated (Max) 0.433" (11.00mm)	Mounting Type	Through Hole
Height - Seated (Max) 0.433" (11.00mm)	Package / Case	Radial
	Size / Dimension	0.709" L x 0.236" W (18.00mm x 6.00mm)
	Height - Seated (Max)	0.433" (11.00mm)
PC Pins	Termination	PC Pins
Lead Spacing 0.591" (15.00mm)	Lead Spacing	0.591" (15.00mm)
Applications DC Link, DC Filtering; High Pulse, DV/DT; Snubber	Applications	DC Link, DC Filtering; High Pulse, DV/DT; Snubber
Features Low ESL	Features	Low ESL
Report errors?		Report errors?

B32652A7103K189 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B32652A7103K189 Payment Methods



B32652A7103K189 Shipping Methods



If you have any question about B32652A7103K189, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com