

B32671P4104J289

B32671P4104J289 Information

	Heisener.com	B32671P4104J289 EPCOS (TDK) Capacitors Film Capacitors CAP FILM 0.1UF 5% 450VDC RADIAL Radial For the pricing/inventory/lead time, please contact	
	For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B32671P4104J289 Specifications

Manufacturer Part NumberB32671P4104J289ManufacturerEPCOS (TDK)CategoryCapacitorsFilm CapacitorsFilm CapacitorsPackageRadialSeriesB32671PCapacitance0.1µFTolerance±5%Voltage Rating - DC60VDielectric MaterialPolypropylene (PP), MetallizedDielectric Material-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0512" L x 0.157" W (13.00mm x 4.00mm)Height - Seated (Max)034" (10.00mm)ApplicationsPover Factor Correction (PFC)		
CategoryCapacitorsPackageFilm CapacitorsPackageRadialSeriesB32671PCapacitance0.1µFTolerance±5%Voltage Rating - AC160VVoltage Rating - DC450VDielectric MaterialPolyproplene (PP), MetallizedDielectric Material-Operating Temperature-55°C ~ 110°CMounting TypeThrough HoleSize / Dimension0.512" L x 0.157" W (13.00mm x 4.00mm)Height - Seated (Max)0.354" (0.00mm)Lead Spacing0.394" (10.00mm)ApplicationsNover Factor Correction (PFC)	Manufacturer Part Number	B32671P4104J289
Film CapacitorsPackageRadialSeriesB32671PCapacitance0.1μFTolerance±5%Voltage Rating - AC160VVoltage Rating - DC450VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeRadialSize / Dimension0.512" L x 0.157" W (13.00mm x 4.00mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsPower Factor Correction (PFC)	Manufacturer	EPCOS (TDK)
PackageRadialSeriesB32671PCapacitance0.1µFTolerance±5%Voltage Rating - AC160VVoltage Rating - DC450VDielectric MaterialPolypropylene (PP), MetallizedDielectric Material-Operating Temperature-55°C ~ 110°CMounting TypeStoll & 100 HolePackage / CaseRadialSize / Dimension0.512" L x 0.157" W (13.00mm x 4.00mm)Height - Seated (Max)0.354" (0.00mm)Lead Spacing0.394" (10.00mm)ApplicationsPower Factor Correction (PFC)	Category	Capacitors
SeriesB32671PCapacitance0.1µFTolerance±5%Voltage Rating - AC160VVoltage Rating - DC450VDielectric MaterialPolypropelen (PP), MetallizedDielectric Material-Operating Temperature-55°C ~ 110°CMounting TypeRadialPackage / CaseRadialSize / Dimension0.512" L x 0.157" W (13.00mm x 4.00mm)Height - Seated (Max)0.354" (9.00mm)Lead Spacing0.39" (10.00mm)ApplicationsPower Factor Correction (PFC)		Film Capacitors
Capacitance0.1μFTolerance±5%Voltage Rating - AC160VVoltage Rating - DC450VDielectric MaterialPolypropylene (PP), MetallizedDielectric Material-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / Case8adialSize / Dimension0.512" L x 0.157" W (13.00mm x 4.00mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsPower Factor Correction (PFC)	Package	Radial
Tolerance±5%Voltage Rating - AC160VVoltage Rating - DC450VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.512" L x 0.157" W (13.00mm x 4.00mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsPower Factor Correction (PFC)	Series	B32671P
Voltage Rating - AC160VVoltage Rating - DC450VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.512" L x 0.157" W (13.00mm x 4.00mm)Height - Seated (Max)O254" (9.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsPower Factor Correction (PFC)	Capacitance	0.1µF
Voltage Rating - DC450VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.512" L x 0.157" W (13.00mm x 4.00mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsPower Factor Correction (PFC)	Tolerance	±5%
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.512" L x 0.157" W (13.00mm x 4.00mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsPower Factor OPEC)	Voltage Rating - AC	160V
ESR (Equivalent Series Resistance)-Operating Temperature-Mounting Type-Package / CaseRadialSize / Dimension0.512" L x 0.157" W (13.00mm x 4.00mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsPower Factor Correction (PFC)	Voltage Rating - DC	450V
Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.512" L x 0.157" W (13.00mm x 4.00mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsPower Factor Correction (PFC)	Dielectric Material	Polypropylene (PP), Metallized
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension0.512" L x 0.157" W (13.00mm x 4.00mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsPower Factor Correction (PFC)	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension0.512" L x 0.157" W (13.00mm x 4.00mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsPower Factor Correction (PFC)	Operating Temperature	-55°C ~ 110°C
Size / Dimension0.512" L x 0.157" W (13.00mm x 4.00mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsPower Factor Correction (PFC)	Mounting Type	Through Hole
Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsPower Factor Correction (PFC)	Package / Case	Radial
TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsPower Factor Correction (PFC)	Size / Dimension	0.512" L x 0.157" W (13.00mm x 4.00mm)
Lead Spacing0.394" (10.00mm)ApplicationsPower Factor Correction (PFC)	Height - Seated (Max)	0.354" (9.00mm)
Applications Power Factor Correction (PFC)	Termination	PC Pins
	Lead Spacing	0.394" (10.00mm)
	Applications	Power Factor Correction (PFC)
Features -	Features	-
Report errors		Report errors?

B32671P4104J289 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B32671P4104J289 Payment Methods





If you have any question about B32671P4104J289, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com