

B32774P6155K000

B32774P6155K000 Information



Part Number	B32774P6155K000	
Manufacturer	EPCOS (TDK)	
Category	Capacitors Film Capacitors	
Description	CAP FILM 1.5UF 10% 630VDC RADIAL	
Package	Radial	
	For the pricing/inventory/lead time, please contact	
	us	
	Website: https://www.heisener.com	
	E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B32774P6155K000 Specifications

ManufacturerEPCOS (TDK)CategoryCapacitorsFilm CapacitorsFilm CapacitorsPackageRadialSeriesAutomotive, AEC-Q200, B32774PCapacitance1.5µFTolerance±10%Voltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedDoprating Temperature2.3 mOhmOperating TypeHrough HolePackage / CaseRadialSiz / Dimension1.240° L x 0.433° W (31.50mm x 11.00mm)Height - Seated (Max)0.748° (19.00mm)TerminationPC PinsLead SpacingJuss" (27.50mm)ApplicationsAutomotive		
CategoryCapacitorsPackageRadialPackageRadialSeriesAutomotive, AEC-Q200, B32774PCapacitance1.5µFTolerance±10%Voltage Rating - AC-Voltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedDoperating Temperature-40°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240" L x 0.433" W (31.50mm x 11.00mm)Height - Seated (Max)0.748" (19.00mm)Lead Spacing1.083" (27.50mm)ApplicationsAutomotive	Manufacturer Part Number	B32774P6155K000
Fin CapacitorsPackageRadialSeriesAutomotive, AEC-Q200, B32774PCapacitance1.5µFTolerance±10%Voltage Rating - AC-Voltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)22.3 mOhmOperating Temperature-40°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240" L x 0.433" W (31.50mm x 11.00mm)Height - Seated (Max)0.748" (19.00mm)TerminationPC PinsLead SpacingAutomotiveApplicationsAutomotive	Manufacturer	EPCOS (TDK)
PackageRadiaSeriesAutomotive, AEC-Q200, B32774PCapacitance1.5µFTolerance±10%Voltage Rating - AC-Voltage Rating - DC630VDielectric MaterialPolyproplene (PP), MetallizedDielectric Material22.3 mOhmOperating Temperature-40°C ~ 125°CMounting TypeRadialSize / Dimension1.240" L x 0.433" W (31.50mm x 11.00mm)Height - Seated (Max)Or48" (19.00mm)TerminationPC PinsApplicationsAutomotiveApplicationsAutomotive	Category	Capacitors
Series Automotive, AEC-Q200, B32774P Series 1.5µF Capacitance ±10% Tolerance ±10% Voltage Rating - AC - Voltage Rating - DC 630V Dielectric Material Polypropylene (PP), Metallized DSR (Equivalent Series Resistance) 22.3 mOhm Operating Temperature -40°C ~ 125°C Mounting Type Through Hole Package / Case Radial Size / Dimension 1.240" L x 0.433" W (31.50mm x 11.00mm) Height - Seated (Max) 0.748" (19.00mm) Termination PC Pins Lead Spacing 1.083" (27.50mm) Automotive Automotive		Film Capacitors
Capacitance1.5µFTolerance±10%Voltage Rating - AC-Voltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)22.3 mOhmOperating Temperature-40°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.748" (19.00mm) x11.00mm)Height - Seated (Max)PC PinsLead SpacingAutomotiveApplicationsAutomotive	Package	Radial
Tolerance±10%Voltage Rating - AC-Voltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)22.3 mOhmOperating Temperature-40°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240" L x 0.433" W (31.50mm x 11.00mm)Height - Seated (Max)O/T48" (19.00mm)TerminationPC PinsLead SpacingAutomotiveApplicationsAutomotive	Series	Automotive, AEC-Q200, B32774P
Voltage Rating - AC-Voltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)22.3 mOhmOperating Temperature-40°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240" L x 0.433" W (31.50mm x 11.00mm)Height - Seated (Max)O.748" (19.00mm)TerminationPC PinsLead SpacingAutomotiveApplicationsAutomotive	Capacitance	1.5µF
Voltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)22.3 mOhmOperating Temperature-40°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240" L x 0.433" W (31.50mm x 11.00mm)Height - Seated (Max)0.748" (19.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsAutomotive	Tolerance	±10%
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)22.3 mOhmOperating Temperature-40°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240" L x 0.433" W (31.50mm x 11.00mm)Height - Seated (Max)0.748" (19.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsAutomotive	Voltage Rating - AC	-
ESR (Equivalent Series Resistance)22.3 mOhmOperating Temperature-40°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240" L x 0.433" W (31.50mm x 11.00mm)Height - Seated (Max)0.748" (19.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsAutomotive	Voltage Rating - DC	630V
Operating Temperature-40°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240" L x 0.433" W (31.50mm x 11.00mm)Height - Seated (Max)0.748" (19.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsAutomotive	Dielectric Material	Polypropylene (PP), Metallized
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240" L x 0.433" W (31.50mm x 11.00mm)Height - Seated (Max)0.748" (19.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsAutomotive	ESR (Equivalent Series Resistance)	22.3 mOhm
Package / CaseRadialSize / Dimension1.240" L x 0.433" W (31.50mm x 11.00mm)Height - Seated (Max)0.748" (19.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsAutomotive	Operating Temperature	-40°C ~ 125°C
Size / Dimension 1.240" L x 0.433" W (31.50mm x 11.00mm) Height - Seated (Max) 0.748" (19.00mm) Termination PC Pins Lead Spacing 1.083" (27.50mm) Applications Automotive	Mounting Type	Through Hole
Height - Seated (Max)0.748" (19.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsAutomotive	Package / Case	Radial
TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsAutomotive	Size / Dimension	1.240" L x 0.433" W (31.50mm x 11.00mm)
Lead Spacing1.083" (27.50mm)ApplicationsAutomotive	Height - Seated (Max)	0.748" (19.00mm)
Applications Automotive	Termination	PC Pins
	Lead Spacing	1.083" (27.50mm)
Features -	Applications	Automotive
	Features	-
Report errors?		Report errors?

B32774P6155K000 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B32774P6155K000 Payment Methods





If you have any question about B32774P6155K000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com