

# B32778G0306K000

#### B32778G0306K000 Information

Part



Part Number	B32778G0306K000		
Manufacturer	EPCOS (TDK)		
Category	Capacitors Film Capacitors		
Description	CAP FILM 30UF 10% 1.1KVDC RADIAL		
Package	Radial		
	For the pricing/inventory/lead time, please contact us		
	Website: https://www.heisener.com E-mail: salesdept@heisener.com		



Request a Quote

For Reference Only

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### B32778G0306K000 Specifications

ManufacturerEPCOS (TDK)CategoryCapacitorsFilm CapacitorsFilm CapacitorsPackageRadialSeriesB32778Capacitance30µFTolerance±10%Voltage Rating - AC-Voltage Rating - DC1100V (1.1kV)Dielectric Material9 Polyproplene (PP), MetallizedOperating Temperature40°C ~ 105°CMounting Type7hrough HolePackage / CaseRadialSiz / Dimension2.264" L x 1.181" W (57.50mm x 30.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC FilteringFeaturesLong Life			
CategoryCapacitorsPackageRadialPackageRadialSeriesB32778Capacitance30µFTolerance±10%Voltage Rating - AC-Voltage Rating - DC1100V (1.1kV)Dielectric MaterialPolypropylene (PP), MetallizedOperating Temperature40°C ~ 105°CMounting TypeFhrough HolePackage / CaseRadialSize / Dimension2.264" L x 1.181" W (57.50mm x 30.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC FilteringFeaturesDC Link, DC Filtering	Manufacturer Part Number	B32778G0306K000	
Fin CapacitorsPackageRadialSeriesB32778Capacitance30µFTolerance±10%Voltage Rating - AC-Voltage Rating - DC1100V (1.1kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)5 mOhmOperating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension2.264" L x 1.181" W (57.50mm x 30.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC FilteringFeaturesLong Life	Manufacturer	EPCOS (TDK)	
PackageRadialSeriesB32778Capacitance30µFTolerance±10%Voltage Rating - AC-Voltage Rating - DC1100V (1.1kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)5 mOhmOperating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension2.264" L x 1.181" W (57.50mm x 30.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC FilteringFeaturesLong Life	Category	Capacitors	
Bit Bit   Series Bit   Series Bit   Capacitance 30µF   Tolerance ±10%   Voltage Rating - AC -   Voltage Rating - DC 1100V (1.1kV)   Dielectric Material Polypropylene (PP), Metallized   ESR (Equivalent Series Resistance) 5 mOhm   Operating Temperature -40°C ~ 105°C   Mounting Type Through Hole   Package / Case Radial   Size / Dimension 2.264" L x 1.181" W (57.50mm x 30.00mm)   Height - Seated (Max) 1.772" (45.00mm)   Termination PC Pins   Lead Spacing 2.067" (52.50mm)   Applications DC Link, DC Filtering   Features Long Life		Film Capacitors	
Capacitance30µFTolerance±10%Voltage Rating - AC-Voltage Rating - DC1100V (1.1kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)5 mOhmOperating Temperature-40°C ~ 105°CMounting TypeRadialPackage / CaseRadialSize / Dimension1.772" (45.00mm) 30.00mm)Height - Seated (Max)1.772" (45.00mm)Lead Spacing2.067" (52.50mm)ApplicationsDC Link, DC FilteringFeaturesLong Life	Package	Radial	
Tolerance±10%Voltage Rating - AC-Voltage Rating - DC1100V (1.1kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)5 mOhmOperating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension2.264" L x 1.181" W (57.50mm x 30.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC FilteringFeaturesLong Life	Series	B32778	
Voltage Rating - AC-Voltage Rating - DC1100V (1.1kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)5 mOhmOperating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension2.264" L x 1.181" W (57.50mm x 30.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC FilteringFeaturesLong Life	Capacitance	30µF	
Voltage Rating - DC1100V (1.1kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)5 mOhmOperating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension2.264" L x 1.181" W (57.50mm x 30.00mm)Height - Seated (Max)1.772" (45.00mm)Termination2.067" (52.50mm)Lead Spacing2.067" (52.50mm)ApplicationsDC Link, DC FilteringFeaturesLong Life	Tolerance	$\pm 10\%$	
Dielectric MaterialPolypropylene (PP), MetallizedDielectric Material5 mOhmESR (Equivalent Series Resistance)5 mOhmOperating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension2.264" L x 1.181" W (57.50mm x 30.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC FilteringFeaturesLong Life	Voltage Rating - AC	-	
ESR (Equivalent Series Resistance)5 mOhmOperating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension2.264" L x 1.181" W (57.50mm x 30.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC FilteringFeaturesLong Life	Voltage Rating - DC	1100V (1.1kV)	
Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension2.264" L x 1.181" W (57.50mm x 30.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC FilteringFeaturesLong Life	Dielectric Material	Polypropylene (PP), Metallized	
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension2.264" L x 1.181" W (57.50mm x 30.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC FilteringFeaturesLong Life	ESR (Equivalent Series Resistance)	5 mOhm	
Package / CaseRadialSize / Dimension2.264" L x 1.181" W (57.50mm x 30.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC FilteringFeaturesLong Life	Operating Temperature	-40°C ~ 105°C	
Size / Dimension2.264" L x 1.181" W (57.50mm x 30.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC FilteringFeaturesLong Life	Mounting Type	Through Hole	
Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC FilteringFeaturesLong Life	Package / Case	Radial	
TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC FilteringFeaturesLong Life	Size / Dimension	2.264" L x 1.181" W (57.50mm x 30.00mm)	
Lead Spacing2.067" (52.50mm)ApplicationsDC Link, DC FilteringFeaturesLong Life	Height - Seated (Max)	1.772" (45.00mm)	
ApplicationsDC Link, DC FilteringFeaturesLong Life	Termination	PC Pins	
Features Long Life	Lead Spacing	2.067" (52.50mm)	
	Applications	DC Link, DC Filtering	
Report errors?	Features	Long Life	
			Report errors?

#### B32778G0306K000 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### B32778G0306K000 Payment Methods





If you have any question about B32778G0306K000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com