



B37979G5331J054 Information

Heisener.com

Part Number B37979G5331J054 Manufacturer EPCOS (TDK)

Category Capacitors Ceramic Capacitors

Description CAP CER 330PF 50V NP0 RADIAL

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B37979G5331J054 Specifications

Manufacturer Part Number B37979G5331J054 Manufacturer EPCOS (TDK) Category Capacitors Package Radial Series B37979G Capacitance 330pF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient C0G, NP0 Operating Temperature -5°C ~ 125°C Features - Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.217" L x 0.197" W (5.50mm x 5.00mm) Height - Seated (Max) 0.217" (5.50mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Formed Leads		
Category Capacitors Package Radial Series B37979G Capacitance 330pF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features - Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.217" L x 0.197" W (5.50mm x 5.00mm) Height - Seated (Max) 0.217" (5.50mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Formed Leads	Manufacturer Part Number	B37979G5331J054
Package Radial Series B37979G Capacitance 330pF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.217" L x 0.197" W (5.50mm x 5.00mm) Height - Seated (Max) 0.217" (5.50mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Formed Leads	Manufacturer	EPCOS (TDK)
Package Radial Series B37979G Capacitance 330pF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.217" L x 0.197" W (5.50mm x 5.00mm) Height - Seated (Max) 0.217" (5.50mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Formed Leads	Category	Capacitors
Series B37979G Capacitance 330pF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.217" L x 0.197" W (5.50mm x 5.00mm) Height - Seated (Max) 0.217" (5.50mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Formed Leads		Ceramic Capacitors
Capacitance 330pF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features - Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.217" L x 0.197" W (5.50mm x 5.00mm) Height - Seated (Max) 0.217" (5.50mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Formed Leads	Package	Radial
Tolerance ±5% Voltage - Rated 50V Temperature Coefficient COG, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.217" L x 0.197" W (5.50mm x 5.00mm) Height - Seated (Max) 0.217" (5.50mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Formed Leads	Series	B37979G
Voltage - Rated Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.217" L x 0.197" W (5.50mm x 5.00mm) Height - Seated (Max) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Formed Leads	Capacitance	330pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features - Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension O.217" L x 0.197" W (5.50mm x 5.00mm) Height - Seated (Max) Thickness (Max) - Lead Spacing O.197" (5.00mm) Lead Style Formed Leads	Tolerance	±5%
Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.217" L x 0.197" W (5.50mm x 5.00mm)Height - Seated (Max)0.217" (5.50mm)Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleFormed Leads	Voltage - Rated	50V
Features Ratings Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.217" L x 0.197" W (5.50mm x 5.00mm) Height - Seated (Max) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Formed Leads	Temperature Coefficient	C0G, NP0
Ratings - RF, Microwave, High Frequency Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.217" L x 0.197" W (5.50mm x 5.00mm) Height - Seated (Max) 0.217" (5.50mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Formed Leads	Operating Temperature	-55°C ~ 125°C
Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.217" L x 0.197" W (5.50mm x 5.00mm) Height - Seated (Max) 0.217" (5.50mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Formed Leads	Features	-
Failure Rate Mounting Type Through Hole Package / Case Radial Size / Dimension 0.217" L x 0.197" W (5.50mm x 5.00mm) Height - Seated (Max) 0.217" (5.50mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Formed Leads	Ratings	-
Mounting Type Package / Case Radial Size / Dimension 0.217" L x 0.197" W (5.50mm x 5.00mm) Height - Seated (Max) 0.217" (5.50mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Formed Leads	Applications	RF, Microwave, High Frequency
Package / Case Radial Size / Dimension 0.217" L x 0.197" W (5.50mm x 5.00mm) Height - Seated (Max) 0.217" (5.50mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Formed Leads	Failure Rate	-
Size / Dimension 0.217" L x 0.197" W (5.50mm x 5.00mm) Height - Seated (Max) 0.217" (5.50mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Formed Leads	Mounting Type	Through Hole
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style O.217" (5.50mm) - Under the seated (Max) Formed Leads	Package / Case	Radial
Thickness (Max) Lead Spacing 0.197" (5.00mm) Lead Style Formed Leads	Size / Dimension	0.217" L x 0.197" W (5.50mm x 5.00mm)
Lead Spacing 0.197" (5.00mm) Lead Style Formed Leads	Height - Seated (Max)	0.217" (5.50mm)
Lead Style Formed Leads	Thickness (Max)	-
·	Lead Spacing	0.197" (5.00mm)
Report errors?	Lead Style	Formed Leads
		Report errors?

B37979G5331J054 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B37979G5331J054 Payment Methods



















B37979G5331J054 Shipping Methods













If you have any question about B37979G5331J054, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com