

B37984M5474K054

B37984M5474K054 Information



nber	B37984M5474K054	
turer	EPCOS (TDK)	
7	Capacitors Ceramic Capacitors	
ion	CAP CER 0.47UF 50V X7R RADIAL	
	Radial	
	For the pricing/inventory/lead time, please contact	
	us	
	Website: https://www.heisener.com	
	E-mail: salesdept@heisener.com	



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B37984M5474K054 Specifications

Manufacturer Part Number B37984M5474K054 Manufacturer EPCOS (TDK) Category Capacitors Caranic Capacitors Caranic Capacitors Package Radial Series B37984M6 Capacitance 0.47µF Tolerance ±10% Voltage - Rated 50V Parting Temperature Coefficient X7R Operating Temperature 5°C ~ 125°C ~ 125°C Pactures - Applications Acc-Q200 Applications Actomotive Package / Case Radial Size / Dimension 0.54% L x 0.295% W (9.00mm x 7.50mm) Height - Seated (Max) 0.998" (2.50mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm)		
CategoryCapacitorsPackageRadialPackageRadialSeriesB37984MCapacitance0.47μFTolerance±10%Voltage - Rated50VTomperature CoefficientX7ROperating Temperature-55°C ~ 125°CPactangs-55°C ~ 125°CRatingsAEC-Q200Applications-10rough HoleFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.95% (2.50mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.917 (5.00mm)Lead StyleFormed Leads - Kinked	Manufacturer Part Number	B37984M5474K054
Ceranic CapacitorsPackageRadialSeriesB37984MCapacitance0.47µFTolerance±10%Voltage - Rated50VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-RatingsAEC-Q200Applications, AutomotiveFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.958" (L s.0.295" W (9.00mm x 7.50mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.197" (S.00mm)Lead StyleFormed Leads - Kinked	Manufacturer	EPCOS (TDK)
PackageRadialSeriesB37984MCapacitance0.47μFTolerance±10%Voltage Rated50VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-RatingsAEC-Q200ApplicationsAutomotiveFailure Rate-Noutring TypeThrough HoleSize / Dimension0.354" L x 0.295" W (9.00mm x 7.50mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleFormed Leads - Kinked	Category	Capacitors
Series B37984M Capacitance 0.47μF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings AEC-Q200 Applications Atuonotive Failure Rate - Noutring Type Through Hole Size / Dimension 0.354" L x 0.295" W (9.00mm x 7.50mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Formed Leads - Kinked		Ceramic Capacitors
Capacitance0.47µFTolerance±10%Voltage - Rated50VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-RatingsAEC-Q200ApplicationsAtionotiveFailure Rate-Nounting TypeHolePackage / CaseRadialSize / Dimension0.98" (2.50mm x 7.50mm)Height - Seated (Max)0.998" (2.50mm)Thickness (Max)0.197" (5.00mm)Lead SpacingFormed Leads - Kinked	Package	Radial
Tolerance±10%Voltage - Rated50VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-RatingsAEC-Q200ApplicationsAutomotiveFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.958" (2.50mm) x 7.50mm)Height - Seated (Max)-Lead Spacing0.197" (5.00mm)Lead StyleFormed Leads - Kinked	Series	B37984M
Voltage - Rated50VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-RatingsAEC-Q200ApplicationsAtomotiveFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.98" (2.50mm x 7.50mm)Height - Seated (Max)-Thickness (Max)0.197" (5.00mm)Lead SpacingFormed Leads - Kinked	Capacitance	0.47µF
Temperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-RatingsAEC-Q200ApplicationsAutomotiveFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.354" L x 0.295" W (9.00mm x 7.50mm)Height - Seated (Max)-Thickness (Max)0.197" (5.00mm)Lead SpacingFormed Leads - Kinked	Tolerance	$\pm 10\%$
Operating Temperature.55°C ~ 125°CFeatures-RatingsAEC-Q200ApplicationsAutomotiveFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.354" L x 0.295" W (9.00mm x 7.50mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleFormed Leads - Kinked	Voltage - Rated	50V
Features-Features-RatingsAEC-Q200ApplicationsAutomotiveFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.354" L x 0.295" W (9.00mm x 7.50mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleFormed Leads - Kinked	Temperature Coefficient	X7R
RatingsAEC-Q200ApplicationsAutomotiveFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.354" L x 0.295" W (9.00mm x 7.50mm)Height - Seated (Max)0.098" (2.50mm)Thickness (Max)0.197" (5.00mm)Lead SpacingFormed Leads - Kinked	Operating Temperature	-55°C ~ 125°C
ApplicationsAutomotiveFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.354" L x 0.295" W (9.00mm x 7.50mm)Height - Seated (Max)0.098" (2.50mm)Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleFormed Leads - Kinked	Features	-
Failure Rate-Failure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.354" L x 0.295" W (9.00mm x 7.50mm)Height - Seated (Max)0.098" (2.50mm)Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleFormed Leads - Kinked	Ratings	AEC-Q200
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.354" L x 0.295" W (9.00mm x 7.50mm)Height - Seated (Max)0.098" (2.50mm)Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleFormed Leads - Kinked	Applications	Automotive
Package / CaseRadialSize / Dimension0.354" L x 0.295" W (9.00mm x 7.50mm)Height - Seated (Max)0.098" (2.50mm)Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleFormed Leads - Kinked	Failure Rate	-
Size / Dimension 0.354" L x 0.295" W (9.00mm x 7.50mm) Height - Seated (Max) 0.098" (2.50mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Formed Leads - Kinked	Mounting Type	Through Hole
Height - Seated (Max)0.098" (2.50mm)Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleFormed Leads - Kinked	Package / Case	Radial
Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleFormed Leads - Kinked	Size / Dimension	0.354" L x 0.295" W (9.00mm x 7.50mm)
Lead Spacing0.197" (5.00mm)Lead StyleFormed Leads - Kinked	Height - Seated (Max)	0.098" (2.50mm)
Lead Style Formed Leads - Kinked	Thickness (Max)	-
•	Lead Spacing	0.197" (5.00mm)
Report errors?	Lead Style	Formed Leads - Kinked
		Report errors?

B37984M5474K054 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B37984M5474K054 Payment Methods





If you have any question about B37984M5474K054, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com