



B37987M1473K000 Information



For Reference Only

Part Number B37987M1473K000
Manufacturer EPCOS (TDK)
Category Capacitors

Ceramic Capacitors

Description CAP CER 0.047UF 100V X7R RADIAL

Package Radia

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B37987M1473K000 Specifications

Manufacturer Part Number B37987M1473K000 Manufacturer EPCOS (TDK) Category Capacitors Package Radial Series B37987M Capacitance 0.047μF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings AEC-Q200 Applications Automotive Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.256" L x 0.197" W (6.50mm x 5.00mm) Height - Seated (Max) 0.098" (2.50mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Spacing Fermed Leads - Kinked		
Category Capacitors Package Radial Series B37987M Capacitance 0.047μF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings AEC-Q200 Applications Automotive Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.256" L x 0.197" W (6.50mm x 5.00mm) Height - Seated (Max) 0.098" (2.50mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Formed Leads - Kinked	Manufacturer Part Number	B37987M1473K000
Package Radial Series B37987M Capacitance 0.047μF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings AEC-Q200 Applications Automotive Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.256" L x 0.197" W (6.50mm x 5.00mm) Height - Seated (Max) 0.098" (2.50mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Formed Leads - Kinked	Manufacturer	EPCOS (TDK)
Package Radial Series B37987M Capacitance 0.047µF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings AEC-Q200 Applications Automotive Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.256" L x 0.197" W (6.50mm x 5.00mm) Height - Seated (Max) 0.098" (2.50mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Formed Leads - Kinked	Category	Capacitors
Series B37987M Capacitance 0.047µF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings AEC-Q200 Applications Automotive Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.256" L x 0.197" W (6.50mm x 5.00mm) Height - Seated (Max) 0.098" (2.50mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Formed Leads - Kinked		Ceramic Capacitors
Capacitance 0.047μF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings AEC-Q200 Applications Automotive Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.256" L x 0.197" W (6.50mm x 5.00mm) Height - Seated (Max) 0.098" (2.50mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Formed Leads - Kinked	Package	Radial
Tolerance ±10% Voltage - Rated 100V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings AEC-Q200 Applications Automotive Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.256" L x 0.197" W (6.50mm x 5.00mm) Height - Seated (Max) 0.098" (2.50mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Formed Leads - Kinked	Series	B37987M
Voltage - Rated100VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-RatingsAEC-Q200ApplicationsAutomotiveFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.256" L x 0.197" W (6.50mm x 5.00mm)Height - Seated (Max)0.098" (2.50mm)Thickness (Max)-Lead Spacing0.098" (2.50mm)Lead StyleFormed Leads - Kinked	Capacitance	0.047μF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features - Ratings AEC-Q200 Applications Applications Automotive Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.256" L x 0.197" W (6.50mm x 5.00mm) Height - Seated (Max) Thickness (Max) - Lead Spacing Lead Style Formed Leads - Kinked	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeatures-RatingsAEC-Q200ApplicationsAutomotiveFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.256" L x 0.197" W (6.50mm x 5.00mm)Height - Seated (Max)0.098" (2.50mm)Thickness (Max)-Lead Spacing0.098" (2.50mm)Lead StyleFormed Leads - Kinked	Voltage - Rated	100V
Features - AEC-Q200 Applications Automotive Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.256" L x 0.197" W (6.50mm x 5.00mm) Height - Seated (Max) 0.098" (2.50mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Formed Leads - Kinked	Temperature Coefficient	X7R
Ratings AEC-Q200 Applications Automotive Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.256" L x 0.197" W (6.50mm x 5.00mm) Height - Seated (Max) 0.098" (2.50mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Formed Leads - Kinked	Operating Temperature	-55°C ~ 125°C
Applications Automotive Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.256" L x 0.197" W (6.50mm x 5.00mm) Height - Seated (Max) 0.098" (2.50mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Formed Leads - Kinked	Features	-
Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.256" L x 0.197" W (6.50mm x 5.00mm) Height - Seated (Max) 0.098" (2.50mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Formed Leads - Kinked	Ratings	AEC-Q200
Mounting Type Through Hole Package / Case Radial Size / Dimension 0.256" L x 0.197" W (6.50mm x 5.00mm) Height - Seated (Max) 0.098" (2.50mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Formed Leads - Kinked	Applications	Automotive
Package / Case Radial Size / Dimension 0.256" L x 0.197" W (6.50mm x 5.00mm) Height - Seated (Max) 0.098" (2.50mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Formed Leads - Kinked	Failure Rate	-
Size / Dimension 0.256" L x 0.197" W (6.50mm x 5.00mm) Height - Seated (Max) 0.098" (2.50mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Formed Leads - Kinked	Mounting Type	Through Hole
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style 0.098" (2.50mm) Formed Leads - Kinked	Package / Case	Radial
Thickness (Max) Lead Spacing 0.098" (2.50mm) Lead Style Formed Leads - Kinked	Size / Dimension	0.256" L x 0.197" W (6.50mm x 5.00mm)
Lead Spacing0.098" (2.50mm)Lead StyleFormed Leads - Kinked	Height - Seated (Max)	0.098" (2.50mm)
Lead Style Formed Leads - Kinked	Thickness (Max)	-
	Lead Spacing	0.098" (2.50mm)
Report errors?	Lead Style	Formed Leads - Kinked
Report criors:		Report errors?

B37987M1473K000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B37987M1473K000 Payment Methods





















B37987M1473K000 Shipping Methods













If you have any question about B37987M1473K000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com