



B41002A6104M Information

Heisener.com

Part Number B41002A6104M
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 0.1UF 20% 50V RADIAL

Package Radial, Can

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B41002A6104M Specifications

Manufacturer Part Number B41002A6104M Manufacturer EPCOS (TDK) Category Capacitors Package Radial, Can Series B41002 Capacitance 0.1µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency ImA @ 120Hz Ripple Current - High Frequency 0.19mA @ 10kHz Impedance - Lead Spacing 0.059" (1.50mm) Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.315" (8.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can Report errors?	1	
Category Capacitors Package Radial, Can Series B41002 Capacitance 0.1µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1mA @ 120Hz Ripple Current - High Frequency 0.19mA @ 10kHz Impedance - Lead Spacing 0.059" (1.50mm) Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.315" (8.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer Part Number	B41002A6104M
Aluminum Electrolytic Capacitors	Manufacturer	EPCOS (TDK)
Package Radial, Can Series B41002 Capacitance 0.1μF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency ImA @ 120Hz Ripple Current - High Frequency 0.19mA @ 10kHz Impedance - Lead Spacing 0.059" (1.50mm) Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.315" (8.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series B41002 Capacitance 0.1 μF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1mA @ 120Hz Ripple Current - High Frequency 0.19mA @ 10kHz Impedance - Lead Spacing 0.059" (1.50mm) Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.315" (8.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 0.1μF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1mA @ 120Hz Ripple Current - High Frequency 0.19mA @ 10kHz Impedance - Lead Spacing 0.059" (1.50mm) Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.315" (8.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1mA @ 120Hz Ripple Current - High Frequency 0.19mA @ 10kHz Impedance - Lead Spacing 0.059" (1.50mm) Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.315" (8.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	B41002
Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1mA @ 120Hz Ripple Current - High Frequency 0.19mA @ 10kHz Impedance - Lead Spacing 0.059" (1.50mm) Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.315" (8.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Capacitance	0.1μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency ImA @ 120Hz Ripple Current - High Frequency 0.19mA @ 10kHz Impedance - Lead Spacing 0.059" (1.50mm) Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 0.19mA @ 120Hz Impedance - Lead Spacing 0.059" (1.50mm) Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Voltage - Rated	50V
Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 0.19mA @ 10kHz Impedance Lead Spacing 0.059" (1.50mm) Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1mA @ 120Hz Ripple Current - High Frequency 0.19mA @ 10kHz Impedance - Lead Spacing 0.059" (1.50mm) Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.315" (8.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	1000 Hrs @ 85°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency O.19mA @ 10kHz Impedance Lead Spacing O.059" (1.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case General Purpose ImA @ 120Hz O.19mA @ 10kHz Impedance - 0.059" (1.50mm) O.315" (8.00mm) Fig. (8.00mm) Through Hole Radial, Can	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency O.19mA @ 10kHz Impedance - Lead Spacing O.059" (1.50mm) Size / Dimension O.157" Dia (4.00mm) Height - Seated (Max) O.315" (8.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing 0.059" (1.50mm) Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.315" (8.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance - Lead Spacing 0.059" (1.50mm) Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.315" (8.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - Low Frequency	1mA @ 120Hz
Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	0.19mA @ 10kHz
Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.315" (8.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.059" (1.50mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.157" Dia (4.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.315" (8.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

B41002A6104M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B41002A6104M Payment Methods





















B41002A6104M Shipping Methods













If you have any question about B41002A6104M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com