

B41022A6335M

Request a Quote

B41022A6335M Information

(A) Heisener.com	Part Number	B41022A6335M
	Manufacturer	EPCOS (TDK)
	Category	Capacitors Aluminum Electrolytic Capacitors
A CONTRACTOR	Description	CAP ALUM 3.3UF 20% 50V RADIAL
	Package	Radial, Can
		For the pricing/inventory/lead time, please contact
		us
For Reference Only		Website: https://www.heisener.com
I of Reference Only		E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B41022A6335M Specifications

ManufacturerEPCOS (TDK)CapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageB41022Capacitance3.3µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-ApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lied Spacing0.059° (1.50mm)Siz / Dimension0.059° (1.50mm)Size / Dimension0.157° Dia (4.00mm)Height - Seated (Max)3.015° (8.00mm)Surface Mount Land Size-Mounting TypeThrough Hole		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageB41022Capacitance3.3µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Package / CaseRatial, Can	Manufacturer Part Number	B41022A6335M
Aluminum Electrolytic CapacitorsPackageRadial, CanPackageB41022Capacitance3.3µFTolerance±20%Voltage - RatedSoVESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-PolarizationGeneral PurposeRiple Current - Low Frequency-Riple Current - High Frequency-Impedance-Lad Spacing0.059° (1.50mm)Size / Dimension0.157° Dia (4.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer	EPCOS (TDK)
PackageRadial, CanSeriesB41022Capacitance3.3µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-PolarizationGeneral PurposeRiple Current - Low Frequency-Riple Current - High Frequency-Impedance-Lad Spacing0.059° (1.50mm)Size / Dimension0.157° Dia (4.00mm)Height - Seated (Max)0.315° (8.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Category	Capacitors
SeriesB41022Capacitance3.3μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.059° (1.50mm)Size / Dimension0.157° Dia (4.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeFrough HolePackage / CaseRatial, Can		Aluminum Electrolytic Capacitors
Capacitance3.3µFTolerance±20%Voltag - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Lifed Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseKadial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency24mA @ 120HzImpedance-Lead Spacing0.55° (1.50mm)Size / Dimension0.157° Dia (4.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Pokage / CaseRatial, Can	Series	B41022
Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency24mA @ 120HzImpedance-Lead Spacing0.059° (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Pockage / CaseRadial, Can	Capacitance	3.3µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency24mA @ 120HzBipple Current - High Frequency-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Poncations-Rounting TypeRadial, Can	Tolerance	±20%
Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency24mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can	Voltage - Rated	50V
Operating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency24mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeFunculationPackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency24mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	1000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency24mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-
Ripple Current - Low Frequency24mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In a constraint of a constrain	Applications	General Purpose
Impedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	24mA @ 120Hz
Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.059" (1.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.157" Dia (4.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.315" (8.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

B41022A6335M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B41022A6335M Payment Methods





If you have any question about B41022A6335M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com