



B41041A6227M Information

Manufact
Category

Part Number B41041A6227M
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 220UF 20% 50V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B41041A6227M Specifications

Manufacturer Part Number B41041A6227M Manufacturer EPCOS (TDK) Category Capacitors Package Radial, Can Series B41041 Capacitance 220μF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 404mA @ 120Hz Ripple Current - High Frequency - Impedance 270 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can Report errors?	L	
Category Capacitors Package Radial, Can Series B41041 Capacitance 220µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 404mA @ 120Hz Ripple Current - High Frequency - Impedance 270 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer Part Number	B41041A6227M
Aluminum Electrolytic Capacitors Package Radial, Can Series B41041 Capacitance 220µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 270 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Manufacturer	EPCOS (TDK)
Package Radial, Can Series B41041 Capacitance 220μF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 404mA @ 120Hz Ripple Current - High Frequency - Impedance 270 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series B41041 Capacitance 220μF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 404mA @ 120Hz Ripple Current - High Frequency - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 220µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 404mA @ 120Hz Ripple Current - High Frequency - Impedance 270 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 404mA @ 120Hz Ripple Current - High Frequency - Impedance 270 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	B41041
Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 404mA @ 120Hz Ripple Current - High Frequency - Impedance 270 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Capacitance	220μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 404mA @ 120Hz Ripple Current - High Frequency Impedance 270 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Polar -40°C ~ 105°C -40°C	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 2000 Hrs @ 105°C -40°C ~	Voltage - Rated	50V
Operating Temperature Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing O.197" (5.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Page General Purpose General Purpose A04MA @ 120Hz - Cannother Commondate - Cannother Commondate Commondat	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 404mA @ 120Hz Ripple Current - High Frequency - Impedance 270 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications Ripple Current - Low Frequency 404mA @ 120Hz Ripple Current - High Frequency - Impedance 270 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 270 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance 270 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance 270 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - Low Frequency	404mA @ 120Hz
Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.689" (17.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	270 mOhms
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.394" Dia (10.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.689" (17.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

B41041A6227M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B41041A6227M Payment Methods



















B41041A6227M Shipping Methods













If you have any question about B41041A6227M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com