

B41041A8226M Information

Manufacturer EPCOS (TDK)
Category Capacitors
Aluminum Elec

Capacitors
Aluminum Electrolytic Capacitors

Description CAP ALUM 22UF 20% 63V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Part Number B41041A8226M

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B41041A8226M Specifications

Manufacturer Part Number B41041A8226M Manufacturer EPCOS (TDK) Category Capacitors Package Radial, Can Series B41041 Capacitance 22µF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Operating Temperature 90lar Applications General Purpose Ripple Current - Low Frequency 65mA @ 120Hz Ripple Current - High Frequency 130mA @ 100kHz Impedance 2.1 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can Report errors?	L	
Category Capacitors Package Radial, Can Series B41041 Capacitance 22µF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 65mA @ 120Hz Ripple Current - High Frequency 130mA @ 100kHz Impedance 2.1 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer Part Number	B41041A8226M
Package Radial, Can Series B41041 Capacitance 22μF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 65mA @ 120Hz Ripple Current - High Frequency 130mA @ 100kHz Impedance 2.1 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer	EPCOS (TDK)
Package Radial, Can Series B41041 Capacitance 22μF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 65mA @ 120Hz Ripple Current - High Frequency 130mA @ 100kHz Impedance 2.1 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series B41041 Capacitance 22µF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 65mA @ 120Hz Ripple Current - High Frequency 130mA @ 100kHz Impedance 2.1 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 22μF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 65mA @ 120Hz Ripple Current - High Frequency 130mA @ 100kHz Impedance 2.1 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 65mA @ 120Hz Ripple Current - High Frequency 130mA @ 100kHz Impedance 2.1 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	B41041
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 130mA @ 120Hz Impedance 2.1 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Polor -000 Hrs @ 105°C -000	Capacitance	22μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polar Applications Ripple Current - Low Frequency Ripple Current - High Frequency Ripple Current - High Frequency 130mA @ 120Hz Rippedance 2.1 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 130mA @ 120Hz Impedance 2.1 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Voltage - Rated	63V
Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 130mA @ 120Hz Impedance 2.1 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 65mA @ 120Hz Ripple Current - High Frequency 130mA @ 100kHz Impedance 2.1 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications Ripple Current - Low Frequency 65mA @ 120Hz Ripple Current - High Frequency 130mA @ 100kHz Impedance 2.1 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency 130mA @ 100kHz Impedance 2.1 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance 2.1 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance 2.1 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - Low Frequency	65mA @ 120Hz
Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	130mA @ 100kHz
Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	2.1 Ohms
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.098" (2.50mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.248" Dia (6.30mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.492" (12.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

B41041A8226M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B41041A8226M Payment Methods



















B41041A8226M Shipping Methods













If you have any question about B41041A8226M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com