

B41041A9107M

Request a Quote

B41041A9107M Information

Heisener.com	Part Number	B41041A9107M
	Manufacturer	EPCOS (TDK)
	Category	Capacitors Aluminum Electrolytic Capacitors
	Description	CAP ALUM 100UF 20% 100V RADIAL
	Package	Radial, Can
		For the pricing/inventory/lead time, please contact
For Reference Only		us
		Website: https://www.heisener.com
		E-mail: salesdept@heisener.com



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B41041A9107M Specifications

Manufacturer Part Number B41041A9107M Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series B41041 Capacitance IOUpF Tolerance ±20% Voltage - Rated IOUV SER (Equivalent Series Resistance) - Voltage - Rated 2000 Hrs © 105°C Operating Temperature 40°C ~ 105°C Operating Temperature 400.5°C Applications General Purpose Apple Current - Low Frequency 400.5°CA Kippe Current - High Frequency - Voltage - Streig 200 Hrs Kippe Current - High Frequency 200 Hrs Voltage - Streig 200 Hrs Voltage - Streig 200 Hrs Kippe Current - High Frequency 400.5°CA Voltage - Streig 200 Hrs	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41041Capacitance100µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency409.5mA @ 120HzRipple Current - High Frequency0.197" (5.00mm)Lied Spacing0.197" (5.00mm)Size / Dimension0.4492" Dia (12.50mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeFinough HolePackage / CaseRadial, Can	Manufacturer Part Number	B41041A9107M
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41041Capacitance100µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency409.5mA @ 120HzImpedance280 mOhmsLiad Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Size / Dimension0.492" Dia (12.50mm)Sizer Adomut Land Size-Hurding TypePalaeRounting TypeRadial, Can	Manufacturer	EPCOS (TDK)
PackageRadial, CanSeriesB41041Capacitance100µFTolerance20%Voltage - Rated000 VESR (Equivalent Series Resistance)-Operating Temperature2000 Hrs @ 105°COperating TemperaturePolarApplicationsGeneral PurposeRipple Current - Low Frequency6Ripple Current - High Frequency2800 Mrs.Lided Spacing0.91°T (5.00mm)Size / Dimension0.49°C (1.50mm)Size / Dimension0.49°C (1.50mm)Size / Dimension0.49°C (1.50mm)Sizer Adduktionalize0.49°C (1.50mm) <td>Category</td> <td>Capacitors</td>	Category	Capacitors
SeriesB41041Capacitance100µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency409.5mA @ 120HzImpedance1.907" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Size / Dimension0.446" (21.50mm)Surface Mount Land Size-Mounting Type-Polaring Type-Strafe Conse5.46" (21.50mm)Surface Mount Land Size-Mounting Type-Polaring Type-Polaring Type-Strafe Conse-Mounting Type-Polaring Type- </td <td></td> <td>Aluminum Electrolytic Capacitors</td>		Aluminum Electrolytic Capacitors
Capacitance100µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Ingedance280 MOhmsLiad Spacing0.197°(5.00mm)Size / Dimension0.492° Dia (12.50mm)Size / Dimension0.494° Dia (12.50mm)Surface Mount Land Size-Mounting TypeForugh HolePackage / CaseRatial Can	Package	Radial, Can
Tolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency409.5mA @ 120HzImpedance280 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Hounting TypeMounting TypePackage / CaseKalia, Can	Series	B41041
Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency409.5mA @ 120HzRipple Current - High Frequency-Impedance280 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can	Capacitance	100µF
ESR (Equivalent Series Resistance)-ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency409.5mA @ 120HzRipple Current - High Frequency280 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency409.5mA @ 120HzRipple Current - High Frequency-Impedance280 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Hight - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeFurough LandePackage / CaseRadial, Can	Voltage - Rated	100V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency409.5mA @ 120HzRipple Current - High Frequency-Impedance280 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeFrequencyPackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency409.5mA @ 120HzRipple Current - High Frequency-Impedance280 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency409.5mA @ 120HzRipple Current - High Frequency-Impedance280 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadia, Can	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency409.5mA @ 120HzRipple Current - High Frequency-Impedance280 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency-Impedance280 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance280 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	409.5mA @ 120Hz
IILead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	280 mOhms
Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.492" Dia (12.50mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.846" (21.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

B41041A9107M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B41041A9107M Payment Methods



B41041A9107M Shipping Methods



If you have any question about B41041A9107M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com