

B41041B7476M

Request a Quote

B41041B7476M Information

Heisener.com	Part Number	B41041B7476M
	Manufacturer	EPCOS (TDK)
	Category	Capacitors Aluminum Electrolytic Capacitors
	Description	CAP ALUM 47UF 20% RADIAL
	Package	Radial, Can
		For the pricing/inventory/lead time, please contact
For Reference Only		us
		Website: https://www.heisener.com
		E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B41041B7476M Specifications

Manufacturer Part Number B41041B7476M Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Scries B41041 Capacitance 47µF Tolerance -20% Voltage - Rated -20% Scries Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization General Purpose Applications General Purpose Ripple Current + High Frequency - Impedance - Lead Spacing 0.079° (2.00mm) Size / Dimension 0.197° Dia (5.00mm) Size / Dimension 0.492° (12.50mm) Size / Dimension - Mounting Type - Parce Mount Land Size - Mounting Type -		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41041Capacitance47µFTolerance±20%Voltage - Rated-ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-000 Hrs @ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance-Liad Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Pounting TypeFrough HolePackage / CaseKadia, Can	Manufacturer Part Number	B41041B7476M
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41041Capacitance47µFTolerance±20%Voltage - Rated-ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeApplications-Ripple Current - Low Frequency-Ripple Current - High Frequency-Lide Spacing0.079° (2.00mm)Size / Dimension0.197° Dia (5.00mm)Size / Dimension0.492° (12.50mm)Hight - Seated (Max)-Mounting TypeFinough HolePackage / CaseRadial, Can	Manufacturer	EPCOS (TDK)
PackageRadial, CanSeriesB41041Capacitance47µFTolerance±20%Voltage - Rated-ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRiple Current - Low Frequency-Linedance0.007° (2.00mm)Siz / Dimension0.197° Dia (5.00mm)Siz / Dimension0.49° (12.50mm)Height - Seated (Max)0.492° (12.50mm)Surface Mount Land Size-Mounting TypeFanceanPackage / CaseKadial, Can	Category	Capacitors
SeriesB41041Capacitance47μFTolerance±20%Voltage - Rated-ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ingedance-Liad Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting Type-Polaring Type-Surface Mount Land Size-Surface Mount Land Size <td< td=""><td></td><td>Aluminum Electrolytic Capacitors</td></td<>		Aluminum Electrolytic Capacitors
Capacitance47µFCapacitance±20%Tolerance±20%Voltage Rated-ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.079° (2.00mm)Size / Dimension0.40°C "105°CHeight - Seated (Max)0.492° (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated-ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarzationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Hight - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Series	B41041
Voltage - Rated-ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Argulance-Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeMail AcanPackage / CaseRatial Can	Capacitance	47µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature- 40°C ~ 105°CPolarPolarApplicationsGeneral PurposeApple Current - Low Frequency-Mippedance-Impedance-Size / Dimension0.079° (2.00mm)Size / Dimension0.492° (12.50mm)Height - Seated (Max)-Mounting Type-Package / CaseMich Ale CaseRest Purp Case-Rot Purp Case-Ring Case- <td>Tolerance</td> <td>$\pm 20\%$</td>	Tolerance	$\pm 20\%$
Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeAipple Current - Low Frequency-Impedance-Impedance0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Hounting TypeFrough HolePackage / CaseRadial, Can	Voltage - Rated	-
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Arpedance-Impedance0.079°(2.00mm)Size / Dimension0.197° Dia (5.00mm)Height - Seated (Max)0.492° (12.50mm)Surface Mount Land Size-Mounting TypeRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 105°C
ApplicationsGeneral PurposeApplications-Ripple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	$-40^{\circ}C \sim 105^{\circ}C$
Ripple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency-Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	-
Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - High Frequency	-
Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.079" (2.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.197" Dia (5.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.492" (12.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

B41041B7476M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B41041B7476M Payment Methods





If you have any question about B41041B7476M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com