



B41041C7228M Information

Manufacturer EPCOS (TDK) Category Heisener.com

Aluminum Electrolytic Capacitors

Description CAP ALUM 2200UF 20% RADIAL

Capacitors

Package

For the pricing/inventory/lead time, please contact

Part Number B41041C7228M

Website: https://www.heisener.com For Reference Only E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B41041C7228M Specifications

Manufacturer Part Number B41041C7228M Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series B41041 Capacitance 2200µF Tolerance ±20% Voltage - Rated - ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Hight State (Max) 1.45(# (27.50mm))	2 110 110 / 22 of 1 Specifications	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series B41041 Capacitance 2200µF Tolerance ±20% Voltage - Rated - ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm)	Manufacturer Part Number	B41041C7228M
Aluminum Electrolytic Capacitors	Manufacturer	EPCOS (TDK)
Package Radial, Can Series B41041 Capacitance 2200μF Tolerance ±20% Voltage - Rated - ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm)	Category	Capacitors
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$		Aluminum Electrolytic Capacitors
Capacitance $2200\mu F$ Tolerance $\pm 20\%$ Voltage - Rated - ESR (Equivalent Series Resistance) - Lifetime @ Temp. $2000 \text{ Hrs } @ 105^{\circ}C$ Operating Temperature $-40^{\circ}C \sim 105^{\circ}C$ Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.295° (7.50mm) Size / Dimension 0.630° Dia (16.00mm)	Package	Radial, Can
Tolerance ±20% Voltage - Rated - ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm)	Series	B41041
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension - ESS (Equivalent Series Resistance) -40°C ~ 105°C -40°C	Capacitance	2200μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing O.295" (7.50mm) Size / Dimension	Tolerance	±20%
Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm)	Voltage - Rated	-
Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing O.295" (7.50mm) Size / Dimension -40°C ~ 105°C Polar Polar	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm)	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing O.295" (7.50mm) Size / Dimension General Purpose - 0.295" (7.50mm)	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm)	Polarization	Polar
Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm)	Applications	General Purpose
Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm)	Ripple Current - Low Frequency	-
Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm)	Ripple Current - High Frequency	-
Size / Dimension 0.630" Dia (16.00mm)	Impedance	-
· · · · · ·	Lead Spacing	0.295" (7.50mm)
11-1-14 C	Size / Dimension	0.630" Dia (16.00mm)
Height - Seated (Max) 1.4/6" (37.50mm)	Height - Seated (Max)	1.476" (37.50mm)
Surface Mount Land Size -	Surface Mount Land Size	-
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Radial, Can	Package / Case	Radial, Can
Report errors?		Report errors?

B41041C7228M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B41041C7228M Payment Methods



















B41041C7228M Shipping Methods













If you have any question about B41041C7228M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com