

B41042A6156M

Request a Quote

B41042A6156M Information

Part Number	B41042A6156M	
Manufacturer	EPCOS (TDK)	
Category	Capacitors Aluminum Electrolytic Capacitors	
Description	CAP ALUM 15UF 20% 50V RADIAL	
Package	Radial, Can	
	For the pricing/inventory/lead time, please contact	
	us	
	Website: https://www.heisener.com	
	E-mail: salesdept@heisener.com	
	Manufacturer Category Description	Aluminum Electrolytic Capacitors Description CAP ALUM 15UF 20% 50V RADIAL Package Radial, Can For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B41042A6156M Specifications

Manufacturer Part NumberB41042A6156MManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41042Capacitance15µFTolerance20%Voltage - Rated50VESR (Equivalent Series Resistance)-Operating Temperature55°C ~ 105°CPolarizationGeneral PurposeApplications60reral PurposeRippe Current - High Frequency148mA @ 100kHzInpedance2.3 OhmsLead Spacing0.079" (2.00mm)
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41042Capacitance15µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency81.4mA @ 120HzImpedance2.3 Ohms
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41042Capacitance15µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency81.4mA @ 120HzImpedance2.3 Ohms
PackageRadial, CanSeriesB41042Capacitance15µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationGeneral PurposeApplicationsS14mA @ 120HzRipple Current - High Frequency148mA @ 100kHzImpedance2.3 Ohms
SeriesB41042Series15µFCapacitance±20%Tolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency81.4mA @ 120HzRipple Current - High Frequency2.3 Ohms
Capacitance15µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105 °COperating Temperature-55° C ~ 105 °CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency81.4mA @ 120 HzRipple Current - High Frequency148mA @ 100 kHzImpedance2.3 Ohms
Tolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency81.4mA @ 120HzRipple Current - High Frequency148mA @ 100kHzImpedance2.3 Ohms
Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency81.4mA @ 120HzRipple Current - High Frequency148mA @ 100kHzImpedance2.3 Ohms
ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency81.4mA @ 120HzRipple Current - High Frequency148mA @ 100kHzImpedance2.3 Ohms
Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency81.4mA @ 120HzRipple Current - High Frequency148mA @ 100kHzImpedance2.3 Ohms
Operating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency81.4mA @ 120HzRipple Current - High Frequency148mA @ 100kHzImpedance2.3 Ohms
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency81.4mA @ 120HzRipple Current - High Frequency148mA @ 100kHzImpedance2.3 Ohms
ApplicationsGeneral PurposeRipple Current - Low Frequency81.4mA @ 120HzRipple Current - High Frequency148mA @ 100kHzImpedance2.3 Ohms
Ripple Current - Low Frequency81.4mA @ 120HzRipple Current - High Frequency148mA @ 100kHzImpedance2.3 Ohms
Ripple Current - High Frequency148mA @ 100kHzImpedance2.3 Ohms
Impedance 2.3 Ohms
Lead Spacing 0.079" (2.00mm)
Size / Dimension 0.197" Dia (5.00mm)
Height - Seated (Max) 0.492" (12.50mm)
Surface Mount Land Size -
Mounting Type Through Hole
Package / Case Radial, Can
Report errors?

B41042A6156M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B41042A6156M Payment Methods



B41042A6156M Shipping Methods



If you have any question about B41042A6156M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com