

B41043A7567M

Request a Quote

B41043A7567M Information

Heisener.com	Part Number	B41043A7567M
	Manufacturer	EPCOS (TDK)
	Category	Capacitors Aluminum Electrolytic Capacitors
	Description	CAP ALUM 560UF 20% 35V RADIAL
	Package	Radial, Can
		For the pricing/inventory/lead time, please contact
For Reference Only		us
		Website: https://www.heisener.com
i or restorence only		E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B41043A7567M Specifications

ManufacturerEPCOS (TDK)CapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageB41043Capacitance560µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature5000 Hrs @ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency1.16A @ 100kHzImpedance1.16A @ 100kHzLied Spacing0.197° (5.00mm)Size / Dimension0.492° Dia (12.50mm)Height - Seated (Max)0.866° (22.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	_	
CapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageB41043Capacitance560µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.16A @ 100kHzImpedance41 mOhmsLead Spacing0.197" (5.00mm)Siz / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Manufacturer Part Number	B41043A7567M
Adminum Electrolytic CapacitorsPackageRadial, CanSeriesB41043Capacitance560μFtolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature5000 Hrs @ 105°CPolarizationPolarApplicationsGeneral PurposeRiple Current - Low Frequency928mA @ 120HzRiple Current - High Frequency1.16A @ 100kHzInpedance41 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer	EPCOS (TDK)
PackageRadial, CanSeriesB41043Capacitance560µFTolerance±20%Voltage - RatedSvESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature5000 Hrs @ 105°CPolarizationPolarApplicationsGeneral PurposeRiple Current - Low Frequency928mA @ 120HzRiple Current - High Frequency1.16A @ 100kHzImpedance0.197" (5.00mm)Siz / Dimension0.492" Dia (12.50mm)Size / Dimension0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Category	Capacitors
SeriesB41043Capacitance560μFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency928mA @ 120HzImpedance41 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Bight - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can		Aluminum Electrolytic Capacitors
Capacitance560µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency928mA @ 120HzImpedance1.16A @ 100kHzLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can	Package	Radial, Can
Tolerance±0%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolartPolarApplicationsGeneral PurposeRipple Current - Low Frequency928mA @ 120HzImpedance41 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Pokage / CaseRatial, Can	Series	B41043
Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency928mA @ 120HzImpedance1.16A @ 100kHzLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Pokage / CaseRatial, Can	Capacitance	560µF
For a constraint of the series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency928mA @ 120HzImpedance1.16A @ 100kHzLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Pounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency928mA @ 120HzInpedance41 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	35V
Operating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency928mA @ 120HzRipple Current - High Frequency1.16A @ 100kHzImpedance41 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max).Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency928mA @ 120HzRipple Current - High Frequency1.16A @ 100kHzImpedance41 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	5000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency928mA @ 120HzRipple Current - High Frequency1.16A @ 100kHzImpedance41 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-55°C ~ 105°C
APRipple Current - Low Frequency928mA @ 120HzRipple Current - High Frequency1.16A @ 100kHzImpedance41 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In a constraint of a constrain	Applications	General Purpose
In performance41 mOhmsImpedance41 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	928mA @ 120Hz
IILead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	1.16A @ 100kHz
Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	41 mOhms
Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.492" Dia (12.50mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.866" (22.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

B41043A7567M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B41043A7567M Payment Methods



B41043A7567M Shipping Methods



If you have any question about B41043A7567M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com