

B41044A2477M

Request a Quote

B41044A2477M Information

Heisener.com	Part Number	B41044A2477M	
	Manufacturer	EPCOS (TDK)	
	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 470UF 20% 6.3V RADIAL	
	Package	Radial, Can	
		For the pricing/inventory/lead time, please contact	
		us	
For Reference Only		Website: https://www.heisener.com	
I of Reference Only		E-mail: salesdept@heisener.com	



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B41044A2477M Specifications

Manufacturer Part Number B41044A2477M Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series B41044 Capacitance 44004 Orlerance 420% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) - Operating Temperature - Operating Temperature 9alar Applications General Purpose Apple Current - High Frequency 450mA @ 100kHz Ippedance 140 mOhms Lead Spacing 0.31s" Dia (8.00mm) Size / Dimension 0.31s" Dia (8.00mm) Surface Mount Land Size - Mounting Type Frough Hole	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41044Capacitance470μFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-PolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency337.5mA @ 120HzRipple Current - High Frequency450mA @ 100kHzImpedance140 mOhmsLead Spacing0.315" Dia (8.00mm)Size / Dimension0.512" (13.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Manufacturer Part Number	B41044A2477M
Adminum Electrolytic CapacitorsPackageRadial, CanSeriesB41044Capacitance470µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-PolarizationGeneral PurposeRipple Current - Low Frequency337.5mA @ 120HzRipple Current - High Frequency450mA @ 100kHzImpedance140 mOhmsLead Spacing0.315° Dia (8.00mm)Size / Dimension0.512° (13.00mm)Size / Dimension0.512° (13.00mm)Surface Mount Land Size-Mounting TypeRadial, Can	Manufacturer	EPCOS (TDK)
PackageRadial, CanSeriesB41044Capacitance470µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency337.5mA @ 120HzRipple Current - High Frequency0.138" (3.50mm)Lied Spacing0.315" Dia (8.00mm)Size / Dimension0.512" (13.00mm)Size / Dimension5.12" (13.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Category	Capacitors
AreaB41044Capacitance470µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency337.5mA @ 120HzImpedance140 mOhmsLad Spacing0.138° (3.50mm)Size / Dinension0.315" Dia (8.00mm)Surface Mount Land Size-Mounting TypeFrough HolePotaning TypeMounting TypePokage / CaseKail, Can		Aluminum Electrolytic Capacitors
Capacitance470µFTolerance±20%Voltage Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs@ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRippe Current - Low Frequency337.5mA @ 120HzImpedance140 mOhmsLead Spacing0.315° Dia (8.00mm)Size / Dimension0.512° (13.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThroug HolePackage / CaseKaida (Can	Package	Radial, Can
Tolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency337.5mA @ 120HzMipedance140 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Series	B41044
Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency337.5mA @ 120HzRipple Current - High Frequency450mA @ 100kHzImpedance1.40 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.512" (13.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKaila (Can	Capacitance	470µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency337.5mA @ 120HzMipedance140 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.512" (13.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency337.5mA @ 120HzBippe Current - High Frequency450mA @ 100kHzImpedance140 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeFackage / CaseRadial, CanRadial, Can	Voltage - Rated	6.3V
Operating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency337.5mA @ 120HzRipple Current - High Frequency450mA @ 100kHzImpedance140 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max).Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency337.5mA @ 120HzRipple Current - High Frequency450mA @ 100kHzImpedance140 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	3000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency337.5mA @ 120HzRipple Current - High Frequency450mA @ 100kHzImpedance140 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-
Ripple Current - Low Frequency337.5mA @ 120HzRipple Current - High Frequency450mA @ 100kHzImpedance140 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency450mA @ 100kHzImpedance140 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance140 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	337.5mA @ 120Hz
Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	450mA @ 100kHz
Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	140 mOhms
Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.138" (3.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.315" Dia (8.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.512" (13.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

B41044A2477M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B41044A2477M Payment Methods





If you have any question about B41044A2477M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com