

B41044A6107M

Request a Quote

B41044A6107M Information

Heisener.com	Part Number	B41044A6107M	
	Manufacturer	EPCOS (TDK)	
	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 100UF 20% 50V RADIAL	
	Package	Radial, Can	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Wahaita https://www.haisanan.com	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B41044A6107M Specifications

ManufacturerEPCOS (TDK)CapacitorsCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41044Capacitance100µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-PolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency330m Am 210HzImpedance0.138" (3.50mm)Lied Spacing0.315" Dia (8.00mm)Size / Dimension0.512" (13.00mm)Height - Seated (Max)5.12" (13.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	_	
CapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageB41044Capacitance100µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-PolarizationGeneral PurposeRipple Current - Low Frequency340mA @ 100kHzRipple Current - High Frequency350 mOhmsLied Spacing0.315" Dia (8.00mm)Size / Dimension0.512" (13.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Package / CaseRatial, Can	Manufacturer Part Number	B41044A6107M
Adminum Electrolytic CapacitorsPackageRadial, CanSeriesB41044Capacitance100μFtolerance±20%Voltage - RatedSoVESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-PolarizationGeneral PurposeRipple Current - Low Frequency328mA @ 120HzRipple Current - High Frequency350 mOhmsLad Spacing0.138° (3.50mm)Size / Dimension0.512° (13.00mm)Height - Seated (Max)0.512° (13.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer	EPCOS (TDK)
PackageRadial, CanSeriesB41044Capacitance100µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-PolarizationGeneral PurposeRiple Current - Low Frequency328mA @ 120HzRiple Current - High Frequency350 mOhmsLiad Spacing0.138" (3.50mm)Size / Dimension0.512" (13.00mm)Size / Dimension5.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Category	Capacitors
SeriesB41044Capacitance100µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency340mA @ 100kHzImpedance350 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can		Aluminum Electrolytic Capacitors
Capacitance100µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency340mA @ 100kHzImpedance350 mOhmsLead Spacing0.138° (3.50mm)Size / Dimension0.512° (13.00mm)Height - Seated (Max)-Surface Mount Land Size-Pounting TypeThrough HolePackage / CaseKaida, Can	Package	Radial, Can
Tolerance±0%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency238mA @ 120HzRipple Current - High Frequency340mA @ 100kHzImpedance0.138" (3.50mm)Lead Spacing0.315" Dia (8.00mm)Size / Dimension0.512" (13.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Series	B41044
Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency238mA @ 120HzBipple Current - High Frequency340mA @ 100kHzImpedance0.138" (3.50mm)Lead Spacing0.315" Dia (8.00mm)Size / Dimension0.512" (13.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Pockage / CaseRatial, Can	Capacitance	100µF
For a constraint of the series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency238mA @ 120HzBipple Current - High Frequency340mA @ 100kHzImpedance350 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.512" (13.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	$\pm 20\%$
Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency238mA @ 120HzBipple Current - High Frequency340mA @ 100kHzImpedance350 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)5.12" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	50V
Operating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency238mA @ 120HzBipple Current - High Frequency340mA @ 100kHzImpedance350 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max).Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency238mA @ 120HzRipple Current - High Frequency340mA @ 100kHzImpedance350 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	3000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency238mA @ 120HzRipple Current - High Frequency340mA @ 100kHzImpedance350 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-
Ripple Current - Low Frequency238mA @ 120HzRipple Current - High Frequency340mA @ 100kHzImpedance350 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
InInRipple Current - High Frequency340mA @ 100kHzImpedance350 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance350 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	238mA @ 120Hz
Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	340mA @ 100kHz
Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	350 mOhms
Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.138" (3.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.315" Dia (8.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.512" (13.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

B41044A6107M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B41044A6107M Payment Methods



B41044A6107M Shipping Methods



If you have any question about B41044A6107M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com