


B41044A8476M

Request a Quote

B41044A8476M Information

	Part Number	B41044A8476M
Heisener.com	Manufacturer	EPCOS (TDK)
	Category	Capacitors Aluminum Electrolytic Capacitors
	Description	CAP ALUM 47UF 20% 63V RADIAL
	Package	Radial, Can
		For the pricing/inventory/lead time, please contact
		us
Reference Only		Website: https://www.heisener.com
Reference Only		E-mail: salesdept@heisener.com



For

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B41044A8476M Specifications

ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41044Capacitance47µFTolerance±20%Voltage - Rated63∨ESR (Equivalent Series Resistance)-Operating Temperature3000 Hrs @ 105°COperating Temperature9arApplicationsGeneral PurposeRipple Current - High Frequency328mA @ 100kHzImpedance500 mOhmsLied Spacing0.138° (3.50mm)Size / Dimension0.131° Dia (8.00mm)Height - Seated (Max)5.12° (13.00mm)Surface Mount Land Size-Mounting TypeThough Hole		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41044Capacitance47µFTolerance±20%6Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency328mA @ 100kHzImpedance500 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.512" (13.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer Part Number	B41044A8476M
Adminum Electrolytic CapacitorsPackageRadial, CanSeriesB41044Capacitance47μFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-PolarizationGeneral PurposeRipple Current - Low Frequency229.6mA @ 120HzRipple Current - High Frequency328mA @ 100kHzImpedance500 mOhmsLead Spacing0.138° (3.50mm)Size / Dimension0.512° (13.00mm)Height - Seated (Max)0.512° (13.00mm)Surface Mount Land Size-Package / CaseKadial, Can	Manufacturer	EPCOS (TDK)
PackageRadial, CanSeriesB41044Capacitance47µFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-PolarizationGeneral PurposeApplications229.6mA @ 120HzRipple Current - Low Frequency328mA @ 100kHzImpedance500 mOhmsLiad Spacing0.138° (3.50mm)Size / Dimension0.512° (13.00mm)Size / Dimension0.512° (13.00mm)Height - Seated (Max)0.512° (13.00mm)Surface Mount Land Size-Package / CaseKadial, Can	Category	Capacitors
SeriesB41044Capacitance47μFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency229.6mA @ 120HzImpedance500 mOhmsLiad Spacing0.138° (3.50mm)Size / Dimension0.315° Dia (8.00mm)Height - Seated (Max)0.512° (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKaila, Can		Aluminum Electrolytic Capacitors
Capacitance47µFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Hugh Frequency229.6mA @ 120HzImpedance500 mOhmsLiad Spacing0.138° (3.50mm)Size / Dimension0.512° (13.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKaila, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency229.6mA @ 120HzImpedance500 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.512" (13.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Series	B41044
Notage - RatedG3VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency229.6mA @ 120HzBipple Current - High Frequency328mA @ 100kHzImpedance500 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.512" (13.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeRadial, Can	Capacitance	47µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency229.6mA @ 120HzBipple Current - High Frequency328mA @ 100kHzImpedance500 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	$\pm 20\%$
Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency229.6mA @ 120HzRipple Current - High Frequency328mA @ 100kHzImpedance500 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.512" (13.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	63V
Operating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency229.6mA @ 120HzRipple Current - High Frequency328mA @ 100kHzImpedance500 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max).Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency229.6mA @ 120HzRipple Current - High Frequency328mA @ 100kHzImpedance500 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	3000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency229.6mA @ 120HzRipple Current - High Frequency328mA @ 100kHzImpedance500 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-
Ripple Current - Low Frequency229.6mA @ 120HzRipple Current - High Frequency328mA @ 100kHzImpedance500 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In a constraint of the first	Applications	General Purpose
Impedance500 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	229.6mA @ 120Hz
Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	328mA @ 100kHz
Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	500 mOhms
Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.138" (3.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.315" Dia (8.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.512" (13.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

B41044A8476M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B41044A8476M Payment Methods





If you have any question about B41044A8476M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com