

B41044A9335M

Request a Quote

B41044A9335M Information

| | Part Number | B41044A9335M |
|----------------|--------------|---|
| | Manufacturer | EPCOS (TDK) |
| Heisener.com | Category | Capacitors Aluminum Electrolytic Capacitors |
| | Description | CAP ALUM 3.3UF 20% 100V RADIAL |
| | Package | Radial, Can |
| | | For the pricing/inventory/lead time, please contact |
| | | us |
| Reference Only | | Website: https://www.heisener.com |
| Reference Only | | E-mail: salesdept@heisener.com |



For

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B41044A9335M Specifications

| Manufacturer Part NumberB41044A9335MManufacturerEPCOS (TDK)CategoryCapacitorsCategoryAluninum Electrolytic CapacitorsPackageRadial, CanPackageB41044SeriesB41044Capacitance3.3µFYoltage - Rated100VESR (Equivalent Series Resistance)-Derating Temperature2000 Hrs @ 105°COperating TemperaturePolarApplicationsGeneral PurposeApplicationsGeneral PurposeRippe Current - Low Frequency-Series - Low Frequency- <td< th=""><th></th><th></th></td<> | | |
|---|------------------------------------|----------------------------------|
| CategoryCapacitorsCategoryAluminum Electrolytic CapacitorsPackageRadial, CanPackageB41044Capacitance3.3µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRippe Current - Low Frequency- | Manufacturer Part Number | B41044A9335M |
| Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41044Capacitance3.3µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency- | Manufacturer | EPCOS (TDK) |
| PackageRadial, CanSeriesB41044Capacitance3.3µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency- | Category | Capacitors |
| SeriesB41044Capacitance3.3μFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105 °COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency- | | Aluminum Electrolytic Capacitors |
| Capacitance3.3μFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency- | Package | Radial, Can |
| Tolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105 °COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency- | Series | B41044 |
| Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105 °COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency- | Capacitance | 3.3µF |
| ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105 °COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency- | Tolerance | ±20% |
| Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency- | Voltage - Rated | 100V |
| Operating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency- | ESR (Equivalent Series Resistance) | - |
| PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency- | Lifetime @ Temp. | 2000 Hrs @ 105°C |
| ApplicationsGeneral PurposeRipple Current - Low Frequency- | Operating Temperature | - |
| Ripple Current - Low Frequency - | Polarization | Polar |
| | Applications | General Purpose |
| | Ripple Current - Low Frequency | - |
| Ripple Current - High Frequency64mA @ 100kHz | Ripple Current - High Frequency | 64mA @ 100kHz |
| Impedance 2.5 mOhms | Impedance | 2.5 mOhms |
| Lead Spacing 0.079" (2.00mm) | Lead Spacing | 0.079" (2.00mm) |
| Size / Dimension 0.197" Dia (5.00mm) | Size / Dimension | 0.197" Dia (5.00mm) |
| Height - Seated (Max) 0.492" (12.50mm) | Height - Seated (Max) | 0.492" (12.50mm) |
| Surface Mount Land Size - | Surface Mount Land Size | - |
| Mounting Type Through Hole | Mounting Type | Through Hole |
| Package / Case Radial, Can | Package / Case | Radial, Can |
| Report errors ⁶ | | Report errors? |

B41044A9335M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B41044A9335M Payment Methods





If you have any question about B41044A9335M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com