

B41252B3189M

B41252B3189M Information

Heisener.com	Part Number Manufacturer Category Description Package	B41252B3189M EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 18000UF 20% 10V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B41252B3189M Specifications

Manufacturer Part Number B41252B3189M Manufacturer EPCOS (TDK) Category Capacitors Category Capacitors Package Radial, Can - Snap-In Series B41252 Capacitance B400µF Tolerance ±20% Voltage - Rated 2000 µFs @ 105°C Operating Temperature - Operating Temperature 2000 µFs @ 105°C Oplariations General Purpose Applications General Purpose Ripple Current - Low Frequency 3.11 A @ 120Hz Nippedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.200" Dai (25.40mm) Kired Munt Land Size - Mounting Type -	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB41252Capacitance18000µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency3.11A @ 120HzRipple Current - High Frequency-Lead Spacing0.394" (10.00mm)Size / Dimension1.000" Dia (25.40mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseKadia, Can - Snap-In	Manufacturer Part Number	B41252B3189M
Aluminum Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB41252Capacitance18000µFTolerance±20%Voltage - Rated0VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency3.11A @ 120HzRipple Current - High Frequency-Lied Spacing0.394" (10.00mm)Size / Dimension1.260" (32.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Pockage / CaseKadial, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB41252Capacitance1800µFTolerance-20%Voltage - Rated0VESR (Equivalent Series Resistance)-Derating Temperature2000 Hrs @ 105°COperating Temperature-000 Hrs @ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-111 A @ 120 HzNippdance-Lead Spacing0394" (10.00mm)Size / Dimension1.000" Dia (25.40mm)Height - Seated (Max)-Surface Mount Land Size-Mouning Type-Package / CaseMail, Can - Snap-In	Category	Capacitors
SeriesB41252Capacitance1800µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Ingedance-Size / Dimension1.000° Dia (25.40mm)Size / Dimension1.260° (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance1800µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency3.11A @ 120HzInpedance-Size / Dimension0.304° (10.00mm)Size / Dimension1.000° Dia (25.40mm)Bight - Seated (Max)1.260° (32.00mm)Surface Mount Land Size-Hounting TypeThrough HolePackage / CaseKalia, Can - Snap-In	Package	Radial, Can - Snap-In
Total±20%Yoltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.11A @ 120HzNipedance-Lead Spacing0.394" (10.00mm)Size / Dinension1.000" Dia (25.40mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Series	B41252
Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.11A @ 120HzImpedance-Icad Spacing0.394" (10.00mm)Size / Dimension1.260" (32.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeRatial, Can - Snap-In	Capacitance	18000µF
FSR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.11A @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.260" Dia (25.40mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can - Snap-In	Tolerance	$\pm 20\%$
Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.11A @ 120HzRipple Current - High Frequency-Impedance-Iked Spacing0.394" (10.00mm)Size / Dimension1.000" Dia (25.40mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	10V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.11A @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.000" Dia (25.40mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.11A @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.000" Dia (25.40mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	2000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency3.11A @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.000" Dia (25.40mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 105^{\circ}\mathrm{C}$
Ripple Current - Low Frequency3.11A @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.000" Dia (25.40mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.000" Dia (25.40mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	3.11A @ 120Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.000" Dia (25.40mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.000" Dia (25.40mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	-
Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.000" Dia (25.40mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.260" (32.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report erro	Package / Case	Radial, Can - Snap-In
Report end		Report errors?

B41252B3189M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE UARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B41252B3189M Payment Methods



If you have any question about B41252B3189M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com