

B41505A6338M000

B41505A6338M000 Information



For Reference Only

Part Number	B41505A6338M000
Manufacturer	EPCOS (TDK)
Category	Capacitors Aluminum Electrolytic Capacitors
Description	CAP ALUM 3300UF 20% 50V SNAP
Package	Radial, Can - Snap-In
	For the pricing/inventory/lead time, please contact us
	Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B41505A6338M000 Specifications

Manufacturer Part NumberB41505A6338M000ManufacturerEPCOS (TDK)CategoryCapacitorsPackageAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB41505Capacitance3300µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)56 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 100HzOperating Temperature40°C ~ 105°CPolarizationFolaralApplicationsGeneral PurposeRiple Current - Low Frequency1.8A @ 100HzRippe Current - High Frequency-Impedance60 mOhms
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB41505Capacitance3300µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)56 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating TemperaturePolarPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency1.8A @ 100HzImpedance60 mOhms
Aluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB41505Capacitance3300µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)56 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature+40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency1.8A @ 100HzImpedance60 mOhms
PackageRadial, Can - Snap-InSeriesB41505Capacitance3300μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)56 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeApplicationsI.8A @ 100HzRipple Current - High Frequency.Impedance60 mOhms
SeriesB41505Capacitance3300µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)56 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency1.8A @ 100HzRipple Current - High Frequency-Impedance60 mOhms
Capacitance330µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)56 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.8A @ 100HzRipple Current - High Frequency-Impedance60 mOhms
Tolerance±20%Yoltage - Rated50VESR (Equivalent Series Resistance)56 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.8A @ 100HzRipple Current - High Frequency-Impedance60 mOhms
Voltage - Rated50VESR (Equivalent Series Resistance)56 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency1.8A @ 100HzHinpedance60 mOhms
For ControlSecond ControlESR (Equivalent Series Resistance)56 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.8A @ 100HzRipple Current - High Frequency-Impedance60 mOhms
Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.8A @ 100HzRipple Current - High Frequency-Impedance60 mOhms
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.8A @ 100HzRipple Current - High Frequency-Impedance60 mOhms
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.8A @ 100HzRipple Current - High Frequency-Impedance60 mOhms
ApplicationsGeneral PurposeRipple Current - Low Frequency1.8A @ 100HzRipple Current - High Frequency-Impedance60 mOhms
Ripple Current - Low Frequency1.8A @ 100HzRipple Current - High Frequency-Impedance60 mOhms
Ripple Current - High Frequency - Impedance 60 mOhms
Impedance 60 mOhms
1
Lead Spacing 0.394" (10.00mm)
Size / Dimension 0.984" Dia (25.00mm)
Height - Seated (Max) 1.457" (37.00mm)
Surface Mount Land Size -
Mounting Type Through Hole
Package / Case Radial, Can - Snap-In
Report errors?

B41505A6338M000 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B41505A6338M000 Payment Methods





If you have any question about B41505A6338M000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com