



B41505A9338M2 Information

Ma Ca Heisener.com

Part Number B41505A9338M2
Manufacturer EPCOS (TDK)

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 3300UF 20% 100V SNAP

Package Radial, Can - Snap-In - 3 Lead

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B41505A9338M2 Specifications

| Category Capacitors Package Radial, Can - Snap-In - 3 Lead Series B41505 Capacitance 3300µF Tolerance ±20% Voltage - Rated 100V ESR (Equivalent Series Resistance) 38 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3A @ 100Hz Ripple Current - High Frequency - Impedance 40 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole | | |
|---|------------------------------------|----------------------------------|
| Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In - 3 Lead Series B41505 Capacitance 3300µF Tolerance ±20% Voltage - Rated 100V ESR (Equivalent Series Resistance) 38 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3A @ 100Hz Ripple Current - High Frequency - Impedance 40 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Manufacturer Part Number | B41505A9338M2 |
| Package Radial, Can - Snap-In - 3 Lead Series B41505 Capacitance 3300μF Tolerance ±20% Voltage - Rated 100V ESR (Equivalent Series Resistance) 38 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3A @ 100Hz Ripple Current - High Frequency - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Manufacturer | EPCOS (TDK) |
| Package Radial, Can - Snap-In - 3 Lead Series B41505 Capacitance 3300µF Tolerance ±20% Voltage - Rated 100V ESR (Equivalent Series Resistance) 38 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3A @ 100Hz Ripple Current - High Frequency - Impedance 40 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Category | Capacitors |
| Series B41505 Capacitance 3300µF Tolerance ±20% Voltage - Rated 100V ESR (Equivalent Series Resistance) 38 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3A @ 100Hz Ripple Current - High Frequency - Impedance 40 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | | Aluminum Electrolytic Capacitors |
| Capacitance 3300μF Tolerance ±20% Voltage - Rated 100V ESR (Equivalent Series Resistance) 38 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3A @ 100Hz Ripple Current - High Frequency - Impedance 40 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Package | Radial, Can - Snap-In - 3 Lead |
| Tolerance ±20% Voltage - Rated 100V ESR (Equivalent Series Resistance) 38 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3A @ 100Hz Ripple Current - High Frequency - Impedance 40 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Series | B41505 |
| Voltage - Rated ESR (Equivalent Series Resistance) 38 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 40 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Capacitance | 3300μF |
| ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 40 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Tolerance | ±20% |
| Lifetime @ Temp. Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance 40 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 5000 Hrs @ 105°C -40°C ~ 100°C -40°C ~ | Voltage - Rated | 100V |
| Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance 40 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | ESR (Equivalent Series Resistance) | 38 mOhm @ 100Hz |
| Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3A @ 100Hz Ripple Current - High Frequency - Impedance 40 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Lifetime @ Temp. | 5000 Hrs @ 105°C |
| Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 40 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Operating Temperature | -40°C ~ 105°C |
| Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 40 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Polarization | Polar |
| Ripple Current - High Frequency Impedance 40 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Applications | General Purpose |
| Impedance 40 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Ripple Current - Low Frequency | 3A @ 100Hz |
| Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Ripple Current - High Frequency | - |
| Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Impedance | 40 mOhms |
| Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Lead Spacing | 0.394" (10.00mm) |
| Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Size / Dimension | 1.378" Dia (35.00mm) |
| Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Height - Seated (Max) | 2.047" (52.00mm) |
| Package / Case Radial, Can - Snap-In - 3 Lead | Surface Mount Land Size | - |
| | Mounting Type | Through Hole |
| Report errors? | Package / Case | Radial, Can - Snap-In - 3 Lead |
| | | Report errors? |

B41505A9338M2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B41505A9338M2 Payment Methods


































If you have any question about B41505A9338M2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com