



B41550A9339Q000 Information

Ma Ca Heisener.com

Part Number B41550A9339Q000
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 33000UF 100V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B41550A9339Q000 Specifications

Manufacturer Part NumberB41550A933Q000ManufacturerEPCOS (TDK)CategoryCapacitorsPackageRadial, Can - Screw TerminalsSeriesB41550Capacitance33000μFTolerance-10%, +30%Voltage - Rated100VESR (Equivalent Series Resistance)9 mOhm @ 100HzLifetime @ Temp.20000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency23A @ 100HzRipple Current - High Frequency-Impedance8 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension3.028" Dia (76.90mm)Height - Seated (Max)5.677" (144.20mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	· 1	
Category Capacitors Package Radial, Can - Screw Terminals Series B41550 Capacitance 33000µF Tolerance -10%, +30% Voltage - Rated 100V ESR (Equivalent Series Resistance) 9 mOhm @ 100Hz Lifetime @ Temp. 20000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 23A @ 100Hz Ripple Current - High Frequency - Impedance 8 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 5.677" (144.20mm) Surface Mount Land Size - Mounting Type Chassis Mount	Manufacturer Part Number	B41550A9339Q000
PackageAluminum Electrolytic CapacitorsPackageRadial, Can - Screw TerminalsSeriesB41550Capacitance33000μFTolerance-10%, +30%Voltage - Rated100VESR (Equivalent Series Resistance)9 mOhm @ 100HzLifetime @ Temp.20000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency23A @ 100HzRipple Current - High Frequency-Lead Spacing1.248" (31.70mm)Size / Dimension3.028" Dia (76.90mm)Height - Seated (Max)5.677" (144.20mm)Surface Mount Land Size-Mounting TypeChassis Mount	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Screw TerminalsSeriesB41550Capacitance33000µFTolerance-10%, +30%Voltage - Rated100VESR (Equivalent Series Resistance)9 mOhm @ 100HzLifetime @ Temp.20000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency23A @ 100HzRipple Current - High Frequency-Impedance8 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension3.028" Dia (76.90mm)Height - Seated (Max)5.677" (144.20mm)Surface Mount Land Size-Mounting TypeChassis Mount	Category	Capacitors
Series B41550 Capacitance 33000μF Tolerance -10%, +30% Voltage - Rated 100V ESR (Equivalent Series Resistance) 9 mOhm @ 100Hz Lifetime @ Temp. 20000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 23A @ 100Hz Ripple Current - High Frequency - Impedance 8 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 5.677" (144.20mm) Surface Mount Land Size - Mounting Type Chassis Mount		Aluminum Electrolytic Capacitors
Capacitance33000µFTolerance-10%, +30%Voltage - Rated100VESR (Equivalent Series Resistance)9 mOhm @ 100HzLifetime @ Temp.20000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency23A @ 100HzRipple Current - High Frequency-Impedance8 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension3.028" Dia (76.90mm)Height - Seated (Max)5.677" (144.20mm)Surface Mount Land Size-Mounting TypeChassis Mount	Package	Radial, Can - Screw Terminals
Tolerance -10%, +30% Voltage - Rated 100V ESR (Equivalent Series Resistance) 9 mOhm @ 100Hz Lifetime @ Temp. 20000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 23A @ 100Hz Ripple Current - High Frequency - Impedance 8 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 5.677" (144.20mm) Surface Mount Land Size - Mounting Type Chassis Mount	Series	B41550
Voltage - Rated100VESR (Equivalent Series Resistance)9 mOhm @ 100HzLifetime @ Temp.20000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency23A @ 100HzRipple Current - High Frequency-Impedance8 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension3.028" Dia (76.90mm)Height - Seated (Max)5.677" (144.20mm)Surface Mount Land Size-Mounting TypeChassis Mount	Capacitance	33000μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 20000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 23A @ 100Hz Ripple Current - High Frequency Impedance 8 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Polar 20000 Hrs @ 100Fz 20000 Hrs @ 105°C -55°C ~ 105°C -105°C -100°C -10	Tolerance	-10%, +30%
Lifetime @ Temp. 20000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 23A @ 100Hz Ripple Current - High Frequency Impedance 8 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount	Voltage - Rated	100V
Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 23A @ 100Hz Ripple Current - High Frequency - Impedance 8 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 5.677" (144.20mm) Surface Mount Land Size Mounting Type Chassis Mount	ESR (Equivalent Series Resistance)	9 mOhm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 23A @ 100Hz Ripple Current - High Frequency - Impedance 8 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 5.677" (144.20mm) Surface Mount Land Size - Mounting Type Chassis Mount	Lifetime @ Temp.	20000 Hrs @ 105°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 8 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 8 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 5.677" (144.20mm) Surface Mount Land Size Mounting Type Chassis Mount	Polarization	Polar
Ripple Current - High Frequency Impedance 8 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 5.677" (144.20mm) Surface Mount Land Size - Mounting Type Chassis Mount	Applications	General Purpose
Impedance8 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension3.028" Dia (76.90mm)Height - Seated (Max)5.677" (144.20mm)Surface Mount Land Size-Mounting TypeChassis Mount	Ripple Current - Low Frequency	23A @ 100Hz
Lead Spacing1.248" (31.70mm)Size / Dimension3.028" Dia (76.90mm)Height - Seated (Max)5.677" (144.20mm)Surface Mount Land Size-Mounting TypeChassis Mount	Ripple Current - High Frequency	-
Size / Dimension3.028" Dia (76.90mm)Height - Seated (Max)5.677" (144.20mm)Surface Mount Land Size-Mounting TypeChassis Mount	Impedance	8 mOhms
Height - Seated (Max) Surface Mount Land Size Mounting Type 5.677" (144.20mm) - Chassis Mount	Lead Spacing	1.248" (31.70mm)
Surface Mount Land Size - Mounting Type Chassis Mount	Size / Dimension	3.028" Dia (76.90mm)
Mounting Type Chassis Mount	Height - Seated (Max)	5.677" (144.20mm)
	Surface Mount Land Size	-
Package / Case Radial, Can - Screw Terminals	Mounting Type	Chassis Mount
	Package / Case	Radial, Can - Screw Terminals
Report errors?		Report errors?

B41550A9339Q000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B41550A9339Q000 Payment Methods





















B41550A9339Q000 Shipping Methods













If you have any question about B41550A9339Q000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com