



# **B41550E8339Q000 Information**

Heisener.com

Part Number B41550E8339Q000
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

**Description** CAP ALUM 33000UF 63V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## B41550E8339Q000 Specifications

| Manufacturer Part NumberB41550E833Q000ManufacturerEPCOS (TDK)CategoryCapacitorsPackageRadial, Can - Screw TerminalsSeriesB41550Capacitance33000µFTolerance-10%, +30%Voltage - Rated63VESR (Equivalent Series Resistance)8 mOhm @ 100HzLifetime @ Temp.20000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency21A @ 100HzRipple Current - High Frequency- |
|--|
| Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series B41550 Capacitance 33000µF Tolerance -10%, +30% Voltage - Rated 63V ESR (Equivalent Series Resistance) Lifetime @ Temp. 20000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications Ripple Current - Low Frequency Ripple Current - High Frequency   |
| PackageAluminum Electrolytic CapacitorsPackageRadial, Can - Screw TerminalsSeriesB41550Capacitance33000μFTolerance-10%, +30%Voltage - Rated63VESR (Equivalent Series Resistance)8 mOhm @ 100HzLifetime @ Temp.20000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency21A @ 100HzRipple Current - High Frequency-   |
| Package Radial, Can - Screw Terminals  Series B41550  Capacitance 33000µF  Tolerance -10%, +30%  Voltage - Rated 63V  ESR (Equivalent Series Resistance) Lifetime @ Temp. 20000 Hrs @ 100Hz  Lifetime @ Temp. 20000 Hrs @ 105°C  Operating Temperature -55°C ~ 105°C  Polarization Applications General Purpose  Ripple Current - Low Frequency Ripple Current - High Frequency  |
| SeriesB41550Capacitance33000μFTolerance-10%, +30%Voltage - Rated63VESR (Equivalent Series Resistance)8 mOhm @ 100HzLifetime @ Temp.20000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency21A @ 100HzRipple Current - High Frequency-  |
| Capacitance33000μFTolerance-10%, +30%Voltage - Rated63VESR (Equivalent Series Resistance)8 mOhm @ 100HzLifetime @ Temp.20000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency21A @ 100HzRipple Current - High Frequency-  |
| Tolerance -10%, +30%  Voltage - Rated 63V  ESR (Equivalent Series Resistance) 8 mOhm @ 100Hz  Lifetime @ Temp. 20000 Hrs @ 105°C  Operating Temperature -55°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 21A @ 100Hz  Ripple Current - High Frequency -   |
| Voltage - Rated63VESR (Equivalent Series Resistance)8 mOhm @ 100HzLifetime @ Temp.20000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency21A @ 100HzRipple Current - High Frequency-   |
| ESR (Equivalent Series Resistance)  Lifetime @ Temp.  20000 Hrs @ 105°C  Operating Temperature  -55°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  -   |
| Lifetime @ Temp.20000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency21A @ 100HzRipple Current - High Frequency-   |
| Operating Temperature  -55°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  -          -   |
| Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 21A @ 100Hz  Ripple Current - High Frequency -  |
| Applications General Purpose Ripple Current - Low Frequency 21A @ 100Hz Ripple Current - High Frequency -  |
| Ripple Current - Low Frequency  21A @ 100Hz  Ripple Current - High Frequency  -  |
| Ripple Current - High Frequency -  |
|  |
|  |
| Impedance 8 mOhms  |
| Lead Spacing 1.248" (31.70mm)  |
| Size / Dimension 3.028" Dia (76.90mm)  |
| Height - Seated (Max) 4.201" (106.70mm)  |
| Surface Mount Land Size -  |
| Mounting Type Chassis Mount  |
| Package / Case Radial, Can - Screw Terminals   |
| Report errors?   |

### **B41550E8339Q000 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### B41550E8339Q000 Payment Methods





















## B41550E8339Q000 Shipping Methods













If you have any question about B41550E8339Q000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com