



B41554E7479Q000 Information

Heisener.com

Part Number B41554E7479Q000 Manufacturer EPCOS (TDK) Category Capacitors

Aluminum Electrolytic Capacitors

CAP ALUM 47000UF 40V SCREW **Description**

Package Radial, Can - Screw Terminals For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B41554E7479Q000 Specifications

Manufacturer Part Number B41554E7479Q000 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series B41554 Capacitance 47000µF Tolerance -10%, +30% Voltage - Rated 40V ESR (Equivalent Series Resistance) 10 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 125°C Operating Temperature -55°C ~ 125°C Operating Temperature 6eneral Purpose Ripple Current - Low Frequency 13A @ 100Hz Ripple Current - High Frequency - Impedance 9 mOhms Lead Spacing 1.122" (28.50mm) Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series B41554 Capacitance 47000µF Tolerance -10%, +30% Voltage - Rated 40V ESR (Equivalent Series Resistance) 10 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 125°C Operating Temperature -55°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 13A @ 100Hz Ripple Current - High Frequency Impedance 9 mOhms Lead Spacing 1.122" (28.50mm) Size / Dimension Leight - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	B41554E7479Q000
Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series B41554 Capacitance 47000µF Tolerance -10%, +30% Voltage - Rated 40V ESR (Equivalent Series Resistance) 10 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 125°C Operating Temperature -55°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 13A @ 100Hz Ripple Current - High Frequency - Impedance 9 mOhms Lead Spacing 1.122" (28.50mm) Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Screw TerminalsSeriesB41554Capacitance47000μFTolerance-10%, +30%Voltage - Rated40VESR (Equivalent Series Resistance)10 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 125°COperating Temperature-55°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency13A @ 100HzRipple Current - High Frequency-Lead Spacing1.122" (28.50mm)Size / Dimension2.532" Dia (64.30mm)Height - Seated (Max)4.201" (106.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Category	Capacitors
Series B41554 Capacitance 47000µF Tolerance -10%, +30% Voltage - Rated 40V ESR (Equivalent Series Resistance) 10 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 125°C Operating Temperature -55°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 13A @ 100Hz Ripple Current - High Frequency - Impedance 9 mOhms Lead Spacing 1.122" (28.50mm) Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance 47000μF Tolerance -10%, +30% Voltage - Rated 40V ESR (Equivalent Series Resistance) 10 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 125°C Operating Temperature -55°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 13A @ 100Hz Ripple Current - High Frequency - Impedance 9 mOhms Lead Spacing 1.122" (28.50mm) Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance -10%, +30% Voltage - Rated 40V ESR (Equivalent Series Resistance) 10 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 125°C Operating Temperature -55°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 13A @ 100Hz Ripple Current - High Frequency - Impedance 9 mOhms Lead Spacing 1.122" (28.50mm) Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Series	B41554
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 125°C Operating Temperature -55°C ~ 125°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 9 mOhms Lead Spacing 1.122" (28.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Round Hood Hrs @ 100Hz 10 mOhm @ 100Hz 1125°C 6 eneral Purpose General Purpose 13A @ 100Hz 123 (28.50mm) 1.122" (28.50mm) 2.532" Dia (64.30mm) 4.201" (106.70mm)	Capacitance	47000μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 125°C Operating Temperature -55°C ~ 125°C Polarization Applications General Purpose Ripple Current - Low Frequency 13A @ 100Hz Ripple Current - High Frequency Impedance 9 mOhms Lead Spacing 1.122" (28.50mm) Size / Dimension 4.201" (106.70mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Tolerance	-10%, +30%
Lifetime @ Temp. 5000 Hrs @ 125°C Operating Temperature -55°C ~ 125°C Polarization Applications General Purpose Ripple Current - Low Frequency 13A @ 100Hz Ripple Current - High Frequency - Impedance 9 mOhms Lead Spacing 1.122" (28.50mm) Size / Dimension 4.201" (106.70mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Voltage - Rated	40V
Operating Temperature -55°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance 9 mOhms Lead Spacing 1.122" (28.50mm) Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	10 mOhm @ 100Hz
Polarization Applications General Purpose Ripple Current - Low Frequency 13A @ 100Hz Ripple Current - High Frequency Impedance 9 mOhms Lead Spacing 1.122" (28.50mm) Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	5000 Hrs @ 125°C
Applications General Purpose Ripple Current - Low Frequency 13A @ 100Hz Ripple Current - High Frequency - Impedance 9 mOhms Lead Spacing 1.122" (28.50mm) Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Operating Temperature	-55°C ~ 125°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 9 mOhms Lead Spacing 1.122" (28.50mm) Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency Impedance 9 mOhms Lead Spacing 1.122" (28.50mm) Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance9 mOhmsLead Spacing1.122" (28.50mm)Size / Dimension2.532" Dia (64.30mm)Height - Seated (Max)4.201" (106.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - Low Frequency	13A @ 100Hz
Lead Spacing1.122" (28.50mm)Size / Dimension2.532" Dia (64.30mm)Height - Seated (Max)4.201" (106.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - High Frequency	-
Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Impedance	9 mOhms
Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lead Spacing	1.122" (28.50mm)
Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	2.532" Dia (64.30mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	4.201" (106.70mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

B41554E7479Q000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B41554E7479Q000 Payment Methods



















B41554E7479Q000 Shipping Methods













If you have any question about B41554E7479Q000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com