



B41560A7339M000 Information



For Reference Only

Part Number B41560A7339M000
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 33000UF 20% 40V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B41560A7339M000 Specifications

Manufacturer Part Number B41560A7339M000 Manufacturer EPCOS (TDK) Category Capacitors Package Radial, Can - Screw Terminals Series B41560 Capacitance 33000μF Tolerance ±20% Voltage - Rated 40V ESR (Equivalent Series Resistance) 12 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 11A @ 100Hz Ripple Current - High Frequency - Impedance 13 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.032" Dia (51.60mm) Height - Seated (Max) 3.217" (81.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		
Category Capacitors Package Radial, Can - Screw Terminals Series B41560 Capacitance 33000µF Tolerance ±20% Voltage - Rated 40V ESR (Equivalent Series Resistance) 12 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 11A @ 100Hz Ripple Current - High Frequency - Impedance 13 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.032" Dia (51.60mm) Height - Seated (Max) 3.217" (81.70mm) Surface Mount Land Size - Mounting Type Chassis Mount	Manufacturer Part Number	B41560A7339M000
PackageAluminum Electrolytic CapacitorsPackageRadial, Can - Screw TerminalsSeriesB41560Capacitance33000μFTolerance±20%Voltage - Rated40VESR (Equivalent Series Resistance)12 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency11A @ 100HzRipple Current - High Frequency-Impedance13 mOhmsLead Spacing0.874" (22.20mm)Size / Dimension2.032" Dia (51.60mm)Height - Seated (Max)3.217" (81.70mm)Surface Mount Land Size-Mounting TypeChassis Mount	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Screw TerminalsSeriesB41560Capacitance33000μFTolerance±20%Voltage - Rated40VESR (Equivalent Series Resistance)12 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency11A @ 100HzRipple Current - High Frequency-Impedance13 mOhmsLead Spacing0.874" (22.20mm)Size / Dimension2.032" Dia (51.60mm)Height - Seated (Max)3.217" (81.70mm)Surface Mount Land Size-Mounting TypeChassis Mount	Category	Capacitors
Series B41560 Capacitance 33000µF Tolerance ±20% Voltage - Rated 40V ESR (Equivalent Series Resistance) 12 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 11A @ 100Hz Ripple Current - High Frequency - Impedance 13 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.032" Dia (51.60mm) Height - Seated (Max) 3.217" (81.70mm) Surface Mount Land Size - Mounting Type Chassis Mount		Aluminum Electrolytic Capacitors
Capacitance33000μFTolerance±20%Voltage - Rated40VESR (Equivalent Series Resistance)12 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency11A @ 100HzRipple Current - High Frequency-Impedance13 mOhmsLead Spacing0.874" (22.20mm)Size / Dimension2.032" Dia (51.60mm)Height - Seated (Max)3.217" (81.70mm)Surface Mount Land Size-Mounting TypeChassis Mount	Package	Radial, Can - Screw Terminals
Tolerance ±20% Voltage - Rated 40V ESR (Equivalent Series Resistance) 12 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 11A @ 100Hz Ripple Current - High Frequency - Impedance 13 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.032" Dia (51.60mm) Height - Seated (Max) 3.217" (81.70mm) Surface Mount Land Size - Mounting Type Chassis Mount	Series	B41560
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 11A @ 100Hz Ripple Current - High Frequency Impedance 13 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 4.004 2.032" Dia (51.60mm) Height - Seated (Max) Surface Mount Land Size - Mounting Type 40V 200Hz 3000 Hrs @ 100Hz 40°C ~ 105°C 600 C ~ 105	Capacitance	33000μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature -40°C ~ 105°C Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type 12 mOhm @ 100Hz 3000 Hrs @ 105°C -40°C ~ 105°C Polar -40°C ~ 105°C -6neral Purpose 11A @ 100Hz -11A @ 100Hz -13 mOhms -2.032" Dia (51.60mm) 3.217" (81.70mm) Chassis Mount	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 11A @ 100Hz Ripple Current - High Frequency Impedance 13 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 4.032" Dia (51.60mm) Height - Seated (Max) Surface Mount Land Size Mounting Type 3000 Hrs @ 105°C -40°C ~ 105°C Folionic Oeneral Purpose 11A @ 100Hz 13 mOhms - Chassis Mount	Voltage - Rated	40V
Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance 13 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.032" Dia (51.60mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount	ESR (Equivalent Series Resistance)	12 mOhm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 11A @ 100Hz Ripple Current - High Frequency - Impedance 13 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.032" Dia (51.60mm) Height - Seated (Max) 3.217" (81.70mm) Surface Mount Land Size - Mounting Type Chassis Mount	Lifetime @ Temp.	3000 Hrs @ 105°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing O.874" (22.20mm) Size / Dimension Leight - Seated (Max) Surface Mount Land Size Mounting Type General Purpose 11A @ 100Hz - 0.874" (22.20mm) 2.032" Dia (51.60mm) 3.217" (81.70mm) Chassis Mount	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Inpedance Is mOhms Lead Spacing Is with a spaci	Polarization	Polar
Ripple Current - High Frequency Impedance 13 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.032" Dia (51.60mm) Height - Seated (Max) 3.217" (81.70mm) Surface Mount Land Size - Mounting Type Chassis Mount	Applications	General Purpose
Impedance13 mOhmsLead Spacing0.874" (22.20mm)Size / Dimension2.032" Dia (51.60mm)Height - Seated (Max)3.217" (81.70mm)Surface Mount Land Size-Mounting TypeChassis Mount	Ripple Current - Low Frequency	11A @ 100Hz
Lead Spacing 0.874" (22.20mm) Size / Dimension 2.032" Dia (51.60mm) Height - Seated (Max) 3.217" (81.70mm) Surface Mount Land Size - Mounting Type Chassis Mount	Ripple Current - High Frequency	-
Size / Dimension2.032" Dia (51.60mm)Height - Seated (Max)3.217" (81.70mm)Surface Mount Land Size-Mounting TypeChassis Mount	Impedance	13 mOhms
Height - Seated (Max) Surface Mount Land Size Mounting Type 3.217" (81.70mm) - Chassis Mount	Lead Spacing	0.874" (22.20mm)
Surface Mount Land Size - Mounting Type Chassis Mount	Size / Dimension	2.032" Dia (51.60mm)
Mounting Type Chassis Mount	Height - Seated (Max)	3.217" (81.70mm)
2 71	Surface Mount Land Size	-
Package / Case Radial, Can - Screw Terminals	Mounting Type	Chassis Mount
	Package / Case	Radial, Can - Screw Terminals
Report errors?		Report errors?

B41560A7339M000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B41560A7339M000 Payment Methods



















B41560A7339M000 Shipping Methods













If you have any question about B41560A7339M000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com