

B41570E8338Q000 Information



For Reference Only

Part Number B41570E8338Q000
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

DescriptionCAP ALUM 3300UF 63V SCREW**Package**Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B41570E8338Q000 Specifications

Manufacturer Part Number B41570E8338Q000 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series B41570 Capacitance 3300µF Tolerance -10%, +30% Voltage - Rated 63V ESR (Equivalent Series Resistance) 39 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 105°C Operating Temperature - Operating Temperature - Applications General Purpose Ripple Current - Low Frequency 6.8A @ 100Hz Ripple Current - High Frequency - Impedance 24 mOhms Lead Spacing 0.500" (12.70mm) Size / Dimension 1.406" Dia (35.70mm) Height - Seated (Max) 3.217" (81.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series B41570 Capacitance 3300µF Tolerance -10%, +30% Voltage - Rated 63V ESR (Equivalent Series Resistance) 39 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 0.500" (12.70mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	B41570E8338Q000
PackageRadial, Can - Screw TerminalsSeriesB41570Capacitance3300μFTolerance-10%, +30%Voltage - Rated63VESR (Equivalent Series Resistance)39 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency6.8A @ 100HzRipple Current - High Frequency-Impedance24 mOhmsLead Spacing0.500" (12.70mm)Size / Dimension1.406" Dia (35.70mm)Height - Seated (Max)3.217" (81.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Screw TerminalsSeriesB41570Capacitance3300µFTolerance-10%, +30%Voltage - Rated63VESR (Equivalent Series Resistance)39 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency6.8A @ 100HzRipple Current - High Frequency-Impedance24 mOhmsLead Spacing0.500" (12.70mm)Size / Dimension1.406" Dia (35.70mm)Height - Seated (Max)3.217" (81.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Category	Capacitors
SeriesB41570Capacitance3300μFTolerance-10%, +30%Voltage - Rated63VESR (Equivalent Series Resistance)39 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency6.8A @ 100HzRipple Current - High Frequency-Impedance24 mOhmsLead Spacing0.500" (12.70mm)Size / Dimension1.406" Dia (35.70mm)Height - Seated (Max)3.217" (81.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance 3300µF Tolerance -10%, +30% Voltage - Rated 63V ESR (Equivalent Series Resistance) 39 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 6.8A @ 100Hz Ripple Current - High Frequency - Impedance 24 mOhms Lead Spacing 0.500" (12.70mm) Size / Dimension 1.406" Dia (35.70mm) Height - Seated (Max) 3.217" (81.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance -10%, +30% Voltage - Rated 63V ESR (Equivalent Series Resistance) 39 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 6.8A @ 100Hz Ripple Current - High Frequency - Impedance 24 mOhms Lead Spacing 0.500" (12.70mm) Size / Dimension 1.406" Dia (35.70mm) Size / Dimension 1.406" Dia (35.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Series	B41570
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 10000 Hrs @ 105°C Operating Temperature Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Rionom Hooms 10000 Hrs @ 100FC General Purpose 6.8A @ 100Hz 6.8A @ 100Hz 7. 8.4 mOhms 1.406" Dia (35.70mm) 1.406" Dia (35.70mm) Chassis Mount Radial, Can - Screw Terminals	Capacitance	3300μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Polar 10000 Hrs @ 105°C Chassis Mount General Purpose 6.8A @ 100Hz - 24 mOhms 0.500" (12.70mm) 1.406" Dia (35.70mm) 3.217" (81.70mm) Chassis Mount Package / Case Radial, Can - Screw Terminals	Tolerance	-10%, +30%
Lifetime @ Temp. Operating Temperature - Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 10000 Hrs @ 105°C Ceneral Purpose 6.8A @ 100Hz 6.Ra @ 100Hz 6.Ra @ 100Hz	Voltage - Rated	63V
Operating Temperature Polarization Polar Applications General Purpose Ripple Current - Low Frequency 6.8A @ 100Hz Ripple Current - High Frequency - Impedance 24 mOhms Lead Spacing 0.500" (12.70mm) Size / Dimension 1.406" Dia (35.70mm) Height - Seated (Max) 3.217" (81.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	39 mOhm @ 100Hz
Polarization Applications General Purpose Ripple Current - Low Frequency 6.8A @ 100Hz Ripple Current - High Frequency Impedance 24 mOhms Lead Spacing 0.500" (12.70mm) Size / Dimension 1.406" Dia (35.70mm) Height - Seated (Max) 3.217" (81.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	10000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency 6.8A @ 100Hz Ripple Current - High Frequency - Impedance 24 mOhms Lead Spacing 0.500" (12.70mm) Size / Dimension 1.406" Dia (35.70mm) Height - Seated (Max) 3.217" (81.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Operating Temperature	-
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 24 mOhms Lead Spacing 0.500" (12.70mm) Size / Dimension 1.406" Dia (35.70mm) Height - Seated (Max) 3.217" (81.70mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency Impedance 24 mOhms Lead Spacing 0.500" (12.70mm) Size / Dimension 1.406" Dia (35.70mm) Height - Seated (Max) 3.217" (81.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance24 mOhmsLead Spacing0.500" (12.70mm)Size / Dimension1.406" Dia (35.70mm)Height - Seated (Max)3.217" (81.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - Low Frequency	6.8A @ 100Hz
Lead Spacing0.500" (12.70mm)Size / Dimension1.406" Dia (35.70mm)Height - Seated (Max)3.217" (81.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - High Frequency	-
Size / Dimension 1.406" Dia (35.70mm) Height - Seated (Max) 3.217" (81.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Impedance	24 mOhms
Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lead Spacing	0.500" (12.70mm)
Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	1.406" Dia (35.70mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	3.217" (81.70mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
-	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

B41570E8338Q000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B41570E8338Q000 Payment Methods





















B41570E8338Q000 Shipping Methods













If you have any question about B41570E8338Q000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com