



B41605A7688M9 Information

Heisener.com

Part Number B41605A7688M9
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 6800UF 20% 40V RADIAL

Package Radial, Can

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B41605A7688M9 Specifications

Manufacturer Part Number B41605A7688M9 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series B41605 Capacitance 6800µF Tolerance ±20% Voltage - Rated 40V ESR (Equivalent Series Resistance) 16 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 125°C Operating Temperature -55°C ~ 125°C Polarization Polar Applications Automotive Ripple Current - Low Frequency - Ripple Current - High Frequency 9A @ 10kHz Impedance - Lead Spacing 0.331" (8.40mm) Size / Dimension 0.984" Dia (25.00mm) Height - Scated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Renart errors?	•	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series B41605 Capacitance 6800µF Tolerance ±20% Voltage - Rated 40V ESR (Equivalent Series Resistance) 16 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 125°C Operating Temperature -55°C ~ 125°C Polarization Polar Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency Pagance Lead Spacing 0.331" (8.40mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Manufacturer Part Number	B41605A7688M9
Package Radial, Can Series B41605 Capacitance 6800μF Tolerance ±20% Voltage - Rated 40V ESR (Equivalent Series Resistance) 16 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 125°C Operating Temperature -55°C ~ 125°C Polarization Polar Applications Automotive Ripple Current - Low Frequency - Ripple Current - High Frequency 9A @ 10kHz Impedance - Lead Spacing 0.331" (8.40mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer	EPCOS (TDK)
Package Radial, Can Series B41605 Capacitance 6800µF Tolerance ±20% Voltage - Rated 40V ESR (Equivalent Series Resistance) 16 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 125°C Operating Temperature -55°C ~ 125°C Polarization Polar Applications Automotive Ripple Current - Low Frequency - Ripple Current - High Frequency 9A @ 10kHz Impedance - Lead Spacing 0.331" (8.40mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series B41605 Capacitance 6800μF Tolerance ±20% Voltage - Rated 40V ESR (Equivalent Series Resistance) 16 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 125°C Operating Temperature -55°C ~ 125°C Polarization Polar Applications Automotive Ripple Current - Low Frequency - Ripple Current - High Frequency 9A @ 10kHz Impedance - Lead Spacing 0.331" (8.40mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 6800μF Tolerance ±20% Voltage - Rated 40V ESR (Equivalent Series Resistance) 16 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 125°C Operating Temperature -55°C ~ 125°C Polarization Polar Applications Automotive Ripple Current - Low Frequency - Ripple Current - High Frequency 9A @ 10kHz Impedance - Lead Spacing 0.331" (8.40mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 40V ESR (Equivalent Series Resistance) 16 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 125°C Operating Temperature -55°C ~ 125°C Polarization Polar Applications Automotive Ripple Current - Low Frequency - Ripple Current - High Frequency 9A @ 10kHz Impedance - Lead Spacing 0.331" (8.40mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	B41605
Voltage - Rated40VESR (Equivalent Series Resistance)16 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 125°COperating Temperature-55°C ~ 125°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Ripple Current - High Frequency9A @ 10kHzImpedance-Lead Spacing0.331" (8.40mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Capacitance	6800μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 125°C Operating Temperature -55°C ~ 125°C Polarization Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency Page 10kHz Impedance Lead Spacing 331" (8.40mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Riono Hrs @ 100Hz 16 mOhm @ 10th 16 mohm @ 100Hz 16 mohm @ 125°C 16 mohm @ 100Hz 16 mohm @ 100Hz 16 mohm @ 100Hz 16 mohm @ 125°C 16 mohm @ 100Hz 1	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -55°C ~ 125°C Polarization Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency 9A @ 10kHz Impedance Lead Spacing 0.331" (8.40mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 5000 Hrs @ 125°C -0125°C -025°C ~ 125°C -0125°C -026	Voltage - Rated	40V
Operating Temperature Polarization Polar Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency Polar Polar Polar Polar Automotive Polar Pola	ESR (Equivalent Series Resistance)	16 mOhm @ 100Hz
Polarization Polar Applications Automotive Ripple Current - Low Frequency - Ripple Current - High Frequency 9A @ 10kHz Impedance - Lead Spacing 0.331" (8.40mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	5000 Hrs @ 125°C
Applications Ripple Current - Low Frequency - Ripple Current - High Frequency 9A @ 10kHz Impedance - Lead Spacing 0.331" (8.40mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-55°C ~ 125°C
Ripple Current - Low Frequency - Ripple Current - High Frequency 9A @ 10kHz Impedance - Lead Spacing 0.331" (8.40mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing 0.331" (8.40mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Applications	Automotive
Impedance-Lead Spacing0.331" (8.40mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	-
Lead Spacing0.331" (8.40mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	9A @ 10kHz
Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.331" (8.40mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.984" Dia (25.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	2.047" (52.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
Report cross.		Report errors?

B41605A7688M9 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B41605A7688M9 Payment Methods



















B41605A7688M9 Shipping Methods













If you have any question about B41605A7688M9, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com