

## B41607A4338M002

#### B41607A4338M002 Information

Heisener.com	 B41607A4338M002 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 3300UF 20% 25V SNAP Radial, Can - Snap-In - 3 Lead For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### B41607A4338M002 Specifications

Manufacturer Part Number       B41607A4338M002         Manufacturer       EPCOS (TDK)         Category       Capacitors         Aluminum Electrolytic Capacitors       Aluminum Electrolytic Capacitors         Package       Radial, Can - Snap-In - 3 Lead         Series       B41607         Capacitance       3300µF         Tolerance       420%         Voltage - Rated       25V         ESR (Equivalent Series Resistance)       80 mOhm @ 100Hz         Lifetime @ Temp.       10000 Hrs @ 125°C         Operating Temperature       -         Polarization       Automotive         Ripple Current - Low Frequency       Automotive         Impedance       -         Lead Spacing       0.394" (10.00mm)         Size / Dimension       0.394" (10.00mm)         Size / Dimension       -         Mounting Type       -         Mounting Type       -	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB41607Capacitance3300µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)80 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 125°COperating Temperature-PolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Ripple Current - High Frequency0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKalia, Can - Snap-In - 3 Lead	Manufacturer Part Number	B41607A4338M002
IdentifyAluminum Electrolytic CapacitonsPackageRadial, Can - Snap-In - 3 LeadSeriesB41607Capacitance3300µFTolerance±20%Voltage - RatedD5VESR (Equivalent Series Resistance)80 mOhm @ 100HzLifetime @ Temp.00000 Hrs @ 125°COperating Temperature00000 Hrs @ 125°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Kipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Hight - Seated (Max)-Surface Mount Land Size-Hounting TypeFinough HolePackage / CaseKalia, Can - Snap-In - 3 Lead	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-In - 3 LeadSeriesB41607Capacitance3300µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)80 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 125°COperating Temperature-PolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Ripple Current - High Frequency0.394" (10.00mm)Size / Dimension0.994" Dia (25.00mm)Size / Dimension1.654" (42.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Pokage / CaseRadial, Can - Snap-In - 3 Lead	Category	Capacitors
SeriesB41607Capacitance3300µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)80 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 125°COperating Temperature-PolarizationPolarApplicationsAutomotiveRipple Current - High Frequency-Indedagacing0.394° (10.00mm)Size / Dimension0.944° Dia (25.00mm)Bigt - Seated (Max)0.944° Dia (25.00mm)Surface Mount Land Size-Mounting Type-Package / CaseMatial, Can - Snap-In - 3 Lead		Aluminum Electrolytic Capacitors
Capacitance330µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)80 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 125°COperating Temperature-PolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Impedance-Stack Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Bight - Seated (Max).654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In - 3 Lead	Package	Radial, Can - Snap-In - 3 Lead
Totance±20%Voltage - Rated25VESR (Equivalent Series Resistance)80 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 125°COperating Temperature-PolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Ripple Current - High Frequency7.6A @ 10kHzImpedance-Lead Spacing0.994" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In - 3 Lead	Series	B41607
Voltage - Rated25VESR (Equivalent Series Resistance)80 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 125°COperating Temperature-PolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Inpedance-Icad Spacing0.394" (10.00mm)Size / Dimension1.654" (42.00mm)Height - Seated (Max).Surface Mount Land Size-Mounting TypeFrequencyPackage / CaseRatial, Can - Snap-In - 3 Lead	Capacitance	3300µF
FSR (Equivalent Series Resistance)80 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 125°COperating Temperature-PolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Ripple Current - High Frequency7.6A @ 10kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.654" (42.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In - 3 Lead	Tolerance	$\pm 20\%$
Lifetime @ Temp.10000 Hrs @ 125°COperating Temperature-PolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Ripple Current - High Frequency7.6A @ 10kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Voltage - Rated	25V
Operating Temperature-PolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Ripple Current - High Frequency7.6A @ 10kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	ESR (Equivalent Series Resistance)	80 mOhm @ 100Hz
PolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Ripple Current - High Frequency7.6A @ 10kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Lifetime @ Temp.	10000 Hrs @ 125°C
ApplicationsAutomotiveApplicationsAutomotiveRipple Current - Low Frequency-Ripple Current - High Frequency7.6A @ 10kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Operating Temperature	-
InRipple Current - Low Frequency-Ripple Current - High Frequency7.6A @ 10kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Polarization	Polar
Ripple Current - High Frequency7.6A @ 10kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Applications	Automotive
Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Ripple Current - Low Frequency	-
Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Ripple Current - High Frequency	7.6A @ 10kHz
Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Impedance	-
Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Size / Dimension	0.984" Dia (25.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Height - Seated (Max)	1.654" (42.00mm)
Package / Case Radial, Can - Snap-In - 3 Lead	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report error	Package / Case	Radial, Can - Snap-In - 3 Lead
		Report errors?

#### B41607A4338M002 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### B41607A4338M002 Payment Methods



# B41607A4338M002 Shipping Methods



If you have any question about B41607A4338M002, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com