

B41607A7228M9

B41607A7228M9 Information

Contract nerves contraction	 B41607A7228M9 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 2200UF 20% 40V RADIAL Radial, Can For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B41607A7228M9 Specifications

Package / Case Radial, Can	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41607Capacitance2200µFTolerance±20%Voltage - Rated40VESR (Equivalent Series Resistance)80 mOhm @ 100HzDiperating Temperature10000 Hrs @ 125°COperating Temperature-55°C ~ 125°CPolarizationAutomotiveRipple Current - Low Frequency-Ripple Current - High Frequency.7.7A @ 10kHzImpedance.Lead Spacing0.331" (8.40mm)Size / Dimension1.654" (42.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can	Manufacturer Part Number	B41607A7228M9
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41607Capacitance2200μFTolerance±20%Voltage - Rated40VESR (Equivalent Series Resistance)80 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 125°COperating Temperature>55°C ~ 125°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Ripple Current - High Frequency0.331" (8.40mm)Size / Dimension0.984" Dia (25.00mm)Size / Dimension1.654" (42.00mm)Height - Seated (Max)-Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer	EPCOS (TDK)
PackageRadial, CanSeriesB41607Capacitance2200μFTolerance-20%Voltage - Rated600 Mohm @ 100HzESR (Equivalent Series Resistance)80 mOhm @ 100HzLifetime @ Temp.00000 Hrs @ 125°COperating Temperature-55°C ~ 125°CPolarizationAutomotiveRipple Current - Low Frequency-Ripple Current - High Frequency0.331" (8.40mm)Siz / Dimension0.984" Dia (25.00mm)Siz / Dimension0.984" Dia (25.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting Type-Package / CaseMatial, Can	Category	Capacitors
SeriesB41607Capacitance2200µFTolerance±20%Voltage - Rated40VESR (Equivalent Series Resistance)80 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 125°COperating Temperature-55°C ~ 125°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Impedance-Liad Spacing0.331" (8.40mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can		Aluminum Electrolytic Capacitors
Capacitance2200µFTolerance±20%Voltage - Rated40VESR (Equivalent Series Resistance)80 mOhm @ 100HzESR (Equivalent Series Resistance)80 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 125°COperating Temperature>55°C ~ 125°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Impedance-Lead Spacing0.331" (8.40mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated40VESR (Equivalent Series Resistance)80 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 125°COperating Temperature-55°C ~ 125°CPolarizationPolarApplicationsAutomotiveRipple Current - High Frequency-Impedance-Lead Spacing0.331" (8.40mm)Size / Dimension1.654" (42.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Pokage / CaseRatial, Can	Series	B41607
Voltage - Rated40VESR (Equivalent Series Resistance)80 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 125°COperating Temperature-55°C ~ 125°CPolarizationPolarApplicationsAutomotiveRipple Current - High Frequency-Impedance-Lead Spacing0.331" (8.40mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeFrequencyPackage / CaseRatial, Can	Capacitance	2200µF
ESR (Equivalent Series Resistance) 80 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 125°C Operating Temperature -55°C ~ 125°C Polar Polar Applications Automotive Ripple Current - Low Frequency - Impedance - Lead Spacing 0.331" (8.40mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Tolerance	±20%
Lifetime @ Temp.10000 Hrs @ 125°CDoperating Temperature-55°C ~ 125°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Ripple Current - High Frequency7.7 A @ 10kHzImpedance-Lead Spacing0.331" (8.40mm)Size / Dimension1.654" (42.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeRadia, Can	Voltage - Rated	40V
Operating Temperature-55°C ~ 125°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Ripple Current - High Frequency7.7A @ 10kHzImpedance-Lead Spacing0.331" (8.40mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeFundelPackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	80 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Ripple Current - High Frequency7.7 A @ 10kHzImpedance-Lead Spacing0.331" (8.40mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	10000 Hrs @ 125°C
ApplicationsAutomotiveApplications-Ripple Current - Low Frequency0.7A @ 10kHzRipple Current - High Frequency-Impedance-Lead Spacing0.331" (8.40mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-55°C ~ 125°C
IIRipple Current - Low Frequency-Ripple Current - High Frequency7.7A @ 10kHzImpedance-Lead Spacing0.331" (8.40mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency7.7A @ 10kHzImpedance-Lead Spacing0.331" (8.40mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseRadial, Can	Applications	Automotive
Impedance-Lead Spacing0.331" (8.40mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	-
Lead Spacing0.331" (8.40mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	7.7A @ 10kHz
Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.331" (8.40mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.984" Dia (25.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	1.654" (42.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

B41607A7228M9 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B41607A7228M9 Payment Methods



B41607A7228M9 Shipping Methods



If you have any question about B41607A7228M9, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com