



### **B41821A5108M000 Information**



For Reference Only

Part NumberB41821A5108M000ManufacturerEPCOS (TDK)

**Category** Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 1000UF 20% 25V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **B41821A5108M000 Specifications**

Manufacturer Part NumberB41821A5108M000ManufacturerEPCOS (TDK)CategoryCapacitorsPackageRadial, CanSeriesB41821Capacitance1000μFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)270 mOhm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency960mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)
CategoryCapacitorsPackageRadial, CanSeriesB41821Capacitance1000μFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)270 mOhm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency960mA @ 120HzRipple Current - High Frequency-Impedance-
PackageAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41821Capacitance1000μFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)270 mOhm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency960mA @ 120HzRipple Current - High Frequency-Impedance-
PackageRadial, CanSeriesB41821Capacitance1000μFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)270 mOhm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency960mA @ 120HzRipple Current - High Frequency-Impedance-
SeriesB41821Capacitance1000μFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)270 mOhm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency960mA @ 120HzRipple Current - High Frequency-Impedance-
Capacitance1000μFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)270 mOhm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency960mA @ 120HzRipple Current - High Frequency-Impedance-
Tolerance ±20%  Voltage - Rated 25V  ESR (Equivalent Series Resistance) 270 mOhm @ 120Hz  Lifetime @ Temp. 2000 Hrs @ 85°C  Operating Temperature -40°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 960mA @ 120Hz  Ripple Current - High Frequency -  Impedance -
Voltage - Rated25VESR (Equivalent Series Resistance)270 mOhm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency960mA @ 120HzRipple Current - High Frequency-Impedance-
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  2000 Hrs @ 85°C  Operating Temperature  -40°C ~ 85°C  Polarization  Polar  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  -  270 mOhm @ 120Hz  -40°C ~ 85°C  -40°C ~ 85°C  Polar  -40°C ~ 85°C  -40°
Lifetime @ Temp.  2000 Hrs @ 85°C  Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  -  2000 Hrs @ 85°C  -40°C ~ 85°C  Polar  Polar  -          -
Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  -40°C ~ 85°C  Polar  Polar  General Purpose  960mA @ 120Hz  -  Impedance
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 960mA @ 120Hz  Ripple Current - High Frequency -  Impedance
Applications General Purpose Ripple Current - Low Frequency 960mA @ 120Hz Ripple Current - High Frequency - Impedance -
Ripple Current - Low Frequency 960mA @ 120Hz  Ripple Current - High Frequency -  Impedance -
Ripple Current - High Frequency - Impedance -
Impedance -
Lead Spacing 0.197" (5.00mm)
1 0
Size / Dimension 0.394" Dia (10.00mm)
Height - Seated (Max) 0.866" (22.00mm)
Surface Mount Land Size -
Mounting Type Through Hole
Package / Case Radial, Can
Report errors?

#### **B41821A5108M000** Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### B41821A5108M000 Payment Methods



















## **B41821A5108M000 Shipping Methods**













If you have any question about B41821A5108M000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com