

# B41821A7336M7

#### B41821A7336M7 Information

Heisener.com	Part Number Manufacturer Category Description Package	B41821A7336M7 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 33UF 20% 35V RADIAL Radial, Can For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### B41821A7336M7 Specifications

Manufacturer EPCOS (TDK)   Category Capacitors   Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors   Package Radial, Can   Series B41821   Capacitance 33µF   Tolerance ±20%   Voltage - Rated 35V   ESR (Equivalent Series Resistance) 7 Ohm @ 120Hz   Lifetime @ Temp. 2000 Hrs @ 85°C   Operating Temperature -40°C ~ 85°C   Polarization General Purpose   Applications General Purpose   Ripple Current - Low Frequency -   Impedance -   Lead Spacing 0.098" (2.50mm)   Size / Dimension 0.197" Dia (5.00mm)   Height - Seated (Max) 0.472" (12.00mm)   Surface Mount Land Size -   Mounting Type Through Hole   Package / Case Kadial, Can	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41821Capacitance33µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)7 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.098" (2.50mm)Siz / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer Part Number	B41821A7336M7
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41821Capacitance33µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)7 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency105mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.098° (2.50mm)Siz / Dimension0.197° Dia (5.00mm)Height - Seated (Max)0.472° (12.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer	EPCOS (TDK)
PackageRadial, CanSeriesB41821Capacitance33µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)7 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRiple Current - Low Frequency-Impedance-Lad Spacing0.098" (2.50mm)Siz / Dimension0.197" Dia (5.00mm)Siz / Dimension0.472" (12.00mm)Height - Seated (Max)-Mounting Type-Package / CaseRadial, Can	Category	Capacitors
SeriesB41821Capacitance33μFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)7 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency105mA @ 120HzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.417" (12.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can		Aluminum Electrolytic Capacitors
Capacitance33µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)7 0hm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)7 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency105mA @ 120HzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Pokage / CaseRatial, Can	Series	B41821
Voltage - Rated35VESR (Equivalent Series Resistance)7 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency105mA @ 120HzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Pockage / CaseRadial, Can	Capacitance	33µF
Constraint7 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency105mA @ 120HzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.472" (12.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Pounting TypeRadial, Can	Tolerance	$\pm 20\%$
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency105mA @ 120HzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	35V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency105mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeFrough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	7 Ohm @ 120Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency105mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency105mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 85^{\circ}\mathrm{C}$
Ripple Current - Low Frequency105mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In a constraint of the second secon	Applications	General Purpose
Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	105mA @ 120Hz
Lead Spacing0.098" (2.50mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.098" (2.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.197" Dia (5.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.472" (12.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

#### B41821A7336M7 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### B41821A7336M7 Payment Methods





If you have any question about B41821A7336M7, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com