



B41821A8107M000 Information



For Reference Only

Part Number B41821A8107M000 Manufacturer EPCOS (TDK) Category

Capacitors

Aluminum Electrolytic Capacitors

CAP ALUM 100UF 20% 63V RADIAL **Description**

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B41821A8107M000 Specifications

Manufacturer Part NumberB41821A8107M000ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41821Capacitance100µFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency280mA @ 120Hz
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41821Capacitance100μFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral Purpose
PackageRadial, CanSeriesB41821Capacitance $100\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $63V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. $2000 \text{Hrs} @ 85^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral Purpose
PackageRadial, CanSeriesB41821Capacitance $100μF$ Tolerance $±20%$ Voltage - Rated $63V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. $2000 Hrs @ 85°C$ Operating Temperature $-40°C ~ 85°C$ PolarizationPolarApplicationsGeneral Purpose
SeriesB41821Capacitance $100\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $63V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. $2000 \text{ Hrs } @ 85^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral Purpose
Capacitance $100\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $63V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral Purpose
Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose
Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral Purpose
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose
Lifetime @ Temp. $2000 \text{Hrs} @ 85^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral Purpose
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose
Polarization Polar Applications General Purpose
Applications General Purpose
Ripple Current - Low Frequency 280mA @ 120Hz
Ripple Current - High Frequency -
Impedance -
Lead Spacing 0.197" (5.00mm)
Size / Dimension 0.394" Dia (10.00mm)
Height - Seated (Max) 0.532" (13.50mm)
Surface Mount Land Size -
Mounting Type Through Hole
Package / Case Radial, Can
Report errors?

B41821A8107M000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B41821A8107M000 Payment Methods





















B41821A8107M000 Shipping Methods













If you have any question about B41821A8107M000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com