

# B41821A8336M8

Request a Quote

#### B41821A8336M8 Information

Heisener.com	Part Number	B41821A8336M8	
	Manufacturer	EPCOS (TDK)	
	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 33UF 20% 63V RADIAL	
	Package	Radial, Can	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### B41821A8336M8 Specifications

ManufacturerEPCOS (TDK)CatagoryCapacitorsPackageAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41821Capacitance33µFTolerance±20%Voltage - Rated60hm @ 120HzESR (Equivalent Series Resistance)60hm @ 120HzDiperating Temperature2000 Hrs @ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency.Impedance.Lied Spacing0.197" (5.00mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size.Package / CaseKaila, Can		
CapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageB41821Capacitance33µFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)6 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency140mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Manufacturer Part Number	B41821A8336M8
Aluminum Electrolytic CapacitorsPackageRadial, CanPackageB41821Capacitance33µFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)60hm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationFolareal PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance0.197" (5.00mm)Siz / Dimension0.248" Dia (6.30mm)Siz / Dimension0.447" (12.00mm)Sirface Mount Land Size-Mounting TypeFolarealPackage / CaseStail, Can	Manufacturer	EPCOS (TDK)
PackageRadial, CanSeriesB41821Capacitance33µFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)6 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolariPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lad Spacing0.197" (5.00mm)Size / Dimension0.248" Dia (6.30mm)Size / Dimension0.472" (12.00mm)Surface Mount Land Size-Mounting TypeFurough HolePackage / CaseRadial, Can	Category	Capacitors
SeriesB41821Capacitance33µFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)6 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency140mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Package / CaseRatial, Can		Aluminum Electrolytic Capacitors
Capacitance33µFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)6 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency140mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Pokage / CaseRadial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)6 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency140mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Series	B41821
Voltage - Rated63VESR (Equivalent Series Resistance)6 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency140mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.428" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Package / CaseRatial, Can	Capacitance	33µF
Composition6 Ohm @ 120HzESR (Equivalent Series Resistance)6 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency140mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.472" (12.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeFarcage / CasePackage / CaseRadial, Can	Tolerance	$\pm 20\%$
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeAipple Current - Low Frequency140mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	63V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency140mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	6 Ohm @ 120Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency140mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency140mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 85^{\circ}\mathrm{C}$
Ripple Current - Low Frequency140mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
InInRipple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	140mA @ 120Hz
Lead Spacing0.197" (5.00mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.248" Dia (6.30mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.472" (12.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
Report chois.		Report errors?

#### B41821A8336M8 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### B41821A8336M8 Payment Methods





If you have any question about B41821A8336M8, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com