

B41821A9475M7

B41821A9475M7 Information

	Containance container	 B41821A9475M7 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 4.7UF 20% 100V RADIAL Radial, Can For the pricing/inventory/lead time, please contact	
	For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B41821A9475M7 Specifications

CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41821Capacitance4.7μFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)35 Ohm @ 120HzDiperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Package / CaseRadial, Can	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41821Capacitance4.7μFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)35 Ohm @ 120HzDiperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer Part Number	B41821A9475M7
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41821Capacitance4.7µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)35 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature4.0°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lad Spacing0.098" (2.50mm)Size / Dimension0.197" Dia (5.00mm)Size / Dimension0.472" (12.00mm)Height - Seated (Max)-Mounting TypeFinough HolePackage / CaseRadial, Can	Manufacturer	EPCOS (TDK)
PackageRadial, CanSeriesB41821Capacitance4.7µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)35 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature4.0°C ~ 85°CPolarizationGeneral PurposeRiple Current - Low Frequency-Impedance-Liad Spacing0.098" (2.50mm)Siz / Dimension0.197" Dia (5.00mm)Siz / Dimension0.472" (12.00mm)Height - Seated (Max)-Mounting Type-Package / CaseKadial, Can	Category	Capacitors
SeriesB41821Capacitance4.7µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)35 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can		Aluminum Electrolytic Capacitors
Capacitance4.7µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)35 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ingedance-Lead Spacing0.998°(2.50mm)Size / Dimension0.197° Dia (5.00mm)Height - Seated (Max)0.472° (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)35 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency45mA @ 120HzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Pokarge / CaseRatial, Can	Series	B41821
Voltage - Rated100VESR (Equivalent Series Resistance)35 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency45mA @ 120HzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Pockage / CaseRatial, Can	Capacitance	4.7µF
ESR 35 Ohm @ 120Hz ESR (Equivalent Series Resistance) 35 Ohm @ 120Hz ESR (Equivalent Series Resistance) 2000 Hrs @ 85°C Doperating Temperature -40°C ~ 85°C Polar Polar Applications General Purpose Ripple Current - Low Frequency 45mA @ 120Hz Nippedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Fhough Hole Package / Case Radial, Can	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency45mA @ 120HzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeRadia, Can	Voltage - Rated	100V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency45mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeFackage / CaseRadial, CanRadial, Can	ESR (Equivalent Series Resistance)	35 Ohm @ 120Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency45mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency45mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency45mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	45mA @ 120Hz
Lead Spacing0.098" (2.50mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.098" (2.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.197" Dia (5.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.472" (12.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

B41821A9475M7 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B41821A9475M7 Payment Methods





If you have any question about B41821A9475M7, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com