

B41827A8107M

Request a Quote

B41827A8107M Information

umber B41827A8107M	
facturer EPCOS (TDK)	
ory Capacitors Aluminum Electrolytic Capacitors	
ption CAP ALUM 100UF 20% 63V RADIAL	
ge Radial, Can	
For the pricing/inventory/lead time, please contact	
us	
E-mail: salesdept@heisener.com	
	Catcurer EPCOS (TDK) ory Capacitors Aluminum Electrolytic Capacitors ption CAP ALUM 100UF 20% 63V RADIAL ge Radial, Can For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B41827A8107M Specifications

ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41827Capacitance100µFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)-Operating Temperature2000 Hrs @ 85°COperating Temperature900 Hrs @ 85°CPolarizationGeneral PurposeApplicationsGoura (1 20 Hz)Ripple Current - High Frequency300mA @ 120 HzNipple Current - High Frequency-Lied Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm, 10.00m)Height - Seated (Max).51" (14.00mm, 10.00m)Surface Mount Land Size-Mounting TypeThrough Hole		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41827Capacitance100μFTolerance±20%6Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer Part Number	B41827A8107M
Adminum Electrolytic CapacitorsPackageRadial, CanSeriesB41827Capacitance100µFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency300mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer	EPCOS (TDK)
PackageRadial, CanSeriesB41827Capacitance100µFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature2000 Hrs @ 85°CPolarizationPolarApplicationsGeneral PurposeRiple Current - Low Frequency300mA @ 120HzRiple Current - High Frequency-Impedance-Liad Spacing0.197" (5.00mm)Size / Dimension0.551" (14.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Category	Capacitors
SeriesB41827Capacitance100µFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency300m A@ 120HzImpedance-Liad Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKaila, Can		Aluminum Electrolytic Capacitors
Capacitance100μFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ingedance-Lad Spacing0.197" (5.00mm)Size / Dimension0.551" (14.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKalia, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency300mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.591" (14.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Series	B41827
Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarPolarApplicationsGeneral PurposeRipple Current - Low Frequency300mA @ 120HzBrippe Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.591" (14.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Capacitance	100µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeApple Current - Low Frequency300mA @ 120HzBippe Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeFracupationPackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency300mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.551" (14.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeRidi, CanPackage / CaseRadial, Can	Voltage - Rated	63V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 300mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Radia, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency300mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency300mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency300mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	300mA @ 120Hz
Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.394" Dia (10.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.551" (14.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

B41827A8107M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B41827A8107M Payment Methods





If you have any question about B41827A8107M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com